

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	330		Shale & siltstone				<u>Geological Markers</u>
	760		SS				Chinle 330
	885		Dolo				Santa Rosa 760
	915		SS				Day-Creek 885
	1067		Anhy & Dolo				White Horse 915
	1180		SS				Blaine 1067
	1280		SS, siltstone & shale				Glorieta 1180
	1558		Anhy & Dolo.				Yeso 1280
	1590		Shale, SS & Granite Wash				Cimarron 1558
	2538		Dolo.				Sangre de Cristo 1590
	2755		Pink Granite				Miss. 2538
							Ordovician 2605
							Pre Cambrian Granite 2755
Halliburton DST No. 1 - 2560' to 2650' (Miss.)							
Opened 10 min 1st flow with strong blow of air. CI 30 min. Open 60 min 2nd flow W/							
weak blow of air. Rec 1400' of water cut drlg mud. - No shows of oil or gas. HP in							
1237 psi. 10 min 1st flow 135 - 672 psi. 30 min ESIP 672 psi. 60 min 2nd flow 672							
psi. 30 min FSIP 672 psi. HP out 1192 psi. BHT 925 F.							