NO. OF COPIES MECEIVED	• •
<del></del>	భు
	Form C-103
DISTRIBUTION	Supersedes Old C-102 and C-103
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE	5a. % dicate Type of Lease
U.S.G.S.	Sate Fee:
OPERATOR	State Oil & Gas Lease No.
Please consider this information comfidential	*
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT _" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL GAS WELL OTHER- Dry Hole - Plugged and abandoned	7, Unit Agreement Name
2. Name of Operator  Gulf Oil Corporation	8 Marca of Leave Nation
3. Address of Operator	Joila Land & Cattle Co. 9. Well No.
Box 670, Hobbs, New Mexico 88240	1
UNIT LETTER M , 575 FEET FROM THE South LINE AND 566 FEET FROM	10. Field and Pool, or Wildcat Wildcat
THE WOST LINE, SECTION 22 TOWNSHIP 31-W RANGE 34-E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
16 5276' GL	Union
Check Appropriate Box To Indicate Nature of Notice, Report or Other Notice of Intention to:  Subsequent	ner Data FREPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	PLUS AND ABANDONMENT
PULL OR ALTER CASING CAMENT JOB CHANGE PLANS CASING TEST AND CEMENT JOB	1 1
OTHER	
work) SEE RULE 1103.  4083' TD.  Drilled 7-7/8" hole to TD at 4083'. Drill pipe stuck at 4050'. I	
drill collars, stabiliser and 7-7/8" bit in hole. Obtained permissic Kapteina and plugged and abandoned as follows: Spotted 47 sack cemer 3838' to 3677'; 40 sack cement plug No. 2 from 1825' to 1685'; 13 sa 3 from 347' to 327', across 8-5/8" shoe at 337' and 10 sack cement plug to surface. Installed dry hole marker. Plugged and abandoned April	on from Mr. J. E. nt plug No. 1 from nok cement plug No. lug No. 4 from 30'
Kapteins and plugged and abandoned as follows: Spotted 47 sack comer 3838' to 3677'; 40 sack coment plug No. 2 from 1825' to 1685'; 13 sa 3 from 347' to 327', across 8-5/8" shoe at 337' and 10 sack coment plug No. 2 from 1825' to 1685'; 13 sa 3 from 347' to 327', across 8-5/8" shoe at 337' and 10 sack coment plug to surface. Installed dry hole marker. Plugged and abandoned April 18. Thereby certify that the information above is true and complete to the best of my knowledge and belief.  ORIGINAL SIGNED BY	on from Mr. J. E.  It plug No. 1 from  Nok cement plug No.  Lug No. 4 from 30'  5, 1970
drill collars, stabiliser and 7-7/8" bit in hole. Obtained permissic Kapteins and plugged and abandened as follows: Spotted 47 sack cemer 3838' to 3677'; 40 sack cement plug No. 2 from 1825' to 1685'; 13 sa 3 from 347' to 327', across 8-5/8" shoe at 337' and 10 sack cement plug to surface. Installed dry hole marker. Plugged and abandened April	on from Mr. J. E. nt plug No. 1 from nok cement plug No. lug No. 4 from 30'