## STATE OF NEW MEXICO

ENERGY AND MINERALS DEPARTME	N)	PTM	DEPAR	MMERALS.	ANO	ENERGY
------------------------------	----	-----	-------	----------	-----	--------

40. 6" (nmits #ttfivts	1	
DISTRIBUTION		
SANTA FE	17	
FILE	V	
U.3.G.5.		
LAND OFFICE		
		1

## OIL CONSERVATION DIVISION

P. O. BOX 2088

Form C-103 -

SANTA FE, NEW MEXICO 87501	Revised 10-1-7.
FILE	Su. Indicate Type of Lease
LAND OFFICE	State Fee
0767ATOA	5. State Oil & Gas Lease No.
han and the same a	
SUNDRY NOTICES AND REPORTS ON VELLS	
1. OIL	7. Unit Agreement Name BDCDGU
Amoco Production Company Oil CONSESSES BASES	BDCDGU 2034
1. Address of Operator SANTA FE	9. Weil No.
P. O. Box 68, Hobbs, New Mexico 88240	361
4. Location of Well	10. Field and Pool, or Wrideat
UNIT LETTER 0 , 660 FEET FROM THE SOUTH LINE AND 1980 FEET FROM	Und. Tubb
Fact 26 20 N 24 E	
THE East LINE, SECTION 36 TOWNSHIP 20-N RANGE 34-E NMPM.	
15. Elevation (Show whether DF, RT, CR, etc.)	12. County
4750' RDB	Union
Check Appropriate Box To Indicate Nature of Notice, Report or Otl	her Data
NOTICE OF INTENTION TO: SUBSEQUENT	REPORT OF:
PERFORM REMEDIAL WORK X	ALTERING CASING
TEMPORARILY ABANDON COMMENCE ORILLING OPNS.  PULL OR ALTER CASING CASING TEST AND CEMENT JQB	PLUG AND ABANDONMENT
OTHER	
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	estimated date of starting any proposed
Moved in service unit 9-1-82. Pulled tubing, packer, tailpipe, and sea retrievable bridge plug at 2011' and pumped sand on top. Perforated at 980' with 3-1/8" gun. Set a packer at 663'. Circulated 40 bbl 2% 63 bbl cement slurry. Circ. 5 bbl cement slurry and displaced cement water. Pulled packer. Drilled out cement 844'- 990'. Set a packer at 20 bbl cement slurry with 2% CACL. Displace with 5 bbl 2% KCL water. drilled out cement 865'-998'. Set a packer at 772' and pumped 35 sack with 5 bbls KCL water. Pulled packer and drilled out cement 800'-990' the retrievable bridge plug and pulled the bridge plug. Ran plasticoanipple, and 2-3/8" tubing. Pumped 25 bbl inhibited water with packer annulus with 5 bbl inhibited water. Ran swab. Moved out service unit currently shut-in.	4 right angle shots KCL water. Pumped with 5 bbl 2% KCL at 772' and pumped Pulled packer and as Thixset. Displaced . Washed sand off of ated packer, seating set at 2136'. Loaded by 9-15-82. Well is
O+2-NMOCD,SF 1-HOU 1-SUSP 1-CLF 1-Amerada 1-UGI 1-Citi 1-CO2 in Action 1-Excelsior 1-Sun. Tex.	es Serv. 1-Conoco
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Cathy L. Forman TITLE Assist. Admin. Analyst	DATE 9- 20-82
Carl Illung DISTRICT SIN EDVISOR	0ATE 7/83 /82