

|                        |  |
|------------------------|--|
| NO. OF COPIES RECEIVED |  |
| DISTRIBUTION           |  |
| SANTA FE               |  |
| FILE                   |  |
| U.S.G.S.               |  |
| LAND OFFICE            |  |
| OPERATOR               |  |

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

RECEIVED  
JUL 18 1980  
OIL CONSERVATION DIVISION  
SANTA FE, NEW MEXICO

Form C-103  
Revised 10-1-78

|                                |                                         |
|--------------------------------|-----------------------------------------|
| 5a. Indicate Type of Lease     | Fee <input checked="" type="checkbox"/> |
| 5b. State Oil or Gas Lease No. |                                         |

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

|                                                                                                                                                                                                          |                                                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <u>CO<sub>2</sub> gas well</u>                                                                                             | 7. Unit Agreement Name                           |
| 2. Name of Operator<br><u>Amerada Hess Corporation</u>                                                                                                                                                   | 8. Farm or Lease Name<br><u>Burner</u>           |
| 3. Address of Operator<br><u>Drawer D, Monument, New Mexico 88265</u>                                                                                                                                    | 9. Well No.<br><u>1</u>                          |
| 4. Location of Well<br>UNIT LETTER <u>K</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM<br>THE <u>West</u> LINE, SECTION <u>9</u> TOWNSHIP <u>30N</u> RANGE <u>31E</u> NMPM. | 10. Field and Pool, or Wildcat<br><u>Wildcat</u> |
| 15. Elevation (Show whether DF, RT, GR, etc.)<br><u>6052' GR</u>                                                                                                                                         | 12. County<br><u>Union</u>                       |

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER Progress ☒

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-4-80 - Drld. rat hole & set 13-3/8" 48# conductor csg. at 53'. Spudded 12-1/4" hole at 4:00 AM 6-8-80. Drld. 12-1/4" hole to 335' w/water. Set 9-5/8" 36# K-55 csg. at 330' & cemented w/200 sks. Class C cement mixed 3% CaCl. Circ. out 20 sks. WOC & drld. plug, float & 15' of cement & tested to 1000#. Held OK. Drld. cement, float shoe & 6' of 8-3/4" hole. Blew hole dry & drld. 8-3/4" hole fr. 335' to 2007' w/air. Mudded up. Ran CNL/Densilog, Minilog, GR & DIL Focus log w/GR & SP. Set 7" 20# K-55 csg. at 2007' & cemented w/225 sks. Class H cement w/additives. Est. top of cement at 1150' outside 7" csg. WOC. Drld. cement & float & tested to 1000# f/30 min. Held OK. Drld. cement & shoe, circ. hole clean & blew hole dry. Drld. 6-1/4" hole fr. 2007' to 2921' w/air. Mudded up. Dresser Atlas ran DIL Focus log w/GR, Densilog/CNL/Minilog. Drld. 6-1/4" hole to 3728'. Dresser Atlas ran DIL Focus log w/GR & CNL/Densilog w/Minilog. Halliburton spotted 75 sks. Class H cement plug in 6-1/4" hole fr. 2060' to 1700'. WOC & checked top of cement at 1705'. Drld. cement to 1900', circ. hole clean, installed tbq. head & rigged down drlg. equipment.

Waiting on completion equipment.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.B. Fisher TITLE Supv. Adm. Ser. DATE 7-10-80

APPROVED BY Carl Illing TITLE SEAL OF THE OIL CONSERVATION DIVISION DATE 7/22/80

CONDITIONS OF APPROVAL, IF ANY: