


STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501



Form C-103  
Revised 10-1-78

OIL CONSERVATION DIVISION  
SANTA FE

Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- CO <sup>2</sup> Gas Well		7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name Wilkinson
3. Address of Operator Drawer D, Monument, New Mexico 88265		9. Well No. 1
4. Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 4 TOWNSHIP 29N RANGE 31E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 6049' GR		12. County Union

10. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Progress <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drld. conductor hole to 35' & set 13-3/8" conductor pipe & cemented w/5 yards Ready Mix. Spudded 12-1/4" hole @ 4 PM 7-1-80. Drld. 12-1/4" hole to 376' & set 9-5/8" 36# csg. at 367' & cemented w/300 sks. Class "H" cement mixed w/3% CaCl. Circ. out 10 sks. cement, WOC & drld plug, cement & shoe & tested w/1000#. Held OK. Drld. 8-3/4" hole fr. 376' to 3450' w/air. Hole sluffing off. Mixed mud and conditioned hole. Drld. fr. 3450' to 3960' drld. w/mud. Attempted to log. No results. Wash, ream & condition hole. Ran 7" 20# csg. set @ 1138' & cemented w/400 sks. cement w/additives. WOC & drld. cement & shoe. Washed & reamed & circ. to condition hole @ 1160'. Set cement retainer in 7" csg. @ 1100' & pumped 100 sks. Class "H" cement mixed 2% CaCl. Pulled out of retainer & reversed out 1/2 bbl. cement. Cut off csg., installed tbg. head & released drlg. rig. 12 Noon 7-22-80

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. A. Fisher TITLE Supv. Adm. Ser. DATE 8/21/80

APPROVED BY Carl W. Wray TITLE \_\_\_\_\_ DATE 9/22/80

CONDITIONS OF APPROVAL, IF ANY: