

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

OIL CONSERVATION DIVISION

MAY 23 1980

Form C-103  
Revised 10-1-78

Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
3. State Oil & Gas Lease No. LG-2020	
7. Unit Agreement Name	
8. Farm or Lease Name Excel	
9. Well No. 1	
10. Field and Pool, or Wildcat Wildcat	
12. County Union	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER: Carbon Dioxide & Hydrocarbons
2. Name of Operator HNG FOSSIL FUELS COMPANY
3. Address of Operator P. O. Box 1188, Houston, Texas - 77001
4. Location of Well UNIT LETTER F 1939 FEET FROM THE North LINE AND 3300 FEET FROM THE East LINE, SECTION 1 TOWNSHIP 31N RANGE 32E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

5125' GR 5135' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOBS ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

May 11, 1980 - Well Spudded.

May 12, 1980 - TD=283': Set 232' of 9-5/8" O.D., 32.30#, H-40, S.T. & C, R-3 casing @ 232' KB. Cemented with 175 sacks Class "H" cement with 2% CaCl<sub>2</sub>. Cement fully circulated. W.O.C. 30 hours. Continued drilling  
May 13, 1980. (Hole Size: 12-1/4")

May 17, 1980 - TD=2475': Set 2,447' of 7" O.D., 20.00#, K-55, S.T. & C, R-3, casing @ 2,447' KB. Cemented with 125 sacks Class "H" cement with 2% CaCl<sub>2</sub> and 2% NaCl added. W.O.C. (Hole Size: 8-3/4")

May 19, 1980 - Rig released.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Richard A. Finch

TITLE Chief Production Clerk

DATE May 21, 1980

APPROVED BY Carl Young

TITLE State Engineer

DATE 5/28/80

CONDITIONS OF APPROVAL, IF ANY: