## Submit 3 Copies to Appropriate

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

D	Sinct Office														
<u>DI</u> P.0	STRICT I D. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION 2040 Pacheco St.			<b>WELL API NO.</b> 30–059–20059										
	STRICT II O. Drawer DD, Artesia, NM 88210	Santa Fe, NM		M 87505	5. Indicate Type of Lease										
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410					6. State Oil & C	STATE	PEE A								
	· · · · · · · · · · · · · · · · · · ·		·			<i></i>	~~~								
		FICES AND REPORTS (													
( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN DIFFERENT RESERVOIR. USE "APPLICATION FOR PE (FORM C-101) FOR SUCH PROPOSALS.)					7. Lease Name or Unit Agreement Name										
1.	Type of Well: OIL GAS WELL WELL	]	CO2	)	BDCDGU-19	134	•								
2		OTHER		•	8. Well No.										
	Amoco Production Com	pany			8. Well No. 221										
3.	Address of Operator				9. Pool name or Wildcat										
4.	PO Box 606, Clayton, Well Location	NM 88415			Tubb.	<del></del>									
7.		Feet From The Nort	h	Line and16	52 Feet Fro	m TheWest	Line								
	Section 22	Township 19N		inge 34E	NMPM Union		County								
		10. Elevation (Show		DF, RKB, RT, GR, etc.)											
<u> </u>	Charle	Appropriate Box to Inc	4762			<u> </u>									
11.		•	•	•											
	NOTICE OF IN	TENTION TO:		SUE	SEQUENTI	REPORT OF:									
ER	FORM REMEDIAL WORK	PLUG AND ABANDON		REMEDIAL WORK		ALTERING CASING	g 🗌								
EM	IPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT												
ULL OR ALTER CASING				CASING TEST AND CEMENT JOB											
ТН	ER: Run Poly Liner	100	X	OTHER:											
	MIRUSU		İ	I INTO RUN POLS	LINER TO T	OP OF PKR.									
		25" BLANKING PLG	UNIT; RUN POLY LINER TO TOP OF PKR; FISH DRILL COLLARS FROM POLYLINER												
	PROFILE			W/TBG FUSE ON WELLHEAD FLANGE;											
BLEED TBG TO 0 PSI NUBOP RELEASE ON/OFF TOOL				INSTALL SS B-1 ADAPTER & MASTER VALVE; INSTALL METER RUN; RU											
										N, REC AS MUCH FLU	LUBRICATOR & FISH BLANKING PLUG; RETURN WELL TO PRODUCTION; RDMOSU				
	AS POSSIBLE	ii, ide iii iiiocii i bo													
	LAYDOWN FG TB	G		OPTION #2											
RUN POLYBORE GAUGE RING  OPTION #1  IF GAUGE RING GOES & LOOKS OK WHEN PULLED: RUN 10-3 1/8" DRILL COLLARS (COLLARS EQUIPPED WITH 2 7/8" PAC BOX ON TOP); RIG UP ROLLER REDUCTION				IF GAUGE RING DOES NOT MAKE IT TO PKR DEPTH OR COMES OUT WITH SIGNS OF CSG DAMAGE, RERUN 3 1/2" FG PRODUCTION TBG; LATCH ON TO PKR; FISH BLANKING PLUG; PRESS TEST CSG & PKR TO 500 PSI; RETURN WELL TO											
									511 101 J, ING U	I KOLLEK KEDUCHO	,T A	PRODUCTION; RI	•	WELL IO	
								hea	reby certify that the information above is true	and complete to the best of my know	viedge and b	ælia.			
								, MOI	NATURE Billy E.	Frulue)	1717	Field Foreman	ı	11/2/9	6
										Prichard				TELEPHONE NO. 3	74–3053
	· - · · · - · - · - · - · - · - · - · -					IELEFTIONE NO.									

(This space for State Use),

DISTRICT SUPERVISOR DATE 11-21-96

CONDITIONS OF APPROVAL, IF ANY