

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.	30-059-20102
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	
BDCDGU-1934	
8. Well No.	211
9. Pool name or Wildcat	Tubb

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER CO2	
2. Name of Operator Amoco Production Company	
3. Address of Operator PO Box 606, Clayton, NM 88415	
4. Well Location Unit Letter <u>G</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>1874</u> Feet From The <u>East</u> Line Section <u>21</u> Township <u>19N</u> Range <u>34E</u> NMPM Union County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4828' GR	

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: Run Poly Liner ☒

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

MIRUSU  
RUN & SET 1.625" BLANKING PLG IN  
PROFILE  
BLEED TBG TO 0 PSI  
NUBOP  
RELEASE ON/OFF TOOL  
SWAB CSG DOWN, REC AS MUCH FLUID  
AS POSSIBLE  
LAYDOWN FG TBG  
RUN POLYBORE GAUGE RING

**OPTION #1**

IF GAUGE RING GOES & LOOKS OK WHEN  
PULLED: RUN 10-3 1/8" DRILL COLLARS  
(COLLARS EQUIPPED WITH 2 7/8" PAC BOX  
ON TOP); RIG UP ROLLER REDUCTION

UNIT; RUN POLY LINER TO TOP OF PKR;  
FISH DRILL COLLARS FROM POLYLINER  
W/TBG FUSE ON WELLHEAD FLANGE;  
INSTALL SS B-1 ADAPTER & MASTER  
VALVE; INSTALL METER RUN; RU  
LUBRICATOR & FISH BLANKING PLUG;  
RETURN WELL TO PRODUCTION;  
RDMOSU

**OPTION #2**

IF GAUGE RING DOES NOT MAKE IT TO  
PKR DEPTH OR COMES OUT WITH SIGNS  
OF CSG DAMAGE, RERUN 3 1/2" FG  
PRODUCTION TBG; LATCH ON TO PKR;  
FISH BLANKING PLUG; PRESS TEST CSG  
& PKR TO 500 PSI; RETURN WELL TO  
PRODUCTION; RDMOSU

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Billy E. Prichard TITLE Field Foreman DATE 11/2/96  
TYPE OR PRINT NAME Billy E Prichard TELEPHONE NO. 374-3053

(This space for State Use)

APPROVED BY Ry E. Johnson DISTRICT SUPERVISOR DATE 11-21-96  
CONDITIONS OF APPROVAL, IF ANY: