				an an the second se			
NO. OF COPIES RECEIVED				i i generatio			
		UEVICO OU COUC	DVITION CONVERTS	1.1. 1.1.1. 1.1.1			
DISTRIBUTION		MEXICO OIL CONSE	Form C-101 Revised 1-1-65				
			Sec. S	• .		Ver at Lours	
TILE			un en	SA. Tidleate Type of Lease			
J.S.G.5.					S. State off &	ر <u></u> ا	
AND OFFICE					of of the total t	on 1,0130 Ho.	
DPERATOR		API # 30-050	9-20135		mmm	mmm	
A DDL IC AT	ION FOR PERMIT TO					HHHHH	
AFT LICAT		DRIEC, DEET ER,	OR I LUO DAGR		7. Unit Agreen	ent ligne	
-						ome Carbon Gas Unit	
DRILL	<u>^</u>	DEEPEN	PLUG	BACK	9. Larin or L.ga	ee Norge	
OIL GAS WELL	X CO2 or mean		ZONE X	TONE	Bravo Do Dioxide	ome Carbon Gas Unit 18	
Transe of Operator	002 0 HE4		2011. 14.3		9. Well No.	dus onre re	
Amoco Production	Company				14	G	
Address of Operator		10, Field and Pool, or Wildoat					
P. O. Box 68,	Hobbs, NM 88240				Und. Tubb		
Location of Well	TTER G LOC	ATED 1980	FEET FROM THE NORT	h LINE	MUUUU	MANIN	
			<u></u>			HHHHH	
.» 1980 PEFT FU	East un	FOFSEC. 14	TWP. 18-N RGE.	34-E MARM	VIIIIII	MANN	
THUR THUR W	IIIIIIIIIIIII	HHHHH	(INNA)	HHHH	12. County	- 7//////	
					Union		
UHHHHH	MMMMM	HHHHH	MAMMAM	HHHH	HHHH	HHHHH	
11111111111111111111111111111111111111			19. Frojesou Doj th	19A. Formatio	n 2	U. Hovery or C.T.	
UMMMM	HHHHHHH	HHHHH	2950'	Tubb	,	Rotary	
. z lowations (Show schether L	(1, KI, etc.) = 121A. Kina	& Status y lug, Bend	21B. Drilling Contractor			ate Work will start	
4766' GL	Blan	ket-on-file	NA			4-17-81	
3.	F	ROPOSED CASING AN	D CEMENT PROGRAM				
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOO	T SETTING DEPTH	H SACKS OF	F CEMENT	EST. TOP	
· · · · · · · · · · · · · · · · · · ·	8-5/8"	24#		Cj	irc. Surf.		
12-1/4"			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
7-7/8"	5-1/2"	n the Tubb for	2950'		<u>to 8-5/8'</u> 		
7-7/8" Propose to drill run and evaluate production. MUD PROGRAM: 0'	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial	n the Tubb for stimulate as and fresh wat mud and brine	mation. After necessary in at er with minimum p	 reaching tempting roperties	TD logs wi commercial	11 be	
7-7/8" Propose to drill run and evaluate production. MUD PROGRAM: 0'	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial	n the Tubb for stimulate as and fresh wat mud and brine conditions.	er with minimum p	reaching tempting	TD logs wi commercial for D BF NOTH	ill be	
7-7/8" Propose to drill run and evaluate production. MUD PROGRAM: 0'	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole	n the Tubb for stimulate as and fresh wat mud and brine conditions.	er with minimum p	reaching tempting	TD logs wi commercial for D BF NOTH	ill be	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700'	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole ched	n the Tubb for stimulate as and fresh wat mud and brine conditions.	mation. After necessary in at er with minimum p	reaching tempting	TD logs wi commercial for D BF NOTH	ill be	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700' BOP Program Attac	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole ched	n the Tubb for stimulate as and fresh wat mud and brine conditions.	er with minimum p	reaching tempting	TD logs wi commercial for D BF NOTH	ill be	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700' BOP Program Attac Gas is not dedice	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole ched	n the Tubb for stimulate as and fresh wat mud and brine conditions. OIL COMME WITHEN 2	er with minimum p RVATION COMM 24 HOURS OF 55	reaching tempting roperties ISSION TO GUINNING	TD logs wi commercial for D BE NOTH OPERATIO	ill be	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700' BOP Program Attac Gas is not dedice 0+2-NMOCD, SF	5-1/2" and equip well i d. ?erforate and -700' Native mud -TD Commercial safe hole ched ated. 1-Hou 1-Susp	n the Tubb for stimulate as and fresh wat mud and brine conditions. OIL COMPS WITHIN 2 1-BD	APPROVAL VAUD F FEILIT CATEGO	reaching tempting roperties ISSION TO GINNING	TD logs wi commercial for D BE NOTH OPERATIO DAYS B/ VAY	III be IED NS	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700' BOP Program Attac Gas is not dedice 0+2-NMOCD, SF	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole ched ated. 1-Hou 1-Susp	n the Tubb for stimulate as and fresh wat mud and brine conditions. OIL COMPS WITHIN 1-BD	APPROVAL VAUD F FERMIT CATEGORIES	reaching tempting roperties ISSION TO GINNING	TD logs wi commercial for D BE NOTH OPERATIO DAYS B/ VAY	III be IED NS	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700' BOP Program Attac Gas is not dedice 0+2-NMOCD, SF	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole ched ated. 1-Hou 1-Susp	n the Tubb for stimulate as and fresh wat mud and brine conditions. OIL COMPS WITHIN 1-BD	APPROVAL VAUD F FERMIT CATEGORIES	reaching tempting roperties ISSION TO GINNING	TD logs wi commercial for D BE NOTH OPERATIO DAYS B/ VAY	III be IED NS	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700' BOP Program Attac Gas is not dedice 0+2-NMOCD, SF Above space descenter reby settly that the informa-	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole ched ated. 1-Hou 1-Susp	n the Tubb for stimulate as and fresh wat mud and brine conditions. OIL COILS WITHER 2 1-BD	APPROVAL VALID F FEILLIT CALLSA UNLESS DRILLI on Proug pace, sive para	reaching tempting roperties ISSION TO CONTRO OR 180 (0 - 21- IG UNDERV	TD logs wi commercial for D BE NOTH OPERATIO DAYS 8/ VAY	TED NS	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700' BOP Program Attac Gas is not dedice 0+2-NMOCD, SF	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole ched ated. 1-Hou 1-Susp	n the Tubb for stimulate as and fresh wat mud and brine conditions. OIL COILS WITHER 2 1-BD	APPROVAL VAUD F FERMIT CATEGORIES	reaching tempting roperties ISSION TO CONTRO OR 180 (0 - 21- IG UNDERV	TD logs wi commercial for D BE NOTH OPERATIO DAYS B/ VAY	TED NS	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700' BOP Program Attac Gas is not dedice 0+2-NMOCD, SF Above space descenter reby settly that the informa-	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole ched ated. 1-Hou 1-Susp	n the Tubb for stimulate as and fresh wat mud and brine conditions. OIL COILS WITHER 2 1-BD	APPROVAL VALID F FEILLIT CALLSA UNLESS DRILLI on Proug pace, sive para	reaching tempting roperties ISSION TO CONTRO OR 180 (0 - 21- IG UNDERV	TD logs wi commercial for D BE NOTH OPERATIO DAYS 8/ VAY	TED NS	
7-7/8" Propose to drill run and evaluated production. MUD PROGRAM: 0' 700' BOP Program Attac Gas is not dedice 0+2-NMOCD, SF ABOVE SPACE DESCRIPTION ereby settly that the Intermedian	5-1/2" and equip well i d. Perforate and -700' Native mud -TD Commercial safe hole ched ated. 1-Hou 1-Susp	n the Tubb for stimulate as and fresh wat mud and brine conditions. OIL COMPA WITHIN 1-BD	APPROVAL VALID F FEILLIT CALLSA UNLESS DRILLI on Proug pace, sive para	reaching tempting roperties SSION TO GINNING OR 180 (0 - 2(- CONDERV	TD logs wi commercial for D BE NOTH OPERATIO DAYS 8/ VAY	TED NS	

NEW MEXICO OIL CONSERVATION COMMISSION • WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-102 Supersedes C-128 Effective 1-1-65

. . •

N 1975 M 2

		All distances mus	t be from the	euter boundarie	s of the Section	a <u>n</u>	11 - 13 54	1024	
Operator AMOC	0		Levan	Bravo [Dome CO2	Gas Unit	1	^{≥11} №. 1834 14	+1G
Unit Letter G	Section 14	Township T18N	18	mue R34E	of capity.	UNION	₩, ₩, <u>₩, </u> , , , , , , , , , , , , , , , , , ,		
Actual Pootace Loca 1980		OR TH	1	980	I	EAST			
Ground Level Elev.	Freducing For		[frees]		teet monthe		line Dedicated		
47 66		ubb	·····		i. Tubb			160	Acres
1. Outline the	acreage dedica	ted to the subject	t well by	colored pene	il or hachur	e marks on th	ne plat be	low.	
2. If more tha interest and	n one lease is Froyalty).	dedicated to the	well, outli	ne each and	identify the	ownership th	nereof (bo	oth as to v	vorking
3. If more than dated by co	i one lease of d mmunitization, u	ifferent ownership nitization, force-p) is dedica booling.etc	ted to the wo ?	ell, have the	interests of	all owne	ers been c	onsoli-
Yes [No If an	iswer is "yes," ty	pe of cons	olidation		······			
If answer is this form if	s "no?" list the onecessary.)	owners and tract	description	s which have	e actually be	een consolida	ited. (Us	e reverse	side of
No allowabb forced-pooli sion.	e will be assigne ng, or otherwise)	d to the well unti or until a non-sta	l all intere ndard unit,	sts have bee eliminating	n consolida such interes	ted (by com ts, has been	munitizat approved	ion, uniti by the C	zation, ommis-
	i	<u> </u>	1				CERTIFI	CATION	
			<i>980</i>			tained her best of my	ein is true	the informat and complet and belief.	
			den	1980		Company		avið al <u>vst (</u>	
	ł		•	l	. 1	Amoco F	roduct	<u>ion Com</u>	pany
	1	1		1			4-16	-81	
		,				shown on t notes of a under my s is true an	his plat wa ictual surve iupervision,	t the well f s plotted fro eys made by and thor th to the hest	om field / me or resame
				····		APRI Otto Surveye Negl torod P and or Land	rotessional	1981 Lalle Engineer	
						N.M.C.	S.NO	े - रे रे र	* +
0 330 660 90					wasi	Certifiente 15	02 5311		
0 330 660 90	1320 1650 118-	2310 2640	2001 150	0 1:00	500 <u>0</u>	<u>i</u>			12

ATTACHMENT "B" NOTES

- Blow-out preventers and master valve to be fluid operated and oil fittings must be in good condition, 3,000# 4.P. (6,000 p.s.i. test), minimum.
- 2. Equipment through which bit must pass shall be as large as the inside diameter of the casing that is being drilled through.
- 3. Nicple above blow-out preventer shall be same size as casing being drilled through.
- 4. Kelly cock required, 3,000# W.P. (5,000 p.s.i. test) minimum.

 OMSCO or comparable safety valve must be available on rig floor at all times with proper connection or sub, 3,000# W.P. (6,000 p.s.i. test), minimum.

 Blow-out preventers and master valve while drilling intermediate hole to 6000' may be 2,000# W.P. (4,000 p.s.i. test), minimum.

- 7. Choke assembly, beyond second valve from cross, may be positioned (Optional) outside of derrick foundation.
- Spool or cross may be climinated if connections are available in the lower part of the blow-out preventer body.
- 9. Plug valves gate valves are optional. Valves shown as 2" are minimum size.
- Casing head and casing head spool, including attached valves, to be furnished by Amoco.
- 11. Rams in preventers will be installed as follows: When drilling, use: When r

Top Preventer - Drill pipe rams Bottom Preventer - Blind rams or

master valve

When running casing, use: Top Preventer – Casing rams

Bottom Preventer - Blind rams or master valve



BLOWOUT PREVENTER HOOK-UP

PLOCO FROM TONT CONTRACT

EXHIBIT D-I MODIFIED