Submit 3 Copies	State of New Mexico		Form C-103
to Appropriate	Energy, Minerals, and Natural Resources Department		Revised 1-1-89
District Office			
OIL CONSERVATION DIVISION		WELL API NO.	
P.O. Box 1980, Hobbs, NM 88240	P.O. Box 2088		30-059-20159
DISTRICT II	Santa Fe, New Mexico 87504-2088		5. Indicate Type of Lease
P.O. Drawer DD, Artesia, NM 88210		STATE FEE	
DISTRICT III			6. State Oil & Gas Lease No.
1000 Rio Brazos Rd., Aztec, NM 87410			
SUNDRY	NOTICES AND REPORTS ON WI	FILS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"			7. Lease Name or Unit Agreement Name
(FORM C-101) FOR SUCH PROPOSALS.)			224/22242 202 242 1447
1. 1)pc s. 150			BRAVO DOME CO2 GAS UNIT
OIL GAS WELL WEL		CO2	
2. Name of Operator			8. Well No.
AMOCO PRODUCTION COMPANY			2431-361M
3. Address of Operator 9.			9. Pool name or Wildcat
P.O. Box 303, AMISTAI	D, NEW MEXICO 88410		BRAVO DOME CO2 GAS UNIT
4. Well Location			
Unit Letter M : 990	Feet From The South	Line and 990	Feet From The West Line
Section 36	Township 24N	Range 31E NMP	PM Union County
	10. Elevation (Show wheth	ser DF. RKB, RT, GR. etc.)	
	5597	GR	
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
	<u> </u>		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK			ALTERING CASING
TEMPORARILY ABANDON	EMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS		PLUG AND ABANDONMENT X
PULL OR ALTER CASING	ALTER CASING CASING TEST AND CEMENT JO		JOB
OTHER:		OTHER:	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)			
SEE RULE 1103			
6/23/00			
MIRUSU, kill well with fresh water, NUBOP, release packer, lay down production tubing and packer, run cast iron bridge			
plug with wireline, set CIBP at 2,359 feet, run workstring, tag CIBP at 2,359, displace casing with corrosion inhibited fluid,			
pressure test casing to 500 psi, cap CIBP with 5 sacks of class C cement from 2359' - 2310', pull workstring to 2,000 feet,			
spot 15 sacks of cement from 2000' - 1852', pull workstring to 30 feet, SDON.			
6/24/00 Fill casing with cement, NDBOP, RDMOSU, cut off wellhead, install PXA marker, cut off well anchors and clean location.			
Fill casing with cement, NDBOP, RDMOSO, cut on weilhead, install PXA marker, cut on weil anchors and clean location.			
I hereby certify that the information above in	s true and complete to the pest of my knowledg	e and celief.	
$YY \cup V$	1/2	Leid Foreman	DATE 6-29-2000
			TELEPHONE NO (505) 374-3010
TYPE OR PRINT NAME Sanny J. Hoto	7///		1222710NE NO (303) 374-3010
(This space for State Use) APPROVED BY DATE 7/13/00			
CONDITIONS OF APPROVAL, IF ANY	70,000	THE REPORT OF THE PARTY OF THE	38 a. 18
COMBINORS OF MECHOVAL, IF ANT	7		