STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

HO. 4" (OPIES RECEIVES	
DISTRIBUTION	
SANTA FE	
FILE	17
U.\$.0.5.	
LAND OFFICE	
02224"02	

OIL CONSERVATION DIVISION

	DISTRIBUTION	6.1.1-	P. O. BOX 2088	Payrend 10 1 20										
	FILE	SANT	'A FE, NEW MEX	CO 87501	Su. Indicate Ty	20. 211								
	U.S.O.S.				State State	Fue Fue								
	OPERATOR				5. State Oil &	Gas Leane No.								
					min	mmmm								
SUNDRY NOTICES AND REPORTS ON WELLS 100 NOT USE THIS FORM FUN PROPOSALS TO DRILL ON TO DEFINE OF PLUS SACENTO A DIFFERENT RESERVOIR. 105 TAPPLICATION FOR PERMIT - TERROR CHOTISFON NOCH PROPOSALS.														
OIL GAS X CO2 OTHER.						7. Unit Agreement Name BDCDGU								
Niamo of Operator						ase Name								
Amoco Production Company						2034								
, A	P. O. Box 68, Hobbs	. New Mexico 8	88240 JL C	ONSERVATION DATE	9. Well No.									
. L	ocation at well			SANTA FI	1/1 10. Field and	Pool, or Whideat								
	UNIT LETTER	990"	North Line	99U FEET FROM	Und. Tu	ıbb								
				34-E										
	THE LINE, SECTION		we.											
		15. Elevatio	in (Show whether DF, RT, 4806 GL	GR, etc.)	12. County Union									
<u></u>	Check	Appropriate Box T	Co Indicate Natura	of Notice, Report or Ot	hor Data	<u> </u>								
		APPROPRIATE BOX 1 ATENTION TO:	o marcare mature	SUBSEQUEN		ि. इ.								
	<u></u>			. —										
7 E R	PORM RENGIAL WORK	PLUG A		NCE DRILLING OPNS.		TERING CASING								
, U L	L OR ALTER CASING	CHANGE		TEST AND CEMENT JOB		· _								
			OT#	ER										
				·										
	Describe Proposed or Completed Op work) SEE RULE 1103.	perations (Clearly state	all pertinen: details, and	give pertinent dates, including	estimated date	of starting any proposed								
	On 9-16-82 CO2-In-Ad	ction (rig #18)	spudded a 12-1	/4" hole at 7:00 pm	. Drilled	l to a TD								
	of 708' and ran 9-5,	/8" casing set	at 708'. Cemen	ted with 400 sacks	class H ce	ment.								
•	Plugged down 5:00 am. 9-18-82. Circulated 33 sacks. WOC 18 hours. Tested casing with													
	600# for 30min. TestedOK. Reduced hole to 8-3/4" and resumed rilling. Drilled to a TD													
	of 2505' and ran 7" casing set at 2500'. Cemented with 850 sacks class H cement. Plugged													
	down 4:30 am. 9-23-8	•												
	2190'-2210', 18'-36',44'-60',70'-83',88'-2300', 2305'-19', 28'-54', and 70'-2404' with 2 JSPF. On 11-2 turned thru a separator and flow tested for 335 hrs. Well flowed 23094 MCF and 3 BLW. Last													
24 hrs. well flowed 1814 MCFD and 0 BLW. Ran 72 hr. BHP build up test 12-3-82 thru 12-6-82 Pulled the packer. Ran 3-1/2" plasticoated tubing, seating nipple, and packer. Tailpipe landed at 2345' and set packer at 2131'. Well is currently shut in.														
												rada 1-Amerigas	1-Uitie	s Serv.
			xcelsion 1-S											
e.	hereny certify that the information	above is true and comp	olete to the best of my kn	owledge and belief.										
16.34	. Cother Life	4.0000 31	Assis.	t. Admin. Analyst	22.5 1	10-83 `								
_=														
r = -	040.84		71768	ing the second s		1/18/83								
					UAIL	<u> </u>								