APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK APPLIC ATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 7. Unit Agreese 7. Unit Ag	
OISTRIBUTION I SANTA FE I FILE I U.S.G.S. I LAND OFFICE I OPERATOR State APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK State Ital Type of Vers Form C-101 DRILL X DEEPEN DRILL X DEEPEN PLUG BACK BDCDG State X CO2 other Sinct X Sinct X Monco Production Company 9. Well No. P. O. Box 68, Hobbs, New Mexico 88240	FEE X
OISTRIBUTION I SANTA FE I FILE I U.S.G.S. I LAND OFFICE I OPERATOR Starte APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Starte Starte I OPERATOR DEEPEN PLUG BACK I PLUG BACK I Starte I OPERATOR DEEPEN PLUG BACK I PLUG BACK BDCDG I I OPERATOR Starte APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK I I I OPERATOR I DEEPEN PLUG BACK I BDCDG I I OPERATOR I I I OPERATOR I I I I I I I I I I I I I I I <t< td=""><td>FEE X</td></t<>	FEE X
SANTAFE NEW MEXICO OIL CONSERVATION COMMISSION Form C-101 FILE Apple Apple Apple U.S.G.S. Apple Apple SA. indicator Compension State State State Compension State State State APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK State State APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 7. Unit Agrees State CO2 or were State BDCDG Other State State State BDCDG State State State BDCDG State State State BDCDG State State State BDCDG State State State State State State State State State State State State State State State State State State State State State State State State State State State State	FEE X
FILE APIL APIL APIL SA. indicator U.S.G.S. APIL APIL SA. indicator State OPERATOR 30.059-20193 S. Signe OIL 6 State State APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK S. Signe OIL 6 State State APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 7. Unit Agrees 7. Unit Agrees At Type of Xell DEEPEN PLUG BACK BDCDG OTHER State State BDCDG OFL CO2 other State BDCDG Amoco Production Company 9. Well No. BS240 10. Field and Accersus of Operator 10. Field and 10. Field and 10. Field and	FEE X
APPLICATION FOR PERMIT TO DRILL, DEEPEN. OR PLUG BACK	
APPLICATION FOR PERMIT TO DRILL, DEEPEN. OR PLUG BACK	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK A Type of Yell DRILL DEEPEN PLUG BACK 7. Unit Agrees 7. Unit Agree	Cus Lease No.
DRILL X DEEPEN PLUG BACK 7. Unit Agrees On L CAS BDCDG On L CAS Sincle X BDCDG On L CAS Sincle X Multiple On L CAS CO2 other Sincle X Name of Corrotor Sincle X Multiple BDCDG Amoco Production Company 9. Well No. Accersus of Operator 1834 P. O. Box 68, Hobbs, New Mexico 88240	
DRILL DEEPEN PLUG BACK 7. Unit Agrees OIL CO2 other BDCDG 8. Form or Leas Name of Operator Sincle X Mail Tiple I BDCDG Name of Operator Sincle X Mail Tiple I BDCDG Amoco Production Company 9. Well No. 1834 P. O. Box 68, Hobbs, New Mexico 88240 10. Field and I	mmmm
- Type of Yell DRILL X DEEPEN PLUG BACK BDCDG eit well ess well X CO2 otwer Sincle X Multiple BDCDG Name of Operator sincle X Multiple BDCDG BDCDG Amoco Production Company 9. Well No. 1834 P. O. Box 68, Hobbs, New Mexico 88240 10. Field and 1	
ent ent PLUG BACK BDCDG ent ent ent ent ent wett x CO2 other ent ent Nome of Operator ent ent ent ent Amoco Production Company 9. Well No. Accrease of Operator 1834 P. O. Box 68, Hobbs, New Mexico 88240	
Amoco Production Company Sincle X Multiple I BDCDGI Accress of Operator 9. Well No. 1834 P. O. Box 68, Hobbs, New Mexico, 88240 10. Field and 1	
Amoco Production Company 9. Well No. Accrease of Operator 1834 P. O. Box 68, Hobbs, New Mexico, 88240 10. Field and 1	
P. 0. Box 68, Hobbs, New Mexico, 88240	<u> </u>
P. O. Box 68, Hobbs, New Mexico 88240	2210
Location of fell	
UNIT LETTER G LOCATED 1650 FEET FROM THE NORTH LINE ANNIH	<u>mmm</u>
1650 22 18-N 34-F	MMMMM
The two recent the second s	<u> MIMMM</u>
Union	
	D. HOLCTY OF C.C.
A 2001 Tubb	Rotary
4/30 Blanket on File	ate Work will store
	arter-1983
PROPOSED CASING AND CEMENT PROGRAM	
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT	
9.2/4" $32.30%$ 700 Circ.	EST. TOP Surface
-374 /* 15.#-20.# 2900' Tieback to 9-5/8"	Surface
Propose to drill and equip well in the Tubb formation. After reaching TD logs and evaluated. Perforate and stimulate as necessary in attempting commercial p	will be run
Mud Program: 0-700' Native Spud Mud 700'-TD KCL-Salt Water Gel-Starch APPROVAL VALLE	
BOP program attached PERMIT EXPIRES	DAYS
Gas is not dedicated UNLESS DRILLING UND	29-83
	ERWAY
0+2-NMOCD SF; 1-HOU R. E. Ogden Rm 21.150; 1-SUSP; 1-PJS; 1-Amerada; 1-Ameriga	
THE STOLES WELTINGS INCOMPLUS INCOMPLEX AND LEVERAL STARS I COMPLETE STARS	5,
1-Jim Russell, Clayton; 1-F. J. Nash, HOU Rm 4.206	
TOVE SPACE DESCRIBE PROPORED UPDOD	~
LONE. GIVE BLOWDIF PREVENTED PROCRAM, IF ANY.	PROPOSED NEW PRODU
by certify that the information above is true and compirte to the best of my knowledge and belief.	
$(\xi \chi \Lambda) \rightarrow \rho_{III}$	
Tule_Assistant Administrative Analystone 8	29183
This spice while Usen	
I SIL	
ROVED BY Soy Eletison TITLE CIL AND GAS INSPECTOR	131183
I SIL-	131183
NOVED BY DOG STORE TITLE CIL ANEL GAS INSPECTOR DATE 8	(31/83
OVED BY DOY CHORINON TITLE CIL AND GAS INSPECTOR	(31/83

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

i

•

Form C-102 Supersedes C-126 Effective 1-1-65

11	distances	must	be	irom	the	outer	boundaries	of	the	Section.	

Operator		All distances must be in)_ease		Well Nc. 1834221G				
AMO	<u>CO</u> Section	Township	Range	County	10572216				
G	22	T18N	R34E	UNION	· \ \				
Actual Footage Lo 1650		IORTH line and	1650	feet from the EAS	Inte				
Ground Level Elev.		ormation			Dedicated Acreage:				
4730	Tubb		Und. Tubb	l er hochure marke	an the plat below				
1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.									
	han one lease is nd royalty).	dedicated to the well,	outline each and	identify the owners	hip thereof (both as to working				
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consoli- dated by communitization, unitization, force-pooling.etc?									
Yes		answer is "yes," type of							
,		owners and tract descri	ptions which have	actually been cons	olidated. (Use reverse side of				
	if necessary.) ble will be assign	red to the well until all i	nterests have been	n consolidated (by	communitization, unitization.				
					been approved by the Commis-				
sion.		·							
[1		7		CERTIFICATION				
1019			1		- t				
1					reby certify that the information con- ed herein is true and complete to the				
	AUG 3 1 1983		5	. best	of my knowledge and belief.				
	NSERVATION DIV		0	1 -					
	SANTA_FE			Name	Lety Seina				
			1650		sist. Admir. Analyst				
	 i			Compa	oco Production Company				
	1		i i	Date	August 29, 1983				
		<u></u>	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~						
	1) he	reby certify that the well location				
	1		l		in on this plat was plotted from field				
			l	11	s of actual surveys made by me or r my supervision, and that the same				
	Ì		ł		rue and correct to the best of my				
	1			know	ledge and belief.				
					UG HAND				
	. 		1	Date S	S ANE OF				
			1	Regist	re Professional Angines				
			1	N.M					
			l	Certifi	coie of F. SHIE				
C 33C 660	90 1320 1650 191	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	500 1000	500 0					

STANDARD 2000 PSI W.P. BOP STACK

- 1. Blow-out preventers may be manually operated.
- All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
- Bell nipple above blow-out preventer shall be same size as casing being drilled through.
- Kelly cock to be installed on kelly.

و من المراجع

- 5. Full opening safety valve 2,000 pti w.p. (4,000 pti test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
- Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
- Double or space saver type preventers may be used in lieu of two single preventers.
- BOP rams to be installed as follows:*

Top preventer - Drill pipe or casing rams Bottom preventer - Blind rams

*Amoco District Superintendent may reverse location of rams.

- 9. Extensions and hand wheels to be installed and braced at all times.
- 10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

:--

