| HE PEDPIES DECEIVED | | • | | | | | |
|---|----------------------|----------------------------|---|---------------------------|--------------------------------|-----------------------------|--|
| DISTRIBUTION | | | WATION COURSEIN | •.1 | | • | |
| SANTA FE | NTA FE | | | | | Form C-101 Revised 14-65 | |
| FILE | | | | | SA. indicate Type of Leave | | |
| U.S.G.S. HPJ + 20195 | | | | | STATE FEE Y | | |
| LAND OFFICE | | | | | .S. State Oli | & Cus Loose No. | |
| OPERATOR | | 50 | | , | | C-174 'VO' | |
| | | | | | min | misimilli | |
| APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK | | | | | | | |
| a. Type of hiers | | | | | 7. Unii Agre | sment Home | |
| b. Type of Well DRILL X DEEPEN PLUG BACK | | | | | |)GU | |
| | | | | | | 8. Farm or Lease Name | |
| WELL X CO2 OTHER SINCE X MULTIPLE ZINC | | | | | BDCD |)GU | |
| Amoco Production Company | | | | | | 9. Well No. | |
| - Accress of Operator | | | | | | 1935 261G | |
| P. O. Box 68, Hobbs, New Mexico 88240 | | | | | 10. Field and Pool, or Wildeat | | |
| Lecation of Well WHIT LETTER G LOCATED 1650 North | | | | | | Tubb | |
| שמוד ננדדו | ER LOS | TATED TOJU | ET FROM THENOT | CII LINE | | | |
| ND 1650 FEET FROM | THE East en | e or sec. 26 Tm | 19-N 35 | _F | | | |
| | | | minni ini | | 12. County | | |
| | | VIETNO TELEFONISTO | | VIIIII: | Union | | |
| | | W. WITTITT | Hillilli | iiiiiii | 17777 | minimu | |
| | | | | | | | |
| | /////XXX///// | | | 9A. Formution | | 20. notary or C. C. | |
| 1. mevations (anow whether ut) | | A SOUTH WATER WATER | 2900' | Tubb | | Rotary | |
| 4531' | Plant | et on File | | | | . Date Work will start | |
| 3. | 1 Dialik | ec on File | N/A | | 4th Q | luarter-1983 | |
| • | P | PROPOSED CASING AND | CEMENT PROGRAM | | | | |
| SIZE OF HOLE | SIZE OF CASING | WEIGHT PER FOOT | CETTING BERTH | 12.2.2 | · | | |
| 12-1/4" | 9-5/8" | 1011 | | | | EST. TOP | |
| 8-3/4" | 7" | 15.#-20.# | 2900 | Cir | | Surface | |
| | | 10.11 | 2300 | THEDack | to 9-5/ | 8" Surface | |
| - 1 | \$. | | | 1 . | l | | |
| Propose to drill | l and equip well | in the Tubb fo | rmation. After | r reachir | ıa TD loc | s will be run | |
| and evaluated. | Perforate and s | stimulate as nec | essary in atten | npting co | mmercial | production. | |
| | | | | | • | | |
| Mud Program: | 0-700' Native | Spud Mud | | | נים דחם | 90 DAYS 1-29-83. | |
| /(| 00'-TD KCL-Sal | lt Water Gel-Sta | rch APF | PROVAL VE | LID FOR _ | 1-29-83. | |
| BOP program atta | achad | • | P | ERMIT EX | THEO LL | INDERWAY | |
| Gas is not dedic | | | | UNLESS D | MILE IN | ÷ | |
| dus is not dedit | .a ceu | | | | | | |
| | | _ | | • | | | |
| 0+2-NMOCD, SF; 1 | L-HOU R. E. Oode | n Rm 21 150: 1- | SUSP - 1-P.15 - 1- | Amorada: | 1-Amoni | 9364 | |
| 1-Cities Service | : 1-Conoco: 1-(| :02 in Action: 1 | -Excelsion: 1-9 | Tav | 1-Ameri | ·yas; | |
| 1-Jim Russell, C | Clayton: 1-F. J. | Nash, HOU Rm 4 | .206 | Julii ICA. | , I-LAXU | /H 3 | |
| | • • • | | | | | • | |
| AROVE SPACE DESCRIBE PR | OPOSED PROGRAM: IF F | PAGPOSAL IS TO DEEPEY OR | PLUG BACK, GIVE DATA OM | PACSENT PROC | | AND BEARING | |
| ereny certify that the into- | D should be | | | | | | |
| 1 | | icte to the best of my kno | wiedge and belief. | | | | |
| ard Itu | - dema | Tul- Assistant | Administrative | Analyst- | R | 129183 | |
| This spucy jow's | | | - COLUMN TO THE | <u> / (ι (α 1 γ 5</u> ¢)) | nte | 1-1149 | |
| | 7/// | | | | | | |
| PROVED OF 804 CA | Whoson | CIL AND | GAS INSPECTOR | | (| 2/2//62 | |
| HOSTIGHS OF APPROVALIF | ANY | HTLE | | ° | ATE | 101103 | |
| | · · · · | | | | • | | |
| | | | | | | | |

OIL CONSERVATION COMMISSION TO BE NOTIFIED WITHIN 24 HOURS OF BEGINNING OPERATIONS

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-101 Supersedes C-128 Effective 1-1-65

All distances must be from the outer boundaries of the Section. Well No. Operator 1935261G AMOCO PRODUCTION COMPANY Township Range Unit Letter **R35E** T19 N UNION Actual Footage Location of Well: 1650 1650 **NORTH** feet from the feet from the line and Dedicated Acreage: Ground Level Elev. 4531 Producing Formation Und. Tubb 160 Tubb Acres 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling. etc? If answer is "yes," type of consolidation _ Yes If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.). No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commis-CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief. 1650 Assist. Admin. Analyst OIL CONSERVATION DIVISION SANTA FE Amoco Production Company August 29, 1983 I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or my supervision, and that the same

STANDARD 2000 PSI W.P. BOP STACK

- Blow-out preventers may be manually operated.
- All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
- Bell nipple above blow-out preventer shall be same size as casing being drilled through.
- 4. Kelly cock to be installed on kelly.
- Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
- Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
- Double or space saver type preventers may be used in lieu of two single preventers.
- 8. BOP rams to be installed as follows:*

Top preventer - Drill pipe or casing rams Bottom preventer - Blind rams

*Amoco District Superintendent may reverse location of rams.

- 9. Extensions and hand wheels to be installed and braced at all times.
- 10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

<u>...</u>

