		-			
- HO. OF SOPICS ACCEIVED		*	•		
DISTRIBUTION					
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION					Form C-101 Revised 14-65
	FILE				
LAND OFFICE APT # 30-059-20196				SA. indicate Type of Lease	
LAND OFFICE 11 717 30-057-20116					-S. SIGTE OLI & CHIS LOUISE NO.
OPERATOR 20					to the Carl & Cars Lorse No.
					Millimmonne.
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK					ZIIIIIIIIIIIIIIIIIIIIIII
					7. Unit Agreement jieme
b. Type of Yell DRILL		DEEPEN		PLUG BACK	BDCDGU
NCLL CAS WELL X	CO2 OTHER		SINGLE V	MULTIPLE	8. Farm or Lease Name
2. Nome of Operator			ZONE X	Zive	BDCDGU
Amoco Production Company					9. Well No.
3. Accress of Operator					1934 262 G
P. O. Box 68, Hobbs,		88240			10. Field and Pool, or Wildcat Und. Tubb
UNIT LETTER_	G	LATED 1650		North	ATTIMITATION AND AND AND AND AND AND AND AND AND AN
AND 1650	E +	· · ·	FROM THE	LINC	VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
TARD 1000 PEET PROM THE	East	26	<u></u>	GE. 34-E NMPM	VIIIIIIIIIIIIIIIII
iilliittittitti	ALLAN AND AND AND AND AND AND AND AND AND A	CAREEN DAVI	TTHINK	TITUTUTU	12. County A
		TITUT MANN	<u> </u>		Union (
	REGULATION .		iiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiii		
		<u> </u>		1111111111	
<u> </u>	AVREERADS LAD	() MOREWARD MOU	9. Proposed Lies		ם 20. ווסומץ כר כינה
A7221	1111111111111		2900*	Tubb	Rotary
4733'	Blank	ket on File	15. Drilling Con		22. Approx. Date Work will start
23.			N/A		4th Quarter-1983
PROPOSED CASING AND CEMENT PROGRAM					
SIZE OF HOLE SI	ZE OF CASING	WEIGHT PER FOOT	SETTING		· · · · · · · · · · · · · · · · · · ·
	9-5/8"	32.30#	13211NG D	EPTH ISACKS OI	
8-3/4"	7"	15.#-20.#	2900		rc. Surface
:			2900	Tiebac	< to 9-5/8" Surface
• .		1	l	<b>I</b> .	
Propose to drill and equip well in the Tubb formation. After reaching TD logs will be run and evaluated. Perforate and stimulate as necessary in attempting commencial much be run					
and evaluated. Perforate and stimulate as necessary in attempting commercial production.					
Mud Program: 0-700' Native Spud Mud 700'-TD KCL-Salt Water Gel-Starch					
	TO ROL-Sal	t water Ger-Sta	ircn		LID FOR 90 DAYS
BOP program attache	ed		÷		
Gas is not dedicate	ed			PERMITER	IRES 11-29-8-3
UNLESS DAILLING UNDERWAY					
			:	• •	
0+2-NMOCD, SF; 1-H	JU R. E. Odde	n Rm 21.150: 1_	SUSP: 1_P.1	S. 1-Amonada	1 Amountant
O+2-NMOCD, SF; 1-HOU R. E. Ogden Rm 21.150; 1-SUSP; 1-PJS; 1-Amerada; 1-Amerigas; 1-Cities Service; 1-Conoco; 1-CO2 in Action; 1-Excelsior; 1-Sun. Tex.; 1-Exxon; 1-Jim Russell, Clayton; 1-F. J. Nuch. HOU Pr. 4 200					
1-Jim Russell, Clay	/ton; 1-F. J.	Nash, HOU Rm 4	.206	, 1-Jun. 1ex.	; I-EXXON;
		· · · · · · · ·		. ÷	
ABOVE SPACE DESCRIBE PROPOSE VE LONG. GIVE BLOWDUF PROVENTED PR	SED PROGRAM: IF PI	ROPOSAL IS TO OCEPEN OR	PLUG BACK, GIVE -	ATA ON BOSCO	
ereby certify that the information and	ave is true and and				UGTIVE ZONE AND PROPOSED NEW PRODUC-
		rte to the best of my kno			
and with the	ma	Tul- Assistant	Adminict		0 1-01-00
This splet for stage	Used		Sum HIStra	<u>ive Analys</u> to	ne 0/24/15
1 X ONV					
ABATTAN AND GAS INSPECTOR 8/3/83					
NOTIONS OF APPHOVAL IF ANY		TITLE VIL AND	GAS INSPECTO	R	ATE 8/31/83
	•		_	U	
OIL CONSERVATION COMMISSION TO BE NOTIFIED					
			ASSION TO	BE NOTIFIEI	)
	WITHIN 2	24 HOURS OF B	EGINNING	<b>OPERATIONS</b>	
					•
	هنداه حدامة من من نشب الفرد من هندها و				•
				الأفري وجهور المسترج والمشر والمسترج المسترج	

## NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-11: Supersedes C-12F

Effective i-i-t. All distances must be from the outer boundaries of the Section Well No. Operato Lease MOCO 1934262G Section Township Fanae Unit Letter County G 26 T19N R34E UNION Actual Footage Location of Well: 1650 NORTH 1650 EAST feet from the line and ieet from the line Ground Level Elev: 4733 **Producing Formation** Pool Dedicated Acreage: Tubb Und. Tubb Acres 160 1. Outline the acreage dedicated to the subject well by colored pencil or/hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling. etc? Yes Yes If answer is "yes," type of consolidation \_ No If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.). No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission. CERTIFICATION I hereby certify that the information contained herein is true and complete to the AUG13 1 1983 best of my knowledge and belief. OIL CONSERVATION DIVISION SANTA FE Name una 1650 Position Assist. Admin. Analyst Company Amoco Production Company Date August 29, 1983 I hereby certify that the well location shown on this plat was platted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief. Reg Certifica

330

660

90

1320

16 50

1980

2310

26.40

2001

1500

500

## STANDARD 2000 PSI W.P. BOP STACK

- Blow-out preventers may be manually operated.
- All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) 2.
- Bell nipple above blow-out preventer shall be same size as casing being 3.
- Kelly cock to be installed on kelly. 4.

1.

Full opening safety value 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any 5.

Spool or cross may be eliminated if connections are available in the lower 6. part of the blow-out preventer body.

Double or space saver type preventers may be used in lieu of two single 7.

8. BOP rams to be installed as follows:\*

> Top preventer Drill pipe or casing rams Blind rams Bottom preventer -

\*Amoco District Superintendent may reverse location of rams.

9. Extensions and hand wheels to be installed and braced at all times.

10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

:..

