40. OF COPICS RECEIVED							
MOISTRIBUTION	NEV	MEXICO OIL CONSER	VATION COMMISSION	i	Form C-101		
SANTA FE	1	· MEXICO OIL CONSE.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		Revised 14-65		
FILE	- 	in the	4-20199		SA. indicate	Ye of Lease	_
U.S.G.S.		$A01$ * -	42011		STATE	PEE X	
LAND OFFICE		11 05	9-		-5. State Off &	Cus Loose No.	_
OPERATOR		30				C-356 ,/Q.	
					mm	momm	~
APPLICATIO	N FOR PERMIT TO	DRILL, DEEPEN, C	OR PLUG BACK				',
la. Type ut Work			Loo biller		7. Unii Agree:		7
DRILL X	Ì			_			
or The or well	·	DEEPEN PLUG BACK		ACK	8. Form or Lease Name		
WELL X CO2 OTHER SINGLE X MULTIPLE						•	
2. Name of Operator	OOL GINEN		ZOHC [A]	Z 34E	BDCDG	iU	
Amoco Production C	Company		*		9. Well No.	0010	
J. Accress of Operator					1935 291G		
P. O. Box 68, Hobb	s New Mexico	88240	•		10. Field and Pool, or Wildcat Und. Tubb		
4. Location of Well			Maurita	!	und.	IUDD	_
SHIT LETTI	LR LO	EATED 1650 FE	ET FROM THE North	LINE			'/
440 1650 PEST PROM	Fact	20·	10 N	_ }			.\
TITLE PROPERTY OF THE PROPERTY	THE LAST	THE PARTY OF THE P	, 19-N 35	-E NMPM	11/1/1/1	71111111111	,
					12. County		1
		Million (MI)		illilli	Union		.\
						mmilli	7
	7111111111111111	to the sold of Mill					1
		Contraction of the state of the	. Proposed Depth 1	A. Formution	1	20, motery of C.C.	_
	11116 by couper	MINOW PHANCEN	2900'	Tubb	1	Rotary	
4632		Liade i'lug. sond 21	5. Drilling Coouractor		22. Approx.	Date Work will store	-
	Blan	et on File N/A			4th Qu	arter-1983	
23.							
			. •				_
		PROPOSED CASING AND	CEMENT PROGRAM				_
SIZE OF HOLE				SACKS OF			
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH		CEMENT	EST. TOP	
		32.30#	SETTING DEPTH	Cir	CEMENT C.	EST. TOP	
12-1/4"	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	Cir	CEMENT	EST. TOP	_
12-1/4"	SIZE OF CASING	32.30#	SETTING DEPTH	Cir	CEMENT C.	EST. TOP	
12-1/4" 8-3/4"	SIZE OF CASING 9-5/8" 7"	32.30# 15.#-20.#	700' 2900'	Cir Tieback	CEMENT C. to 9-5/8	EST. TOP Surface Surface	
12-1/4" 8-3/4" Propose to dril	SIZE OF CASING 9-5/8" 7" and equip wel	32.30# 15.#-20.#	700' 2900'	Cir Tieback reachir	to 9-5/8	EST. TOP Surface " Surface s will be run	
12-1/4" 8-3/4" Propose to dril	SIZE OF CASING 9-5/8" 7" and equip wel	32.30# 15.#-20.#	700' 2900'	Cir Tieback reachir	to 9-5/8	EST. TOP Surface " Surface s will be run	
12-1/4" 8-3/4" Propose to dril	SIZE OF CASING 9-5/8" 7" and equip wel	32.30# 15.#-20.#	700' 2900'	Cir Tieback reachir	to 9-5/8	EST. TOP Surface " Surface s will be run	
12-1/4" 8-3/4" Propose to dril and evaluated.	SIZE OF CASING 9-5/8" 7" and equip well Perforate and	32.30# 15.#-20.# l in the Tubb fostimulate as nec	700' 2900'	Cir Tieback reachir	to 9-5/8	EST. TOP Surface " Surface s will be run	
12-1/4" 8-3/4" Propose to dril and evaluated. Mud Program:	9-5/8" 7" and equip well Perforate and	32.30# 15.#-20.# l in the Tubb fostimulate as nec	2900' 2900' rmation. After	Cir Tieback reachir	to 9-5/8	EST. TOP Surface " Surface s will be run	
12-1/4" 8-3/4" Propose to dril and evaluated. Mud Program:	9-5/8" 7" and equip well Perforate and	32.30# 15.#-20.# l in the Tubb fostimulate as nec	2900' 2900' rmation. After essary in attem	Cir Tieback reachir pting co	to 9-5/8	EST. TOP Surface " Surface swill be run production.	
12-1/4" 8-3/4" Propose to dril and evaluated. Mud Program:	9-5/8" 7" l and equip wel Perforate and 0-700' Native 00'-TD KCL-Sa	32.30# 15.#-20.# l in the Tubb fostimulate as nec	2900' 2900' rmation. After essary in attem	Cir Tieback reachir pting co	to 9-5/8	EST. TOP Surface " Surface swill be run production.	
12-1/4" 8-3/4" Propose to dril and evaluated. Mud Program: 70 BOP program atta	9-5/8" 7" l and equip wel Perforate and 0-700' Native 00'-TD KCL-Sa	32.30# 15.#-20.# l in the Tubb fostimulate as nec	2900' 2900' rmation. After essary in attem	Cir Tieback reaching pting co	to 9-5/8 ng TD logs mmercial	EST. TOP Surface " Surface swill be run production.	
12-1/4" 8-3/4" Propose to dril and evaluated. Mud Program:	9-5/8" 7" l and equip wel Perforate and 0-700' Native 00'-TD KCL-Sa	32.30# 15.#-20.# l in the Tubb fostimulate as nec	2900' 2900' rmation. After essary in attem	Cir Tieback reaching pting co	to 9-5/8 ing TD logsommercial	EST. TOP Surface " Surface swill be run production.	
12-1/4" 8-3/4" Propose to dril and evaluated. Mud Program: 70 BOP program atta	9-5/8" 7" l and equip wel Perforate and 0-700' Native 00'-TD KCL-Sa	32.30# 15.#-20.# l in the Tubb fostimulate as nec	2900' 2900' rmation. After essary in attem	Cir Tieback reaching pting co	to 9-5/8 ng TD logs mmercial	EST. TOP Surface " Surface swill be run production.	
12-1/4" 8-3/4" Propose to dril and evaluated. Mud Program: 70 BOP program atta	9-5/8" 9-5/8" 7" and equip wel Perforate and 0-700' Native 00'-TD KCL-Sa	32.30# 15.#-20.# l in the Tubb fostimulate as nec Spud Mud lt Water Gel-Sta	2900' 2900' rmation. After essary in attended to the permit unless	Tieback reaching co	to 9-5/8 to 9-5/8 or To logs ommercial OR 90 i//29 GUNDERV	EST. TOP Surface "Surface swill be run production. DAYS 1/8-3 VAY	
12-1/4" 8-3/4" Propose to dril and evaluated. Mud Program: 70 BOP program atta Gas is not dedice.	9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sa ached cated	32.30# 15.#-20.# l in the Tubb fostimulate as nec Spud Mud It Water Gel-Sta	2900' 2900' 2900' rmation. After essary in attention. APPROVA PERMIT UNLES SUSP; 1-PJS; 1-	reaching co	to 9-5/8 to 9-5/8 ommercial or 90 i1/29 GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8-3 VAY	
Propose to dril and evaluated. Mud Program: 80P program atta Gas is not dediced. 0+2-NMOCD, SF; 1-Cities Service	9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sanched cated L-HOU R. E. Ogde; 1-Conoco; 1-	32.30# 32.30# 15.#-20.# l in the Tubb fostimulate as nec Spud Mud It Water Gel-Sta en Rm 21.150; 1- CO2 in Action; 1	2900' 2900' 2900' rmation. After essary in atten rch APPROVA PERMIT UNLES SUSP; 1-PJS; 1Excelsior: 1-S	reaching co	to 9-5/8 to 9-5/8 ommercial or 90 i1/29 GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8-3 VAY	
Propose to dril and evaluated. Mud Program: 80P program atta Gas is not dediced. 0+2-NMOCD, SF; 1-Cities Service	9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sanched cated L-HOU R. E. Ogde; 1-Conoco; 1-	32.30# 15.#-20.# l in the Tubb fostimulate as nec Spud Mud It Water Gel-Sta	2900' 2900' 2900' rmation. After essary in atten rch APPROVA PERMIT UNLES SUSP; 1-PJS; 1Excelsior: 1-S	reaching co	to 9-5/8 to 9-5/8 ommercial or 90 i1/29 GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8-3 VAY	
Propose to dril and evaluated. Mud Program: 80P program atta Gas is not dediced. 0+2-NMOCD, SF; 1-Cities Service	9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sanched cated L-HOU R. E. Ogde; 1-Conoco; 1-	32.30# 32.30# 15.#-20.# l in the Tubb fostimulate as nec Spud Mud It Water Gel-Sta en Rm 21.150; 1- CO2 in Action; 1	2900' 2900' 2900' rmation. After essary in atten rch APPROVA PERMIT UNLES SUSP; 1-PJS; 1Excelsior: 1-S	reaching co	to 9-5/8 to 9-5/8 ommercial or 90 i1/29 GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8-3 VAY	
Propose to dril and evaluated. Mud Program: 80P program atta Gas is not dediced. 0+2-NMOCD, SF; 1-Cities Service	9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sanched cated L-HOU R. E. Ogde; 1-Conoco; 1-	32.30# 32.30# 15.#-20.# l in the Tubb fostimulate as nec Spud Mud It Water Gel-Sta en Rm 21.150; 1- CO2 in Action; 1	2900' 2900' 2900' rmation. After essary in atten rch APPROVA PERMIT UNLES SUSP; 1-PJS; 1Excelsior: 1-S	reaching co	to 9-5/8 to 9-5/8 ommercial or 90 i1/29 GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8-3 VAY	
Propose to dril and evaluated. Mud Program: 80P program atta Gas is not dediced. 0+2-NMOCD, SF; 1-Cities Service	9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sa ached cated L-HOU R. E. Ogd 2; 1-Conoco; 1- Clayton; 1-F. J	32.30# 15.#-20.# l in the Tubb fo stimulate as nec Spud Mud It Water Gel-Sta en Rm 21.150; 1-C02 in Action; 1 . Nash, HOU Rm 4	rmation. After essary in attem APPROVA PERMIT UNLES SUSP; 1-PJS; 1- Excelsior; 1-S .206	reaching co	to 9-5/8 to 9-5/8 ommercial or 90 i1/29 GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8-3 VAY	
Propose to dril and evaluated. Mud Program: 80P program atta Gas is not dediced. 0+2-NMOCD, SF; 1-Cities Service	9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sa ached cated L-HOU R. E. Ogd 2; 1-Conoco; 1- Clayton; 1-F. J	32.30# 32.30# 15.#-20.# l in the Tubb fostimulate as nec Spud Mud It Water Gel-Sta en Rm 21.150; 1- CO2 in Action; 1	rmation. After essary in attem APPROVA PERMIT UNLES SUSP; 1-PJS; 1- Excelsior; 1-S .206	reaching co	or 90 (1/29) GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8/3 VAY Jas; 1;	
Propose to dril and evaluated. Mud Program: 80P program atta Gas is not dediced. 0+2-NMOCD, SF; 1-Cities Service	9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sa ached cated L-HOU R. E. Ogd 2; 1-Conoco; 1- Clayton; 1-F. J	32.30# 15.#-20.# l in the Tubb fo stimulate as nec Spud Mud It Water Gel-Sta en Rm 21.150; 1-C02 in Action; 1 . Nash, HOU Rm 4	rmation. After essary in attemore. APPROVA PERMIT UNLES SUSP; 1-PJS; 1-Excelsior; 1-S .206	Cir Tieback reaching pring co	or 90 (1/29) GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8/3 VAY Jas; 1;	
Propose to dril and evaluated. Mud Program: 70 BOP program atta Gas is not dediced. 0+2-NMOCD, SF; 1 1-Cities Service 1-Jim Russell, (9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sanched cated L-HOU R. E. Ogd 1-Conoco; 1-Clayton; 1-F. J	32.30# 15.#-20.# l in the Tubb fo stimulate as nec Spud Mud It Water Gel-Sta en Rm 21.150; 1-C02 in Action; 1 . Nash, HOU Rm 4	rmation. After essary in attem APPROVA PERMIT UNLES SUSP; 1-PJS; 1- Excelsior; 1-S .206	Cir Tieback reaching pring co	or 90 (1/29) GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8-3 VAY	16.
Propose to dril and evaluated. Mud Program: 80P program atta Gas is not dediced. 0+2-NMOCD, SF; 1-Cities Service	9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sanched cated L-HOU R. E. Ogd 1-Conoco; 1-Clayton; 1-F. J	32.30# 15.#-20.# l in the Tubb fo stimulate as nec Spud Mud It Water Gel-Sta en Rm 21.150; 1-C02 in Action; 1 . Nash, HOU Rm 4	rmation. After essary in attemore. APPROVA PERMIT UNLES SUSP; 1-PJS; 1-Excelsior; 1-S .206	Cir Tieback reaching pring co	or 90 (1/29) GUNDERV	EST. TOP Surface Surface Swill be run production. DAYS 1/8/3 VAY Jas; 1;	16.
Propose to dril and evaluated. Mud Program: 70 BOP program atta Gas is not dediced. 0+2-NMOCD, SF; 1 1-Cities Service 1-Jim Russell, (9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sanched cated L-HOU R. E. Ogd 1-Conoco; 1-Clayton; 1-F. J	and the Tubb for stimulate as necessimulate as necessimul	2900' 2900' rmation. After essary in attemore. APPROVA PERMIT UNLES SUSP; 1-PJS; 1Excelsior; 1-S .206 PLUE PACE. SIVE BATA ON Wiedge and bellef. Administrative	Cir Tieback reaching pring co	or 90 il/29 GUNDERV 1-Americal 1-Exxor	EST. TOP Surface Surface Swill be run production. DAYS 1/8-3 VAY Jas; 1;	16.
Propose to dril and evaluated. Mud Program: 70 BOP program atta Gas is not dediced. 0+2-NMOCD, SF; 1 1-Cities Service 1-Jim Russell, (9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sanched cated L-HOU R. E. Ogd 1-Conoco; 1-Clayton; 1-F. J	and the Tubb for stimulate as necessimulate as necessimul	rmation. After essary in attemore. APPROVA PERMIT UNLES SUSP; 1-PJS; 1-Excelsior; 1-S .206	Cir Tieback reaching pring co	or 90 il/29 GUNDERV 1-Americal 1-Exxor	EST. TOP Surface Surface Swill be run production. DAYS 1/8/3 VAY Jas; 1;	
Propose to dril and evaluated. Mud Program: 70 BOP program atta Gas is not dediced. 0+2-NMOCD, SF; 1 1-Cities Service 1-Jim Russell, (9-5/8" 7" I and equip well Perforate and 0-700' Native 00'-TD KCL-Sanched cated L-HOU R. E. Ogd 1-Conoco; 1-Clayton; 1-F. J	and the Tubb for stimulate as necessimulate as necessimul	2900' 2900' rmation. After essary in attemore. APPROVA PERMIT UNLES SUSP; 1-PJS; 1Excelsior; 1-S .206 PLUE PACE. SIVE BATA ON Wiedge and bellef. Administrative	Cir Tieback reaching pring co	or 90 il/29 GUNDERV 1-Americal 1-Exxor	EST. TOP Surface Surface Swill be run production. DAYS 1/8-3 VAY Jas; 1;	16.

OIL CONSERVATION COMMISSION TO BE NOTIFIED WITHIN 24 HOURS OF BEGINNING CPERATIONS

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

All distances must be from the outer boundaries of the Section. Well No. 1935291G AMOCO County Township **R35E** UNION T19N 29 Actual Footage Location of Well: 1650 EAST 1650 NOR TH line teet from the line and Dedicated Acreage: Pool Producing Formation Acres 160 Und. Tubb Tubb 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling. etc? If answer is "yes," type of consolidation _ Yes If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.). No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit. eliminating such interests, has been approved by the Commission. CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief. CONSERVATION DIVISION 1650 Assist. Admin. Analyst Company Amoco Production Company Date August 29, 1983 I hereby certify that the well-location en on this plat was plotted from field notes of actual surveys made by me or ier my supervision, and that the same 1000 500 2000 1500 330 660

STANDARD 2000 PSI W.P. BOP STACK

- Blow-out preventers may be manually operated.
- All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
- Bell nipple above blow-out preventer shall be same size as casing being drilled through.
- 4. Kelly cock to be installed on kelly.
- Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
- Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
- Double or space saver type preventers may be used in lieu of two single preventers.
- 8. 80P rams to be installed as follows:*

Top preventer - Drill pipe or casing rams Blind rams

*Amoco District Superintendent may reverse location of rams.

- 9. Extensions and hand wheels to be installed and braced at all times.
- 10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

Ξ.

