		, •					
40. OF COPICS ACCEIVED			,				
MOITUBIETZIO	NEW MEXICO OIL CONSERVATION COMMISSION						
SANTA FE						Form C-101 Revised 14-65	
U.S.G.S.	11	To the second			SA. indicate	Type of Lease	
LAND DEFICE IN SIGN					STATE] rec [X]	
OPERATOR					.5. state OI4 6	Cus Lease No.	
				•	mm	Minne.	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK							
					7. Unii Agres	meni ilane	
b. Type of Tell DRILL	-	DEEPEN PLUG BAC		JG BACK	BDCDGU		
MELL WELL X	CO2 OTHER				8. Farm or Lease Name		
			ZONE LOS	2746	BDCDO	SU	
Amoco Production	company		<u> </u>		1834	R/11 D	
P. O. Box 68, Hob	bs. New Marias	99240			10. Field and	Pool, or Wildcat .	
Lecation of Well	D	4.6.6			Und.	Tubb	
660	TER LO	660 EATED	FEET FROM THE SOU	thLINE	TTilll		
NB OOO PEET FROM	THE East in	VE OF SEC. 34	TWP 18-N 16E	34-E			
				Jillill.	12. County		
					Union		
MIIIII.	rialki i					Willillilli	
			19. Proposed Depth	19A formution		THIIIII.	
T exampos (Snow mustucing		//////////////////////////////////////	2900'	Tubb		Rotary	
4626'	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	& Status Plug. Bond	215. Drilling Contracte	1	22. Approx.	Date Work will store	
3.	i bidhk	et on File	N/A		4th Qu	arter-1983	
	P	ROPOSED CASING AND	D CEMENT PROGRAM				
SIZE OF HOLE	SIZE OF CASING WEIGHT PER FOOT SETTING DEDTU Section						
12-1/4" 8-3/4"	<u> </u>	32.30# . 700'			C		
0-3/4	7"	15,#-20,#	2900	Tieback		Surface " Surface	
:	1					- Juliuce	
Duanas to 1 12	•		•	•		Kr.	
Propose to dril	l and equip well	in the Tubb f	ormation. Aft	er reachin	g TD loas	will be run	
and evaluated.	reflurate and s	timulate as ne	cessary in att	empt ino c o	mmercial	production.	
Mud Program:		Spud Mud		방력	<u>당왕(</u> (main	
70	00'-TD KCL-Sal	t Water Gel-St.	arch	18			
BOP program atta	APPRO	WAL VALID FOR		· JIH NO	DV - 9 191	3	
Gas is not dedic			. ,	OII CONG			
ado io not dedit	UNI HINE	ESS DAIL GOLDA	ERWAY	OIL COME	ERVATION	DIVISION	
					SANTA FE		
0+2-NMOCD, SF; 1 1-Cities Service	1-HOU R. E. Ogde	n Rm 21.150; 1	-SUSP: 1-PJS:	1-Amerada•	1-Americ	25.	
				-Sun. Tex.	1-Exxon	u 2 5	
1-Jim Russell, (- layton; I-F. J.	Nash, HOU Rm	4.206			•	
A HOVE SPACE DESCRIBE DE	OPOSED PROGRAMITE				•	•	
TEDY CERTIFUL CHAPTER - 1-1	ER PHOGRAM, IF ANY.	ROPOSAL IS TO DEEPEN OR	PLUG EACK, GIVE DATA	DM PRESENT PRODU	CTIVE ZONE AN	-SUCORS WIN DIEDROPS O	
recor certify that the indomnetto							
ned 1 Ulli	dition	Tul- Assistant	Administration	. Λ <u>ω</u> π1			
This spect or s	State Use)	- 4221214III	Auministrative	: Analysto	te <u>1-1-</u>	/-83	
PROVED BY		TITLE_		10 10 10 10 10 10 10 10 10 10 10 10 10 1	11	1.18 1	
NOITIONS OF APPROVAL, IF	ANY:			DA	TE	p I start at	

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-102 Supersedes C-121 Effective 1-1-61

All distances must be from the outer boundaries of the Section Well No. Jire: atc: 1834 341P AMOCO County Township Hange UNION T18N R34E Actual Foctage Location of Well: feet from the feet from the line and Dedicated Acreage; Producing Formation Ground Level Elev. Und. Tubb Tubb 160 4626 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and rovalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling.etc? If answer is "ves," type of consolidation __ If answer is "no." list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.)_ No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commis-CERTIFICATION I hereby certify that the information contained herein is true and complete to the my knowledge and belief. Admin. Analyst AMOCO PRODUCTION COMPANY Company 11-7-83 I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief. 660

1500

2000

1320 1650

2310 2640

1000

STANDARD 2000 PSI W.P. BOP STACK

- 1. Blow-out preventers may be manually operated.
- All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
- Bell nipple above blow-out preventer shall be same size as casing being crilled through.
- 4. Kelly cock to be installed on kelly.
- Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
- Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
- Double or space saver type preventers may be used in lieu of two single preventers.
- 8. BOP rams to be installed as follows:*

Top preventer - Drill pipe or casing rams Bottom preventer - Blind rams

*Amoco District Superintendent may reverse location of rams.

- 9. Extensions and hand wheels to be installed and braced at all times.
- 10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

