			·-				
NO. OF COPICS PECEIVED	1		·	•			
DISTRIBUTION	MEXICO OIL CON	SERVATION COM	MISSION	_	·-		
SANTAFE					Form C-101 Revised id-65		
LAND OFFICE			,		SA. instear	S TYPE OF LEGUE	
LAND OFFICE			0,, 9	-2-224		STATE	
OPERATOR						S. Sime Oli	& Gus Lease No.
				<b>A 1 m 1 7</b>	· · · · · · · · · · · · · · · · · · ·	heren	· · · · · · · · · · · · · · · · · · ·
APPLICATI	ON FOR PER	MIT TO			C	AIIIII	HHHHHHH
14. Type of hors	-		I has had here here !	UIDL	<b>C</b>	7. Unit Agre	Sement Home
b. Type of Well DRILL X DEEPEN					PLUG BACK	BDC	
WELL CO2 OTHER				SINGLE [V]		8. Farm or L	ease Name
2. Name of Operator				SINCLE X		BDCI	<u>)GU</u>
Amoco Production ( J. Accress of Operator		•		9. Well No. 1024	071G		
	· · · ·	- -			d Pool, or Wildcat		
P. O. Box 68, Hobl	88240	· · ·		Und.	Tubb		
UNIT LETT	ERG		ATED 1650	FEET FROM THE	North Line	TITTA	<u>illillillilli</u>
10 1650 PEET FROM	Eas	t	torse. 7		-34_F		<u>IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII</u>
<i>1111111111111111111111111111111111111</i>	MARIE	inn i	Millin Internet		34-E KMPM	12. County	THUM IN THE T
HILLER BARRANT CONTRACTOR		ΠÜ	<u>Millillill</u>	MIMM	HHHHH	Union	A/////////
(())))))))))))))))))))))))))))))))))))	UKAN)	lllill	<u>illillilli</u>	inninni	<u>iiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiii</u>	Millin	<u> </u>
11111111111111111111111111111	HIWNIII			19. Proposed Dept	<u> 111111111111111111111111111111111111</u>	<u>IIIIII</u>	
1 History Stor While I	HHHH	MM		2900 *		а.,	20. hoiery or C. L.
483287.517A TE	VIVIL de dige	21A. Kina	& Status Plug. Bond	215. Drilling Conu	Tubb	22 625107	Rotary
4832-		Blank	et on File	N/A			uarter-1983
		P	ROPOSED CASING AN	D CENENT PPOC	2.4.14		·····
SIZE OF HOLE	SIZE OF C					·	
12-1/4"	9-5	/8"	WEIGHT PER FOO	TI SETTING DE			EST. TOP
8-3/4"	1 7"		15, #-20, #	2900*			Surface
:				2,700	TIEDdCK	<u>to 9-5/</u>	8" Surface
	• .	1		1		<b>I</b>	•
Propose to dril and evaluated.	l and equi	p well	in the Tubb f	formation	After reachir		c will be win
and evaluated.	Perforate	and s	timulate as ne	ecessary in	attempting co	ommercial	production
				•	· · · ·		production.
		d CIVE	Spud Mud				
	. –		t Water Gel-St	larch	APPROVAL I		· 6.
BOP program atta	ched	:			FERMITED	VALID FOR	70 DAYS
Gas is not dedic	cated			•			2-15-8%
	•				••		ERWAY
0+2-NMOCD, SF: 1	-HOLL R F		D D 21 150 1	<u></u>			
O+2-NMOCD, SF; 1 1-Cities Service 1-Jim Russell, C	: 1-Conoc	• Ugae •• 1_0	n RM 21.150; 1 02 in Action:	-SUSP; 1-PJS	S; 1-Amerada;	1-Ameri	gas;
1-Jim Russell, C	layton; 1	-F. J.	Nash, HOLL Rm	1-Exceision:	; I-Sun. Tex.	; 1-Exxo	n;
	-				. •	. •	~
A DOVE SPACE DESCRIBE PRI	DPOSED PROG	RAM: 17 94	OPOSAL IS TO DEEPEN O	P PLUG CACK, GIVE D	ATA ON PRESENT PROD	UCTIVE TONE A	KO BROSSES
reor certify that the infirmatio	n shove is true	and cumpli	rte to the best of my ki				
Hiti )	l 1 in						
	Sum -		TulAssistant	Administrat	ive Analysto	are_ 11-	-10-83
(The spectors	•						
PROVED BY	712000		g™n an Anna an Anna an Anna Anna Anna Ann				•
NDITIONS OF APPNOVAL, IF			TITLE	22 - 2010 - 2010 	- Салан (ур. 196) D	ATE /	1:15-33
- <b>-</b> , IF		,					
	OIL C	ONSER	VATION COUNT	SSION TO R	C NETICIEN		•
	WIT	HIN 24	HOURS OF BE	CONTRACTOR	PATERS		
					an a se se se se se conservation de la conservation de la conservation de la conservation de la conservation de		

## NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C-1(2 Supersedes C-128 Effective 1-1-6:

	All dis		the outer boundaries	of the Section.	Well Nc.					
AMOCO			-C S+-		1834071G					
G 7			R 3 4 E	County UNIC	N					
Actual Foctage Location of 1650	well: from the NOR TH	line and	1650 : ,	eet from the EAS	Tline					
······································	From the Producing Formation			eet hom the	Dedicated Acreage:					
4832	Tubb		Und. Tubt	)	160 Acres					
		ne subject well	by colored pencil	or hachure marks	on the plat below.					
<ol> <li>Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.</li> <li>If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).</li> </ol>										
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owpers been consoli- dated by communitization, unitization, force-pooling, etc?										
Yes N	Yes No If answer is "yes," type of consolidation									
If answer is "no." list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.)										
No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit. eliminating such interests, has been approved by the Commission.										
		7			CERTIFICATION					
1		Z		k lhe	reby certify that the information con-					
		5 0		toin	ed herein is true and complete to the					
		6 12	l I	) befst	of my knowledge and belief.					
ای د مراجعه این می در این می این ا این ده دهمینیه د ده ده مینیه		K. –			uting Sema					
		ş		Nœne						
	the second se	7		Ass	st. Admin. Analyst					
	TON DIVISION	Ş	•		CO PRODUCTION COMPANY					
SUPL	-} i	8	l							
i		Ş	1	<u> </u>	11-10-83					
	:	\$	1							
	<u></u>	<u>}</u>	$\sim$	~~~~						
				1 he	reby certify that the well location					
			•	shov	vn on this plat was plotted from field					
					s of actual surveys made by me or					
					r my supervision, and that the same					
			l ,		rue and correct to the best of my					
· +					and the second s					
			r I	SEF	РТ. 28 1983					
				Date S	urveyed the sub					
					ered Professional Engineer Land Surveyor					
					I.L.S. NO. 5103					
			1		cote No.					
0 336 660 '90 13	20 1650 1980 2310 2	640 2000	1500 1000	soc o	Core 190					
					······································					

STANDARD 2000 PSI W.P. BOP STACK

- 1. Blow-out preventers may be manually operated.
- All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
- Bell nipple above blow-out preventer shall be same size as casing being drilled through.
- 4. Kelly cock to be installed on kelly.
- 5. Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
- Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
- Double or space saver type preventers may be used in lieu of two single preventers.
- BOP rams to be installed as follows:\*

Top preventer - Drill pipe or casing rams Bottom preventer - Blind rams

\*Amoco District Superintendent may reverse location of rams.

- 9. Extensions and hand wheels to be installed and braced at all times.
- 10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

Ξ.

