

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	11
LAND OFFICE	1
OPERATOR	1

API # 30-059-20275

5A. Indicate Type of Lease	
STATE <input type="checkbox"/>	FEE <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1. Type of work		2. Name of Operator		3. Address of Operator		4. Location of Well		5. Well No.		6. State Oil & Gas Lease No.	
a. Type of Well		Amoco Production Company		P.O. Box 68 Hobbs, New Mexico 88240		UNIT LETTER <u>G</u> LOCATED <u>1650</u> FEET FROM THE <u>North</u> LINE		Bravo Dome Carbon Dioxide Gas Unit		Bravo Dome Carbon Dioxide Gas Unit	
b. Type of Well						AND <u>1980</u> FEET FROM THE <u>East</u> LINE OF SEC. <u>31</u> TWP. <u>20-N</u> R. <u>35-E</u> N.M.P.M.		2035 311G		Bravo Dome Carbon Dioxide Gas Unit 640-Acre Area	
OIL WELL <input type="checkbox"/>		GAS WELL <input checked="" type="checkbox"/>									
DRILL <input checked="" type="checkbox"/>		DEEPEN <input type="checkbox"/>									
SINGLE ZONE <input checked="" type="checkbox"/>		MULTIPLE ZONE <input type="checkbox"/>									
17. County		19. Proposed Depth		19A. Formation		20. Rotary or C.T.					
Union		2900'		Tubb		Rotary					
21A. Kind & Status Plug. Bond		21B. Drilling Contractor		22. Approx. Date work will start							
Blanket-on-file		N/A									
23. ELEVATIONS (show whether D.P., H.L., etc.)											
4724' GL											

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
12-1/4"	9-5/8"	32.30#	700'	Circulate	surface
8-3/4"	7"	20.0#	2900'	Tieback to 9-5/8"	surface

Propose to drill and equip well in the Tubb formation. After reaching TD logs will be run and evaluated. Perforate and stimulate as necessary in attempting commercial production.

Mud Program: 0 - 700' Native Spud Mud
700 - TD KCL Salt Water Gel-Starch

APPROVAL VALID FOR 180 DAYS
PERMIT EXPIRES 3-18-86
UNLESS DRILLING UNDERWAY

BOP Diagram attached.

O+5-NMOCD,SF 1-J. R. Barnettt, HOU Rm. 21.156 1-F. J. Nash, HOU Rm. 4.206 1-WF, C 1-WF,
1-Susp, 1-CMH 1-Amerada 1-Amerigas 1-Cities Service 1-Conoco 1-CO2 in Action 1-Sun
1-Excelsior 1-Tex 1-Exxon

4. ABOVE SPACE DESCRIBE PROPOSED PROGRAM; IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRO-
DUCTIVE ZONE. GIVE SHUT-IN PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Charles M. Herring Title Administrative Analyst (SG) Date 9-16-85

PROVED BY Roy E. Johnson TITLE DISTRICT SUPERVISOR DATE 9-18-85

CONDITIONS OF APPROVAL, IF ANY:

NEW MEXICO OIL CONSERVATION COMMISSION
WELL LOCATION AND ACREAGE DEDICATION PLAT

Form O-101
Supersedes C-128
Effective 1-4-65

All distances must be from the outer boundaries of the Section

Operator AMOCO PRODUCTION COMPANY			Lease B.D.C.D.G.U.		Well No. 2035311G
Unit Letter G	Section 31	Township T20N	Range R35E	County UNION	
Actual Footage Location of Well: 1650 feet from the NORTH line and 1980 feet from the EAST line					
Ground Level Elev. 4724	Producing Formation Tubb		Pool Bravo Dome 640 Acre Area		Dedicated Acreage: 640 Acres

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☒ Yes ☐ No If answer is "yes," type of consolidation **Unitization**

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) _____

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.


62 Amoco Production Company Fred Roberts Odell Roberts Minnie Rodgers Verna South Leona J. Bray Albert Jueschke Barbara Langston Est. Olivia V. Seaton Paul Jueschke Richard Jueschke Josephine E. Weese	<div style="text-align: right; margin-bottom: 10px;">60 A PT</div> <div style="position: relative; height: 100px;"> <div style="position: absolute; left: 40%; top: 0; transform: rotate(-90deg);">1650</div> <div style="position: absolute; left: 45%; top: 50%;">1980</div> </div> <div style="margin-top: 10px;"> Amoco Production Company Fred Roberts Odell Roberts Minnie Rodgers Verna South </div>
--	--

CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Name *Charles M. Lanning*
 Position *Admin. Analyst (SG)*
 Company *Amoco Production Company*
 Date *9-16-85*

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.



STANDARD 2000 PSI W.P. BOP STACK

1. Blow-out preventers may be manually operated.
2. All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
3. Bell nipple above blow-out preventer shall be same size as casing being drilled through.
4. Kelly cock to be installed on kelly.
5. Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
6. Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
7. Double or space saver type preventers may be used in lieu of two single preventers.
8. BOP rams to be installed as follows: *
 - Top preventer - Drill pipe or casing rams
 - Bottom preventer - Blind rams*Amoco District Superintendent may reverse location of rams.
9. Extensions and hand wheels to be installed and braced at all times.
10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

