

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-78

NO. OF COPIES DESIRED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API-# 30-059-20282

5A. Indicate Type of Lease
STATE <input type="checkbox"/> REC <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of work

b. Type of Well

DRILL ☒DEEPEN ☐PLUG BACK ☐OIL WELL ☐GAS WELL ☒ CO2

OTHER

SINGLE ZONE ☒MULTIPLE ZONE ☐

2. Name of Operator

Amoco Production Company

3. Address of Operator

P.O. Box 68 Hobbs, New Mexico 88240

4. Location of well

UNIT LETTER JLOCATED 1650FEET FROM THE South LINEAND 1650FEET FROM THE EastLINE OF SEC. 28TWP. 18NRCC. 35E

Bravo Dome Carbon Dioxide Gas Unit

Bravo Dome Carbon Dioxide Gas Unit

9. Well No.

1835 281J

Bravo Dome Carbon Dioxide Gas Unit 640-Acre Area

17. County

Union

19. Proposed Depth

2900'

15A. Formation

Tubb

20. Rotary or C.T.

Rotary

21A. Kind & Status Plug. bond

Blanket-on-file

21B. Drilling Contractor

N/A

22. Approx. Date work will start

ASAP

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
12-1/4"	9-5/8"	32.30#	700'	Circulate	surface
8-3/4"	7"	20.0#	2900'	Tieback to 9-5/8"	surface

Propose to drill and equip well in the Tubb formation. After reaching TD logs will be run and evaluated. Perforate and stimulate as necessary in attempting commercial production.

Mud Program:

0 - 700' Native Spud Mud
700 - TD KCL Salt Water Gel-Starch

BOP Diagram attached.

0+5-NMOCD,SF 1-J. R. Barnettt, HOU Rm. 21.156 1-F. J. Nash, HOU Rm. 4.206 1-WF, C 1-WF,
1-Susp, 1-CMH 1-Amerada 1-Amerigas 1-Cities Service 1-Conoco 1-CO2 in Action 1-Sun
1-Excelsior 1-Tex 1-Exxon

4. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRO-
DUCIVE ZONE. GIVE SHUT-IN PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed

Charles M. HerringTitle Administrative Analyst (SG)

Date

9-25-85

(This space for State Use)

APPROVED BY

TITLE

DATE

9-30-85

CONDITIONS OF APPROVAL, IF ANY

180
3-30-86

**NEW MEXICO OIL CONSERVATION COMMISSION
WELL LOCATION AND ACREAGE DEDICATION PLAT**

Form C-102
Supersedes C-128
Effective 1-1-65

All distances must be from the outer boundaries of the Section.

Operator AMOCO PRODUCTION COMPANY		Lease Bravo Dome Carbon Dioxide Gas Unit		Well No. 1835281J
Unit Letter J	Section 28	Township T18N	Range R35E	County UNION
Actual Footage Location of Well:				
1650	feet from the	SOUTH	line and	1650
1650	feet from the	EAST	line	
Ground Level Elev. 4605	Producing Formation Tubb	Pool Bravo Dome 640 Acre Area	Dedicated Acreage: 640 Acres	

1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☒ Yes ☐ No If answer is "yes," type of consolidation Agreement or Forced Pooling

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) _____

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.

445 PT Sun Production Company G. Whittenburg et al Cornell Oil Company	1138 Amoco Prod. Co. Fred J. Simmons et ux	1139 Sun Prod. Co. W. M. Simmons et al
Joe H. Staley et al G. Whittenburg et al	1146 Cornell Oil Co. Edith Edmundson et vir	444 PT G. Whittenburg et al Cornell Oil Co. G. Whittenburg et al Cornell Oil Co.
<div style="position: relative;"> <div style="position: absolute; top: 0; left: 0; width: 100%; height: 100%; border: 1px dashed black;"></div> <div style="position: absolute; top: 10%; left: 10%;"> 149 Amoco Production Company L. D. Ellis et ux </div> <div style="position: absolute; top: 40%; left: 40%;"> <div style="border: 1px solid black; width: 100px; height: 100px; transform: rotate(90deg);"></div> <div style="position: absolute; top: 0; left: 0; width: 100%; height: 100%; border: 1px solid black;"></div> </div> </div>		

CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Name Charles M. Lanning
 Position Admin. Analyst (SG)
 Company Amoco Production Company
 Date 9-25-85

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

JUL 23 1985
 Date Surveyed
 Registered Professional Engineer
 and/or Land Surveyor
 NEW MEXICO
 No. 5108
 N. L. SHIELDS
 Certificate No. 103

0 330 660 990 1320 1650 1980 2310 2640 2000 1500 1000 500 0

STANDARD 2000 PSI W.P. BOP STACK

1. Blow-out preventers may be manually operated.
2. All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test) minimum.
3. Bell nipple above blow-out preventer shall be same size as casing being drilled through.
4. Kelly cock to be installed on kelly.
5. Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
6. Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
7. Double or space saver type preventers may be used in lieu of two single preventers.
8. BOP rams to be installed as follows:
 - Top preventer - Drill pipe or casing rams
 - Bottom preventer - Blind rams

*Amoco District Superintendent may reverse location of rams.
9. Extensions and hand wheels to be installed and braced at all times.
10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

