Submit 3 Copies	State of New Me		Form C-103
to Appropriate	Energy, Minerals, and Natural Resources Department		Revised 1-1-89
District Office			
<u>DISTRICT I</u>	OIL CONSERVATION DIVISION		WELL API NO.
P.O. Box 1980, Hobbs, NM 88240	P.O. Box 208	38	30 059 20375
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico 87	504-2088	5. Indicate Type of Lease STATE FEE X
			6. State Oil & Gas Lease No.
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 874	-10		6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS			
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name
1. Type of Well	I GRAN G-1017 TOR SOCITI THOI GOALS.		BRAVO DOME CO2 GAS UNIT 1935
OIL OIL	GAS		BITAVO DOME COZ GAS CIVIT 1995
WELL	WELL OTHER	CO2	
2. Name of Operator			8. Well No.
AMOCO PRODUC	TION COMPANY		272E
3. Address of Operator			9. Pool name or Wildcat
P.O. Box 303,	AMISTAD, NEW MEXICO 88410		BRAVO DOME CO2 GAS UNIT
4. Well Location			
Unit Letter E : 1664 Feet From The North Line and 958 Feet From The West Line			
Section 27 Township 19N Range 35E NMPM Union County			
10. Elevation (Show whether DF, RKB, RT, GR, etc.)			
4568'			
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE	OF INTENTION TO:	SUBSE	QUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS	. X PLUG AND ABANDONMENT
PULL OR ALTER CASING CASING TEST AND CEMENT		JOB	
OTHER:		OTHER:	[-¬
12. Describe Proposed or Completed Operations  (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)  SEE RULE 1103.			
05/01/98 MIRT spud surface at 16:15, drill 12 1/4" hole to 729', run 17 jts 24# J-55 8 5/8" casing. Cement with 400 sks			
Premium + class C cement and circulate 175 sks to pit. WOC 8 hrs, drill 7 7/8" hole 759' - 2253'. Run 6 jts 5 1/2" 15.5#			
J-55 LT&C, 68 jts 5 1/2" 5.6# Star Fiberglass casing. Fiberglass casing landed at 2031'. Top of Cimarron @ 2020', Top			
of Tubb @ 2043'. Cement with 400 sks Midcon Premium+ Class C, circulate 150 sks to pit. MORT, wait on completion			
unit.			
I have by a parties at the attention	ation above is true and complete to the best of m	v knowledge and halist	
SIGNATURE	TITLE	y knowledge and beliet. Field Team Leader	DATE 5/5/98
TYPE OR PRINT NAME D. J.	Holcomb		TELEPHONE NO. (606) 374-3010
(This space for State Use)	9/10	ISTRICT SUPERV	1508 our 5/22/60
717 00 1000			
CONDITIONS OF APPROVAL, IF AN	<i>'V</i>		