## District 1 1625 N. French Dr., Hobbs, NM 88240

Previous Operator Signature

## State of New Mexico Energy, Minerals & Natural Resources

Form C-104 Revised March 25, 1999

Submit to Appropriate District Office

District II OIL CONSERVATION DIVISION 811 South First, Artesia, NM 88210 2040 South Pacheco District III 5 Copies 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe. NM 87505 District IV AMENDED REPORT 2040 South Pacheco, Santa Fe, NM 87505 REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT 1 Operator name and Address <sup>2</sup> OGRID Number OXY USA Inc. 16696 P.O. Box 50250 <sup>3</sup> Reason for Filing Code Midland, TX 79710 AG - NW API Number 5 Pool Name <sup>6</sup> Pool Code 30-0 059-20392 Bravo Dome Carbon Dioxide Gas 640 Property Code 96010 8 Property Name 9 Well Number 27111 Bravo Dome Carbon Dioxide Gas Unit 2034 212 11. Surface Location UL or lot no Township Fect from the Range Lot. Idn North/South Line Feet from the East/West line County 1819 north 2332 west Union Bottom Hole Location UL or lot no Township Lot. Idn Feet from the North/South Line Feet from the East/West line County 12 Lse Code 13 Producing Method Code <sup>14</sup> Gas Connection Date <sup>15</sup> C-129 Permit Number C-129 Effective Date <sup>17</sup> C-129 Expiration Date Р 9/30/02 III. Oil and Gas Transporters <sup>18</sup> Transporter 19 Transporter Name and Address 20 POD 21 O/G 22 POD ULSTR Location OGRID and Description OXY USA Inc. 16696 2833204 G P.O. Box 303 Amistad, NM 88410 Produced Water 24 POD ULSTR Location and Description Well Completion Data 25 Spud Date <sup>26</sup> Ready Date 27 TD 28 PBTD 29 Perforations DHC, MC 9/9/02 2444 31 Hole Size 2126-2400 32 Casing & Tubing Size 33 Depth Set 34 Sacks Cement 12-1/4" 8-5/8" 702' 300sx 7-7/8" 5-1/2" 2444' 350sx VI. Well Test Data 35 Date New Oil 36 Gas Delivery Date 37 Test Date 38 Test Length Tbg. Pressure 40 Csg. Pressure 9/30/02 42 Oil 10/17/02 41 Choke Size 24 105 43 Water 44 Gas 45 AOF 46 Test Method 2-orf <sup>47</sup> I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. 2700 flwa SERVATION DIVISION Signature: Approved by Printed name Title: David Stewart DISTRICT SUPERVISOR Title Approval Date: Regulatory Analyst Date: lotsiloz Phone: 915-685-5717 <sup>48</sup> If this is a change of operator fill in the OGRID number and name of the previous operator

Printed Name

Title

Date

All distances must be from the outer boundaries of the Section Well No. Cheratar 2034211L Bravo Dome CO2 Gas Unit AMOCO PRODUCTION COMPANY Township T20N County R34E UNION Actual Footage Location of Well: 1980 SOUTH feet from the feet from the line and 660 Producing Formation Dedicated Acreage: Ground Level Elev. Und. Tubb 160 Tubb 4774 Acres 1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling. etc? If answer is "yes," type of consolidation \_\_ If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.). No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission. CERTIFICATION I hereby certify that the Information contained herein is true and complete to the best of my knowledge and belief. OIL CONSERVATION DIVISION Nome Position Assist. Admin. Analyst Amoco Production Company 7-22-83 I hereby certify that the well location shown on this plat was plotted from field 660 notes of actual surveys made by me or carrect to the best of my

2007

500

## STANDARD 2000 PS1 W.P. BOP STACK

- Blow-out preventers may be manually operated.
- All equipment must be in good condition, 2,000 psi W.P. (4,000 psi test)
- Bell nipple above blow-out preventer shall be same size as casing being 3. drilled through.
- Kelly cock to be installed on kelly.
- Full opening safety valve 2,000 psi w.p. (4,000 psi test) minimum must be available on rig floor at all times with proper connection or subs to fit any tool joint in string.
- 6. Spool or cross may be eliminated if connections are available in the lower part of the blow-out preventer body.
- 7. Double or space saver type preventers may be used in lieu of two single preventers.
- 8. BOP rams to be installed as follows:\*

Top preventer Drill pipe or casing rams

Bottom preventer Blind rams

\*Amoco District Superintendent may reverse location of rams.

- 9. Extensions and hand wheels to be installed and braced at all times.
- 10. Manifold valves may be gate or plug metal to metal seal 2" minimum.

