Submit 3 Copies To Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources		Form C-100 Revised March 25, 1999	
District I 1625 N. French Dr., Hobbs, NM 87240 District II 811 South First, Artesia, NM 87210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 2040 South Pacheco, Santa Fe, NM 87505	OIL CONSERVATION DIVISION 2040 South Pacheco Santa Fe, NM 87505		WELL API NO. 30-05: 5. Indicate Type STATE [6. State Oil & Ga	9-20393 of Lease FEEX
(DO NOT USE THIS FORM FOR PROPODIFFERENT RESERVOIR. USE "APPLIC PROPOSALS.) 1. Type of Well: Oil Well Gas Well 2. Name of Operator OXY USA Inc. 3. Address of Operator P.O. Box 50250 Midland, TX 4. Well Location Unit Letter E:	Other CO2 Supply W 79710-0250 2491feet from the	EN OR PLUG BACK TO A C-101) FOR SUCH Tell 16696 north line and	Bravo Dome Carl 2034 8. Well No. 282 9. Pool name or V Bravo Dome Carb	om the west line
Section 28 11. Check A NOTICE OF INTE	ppropriate Box to Indica	4853.7' ate Nature of Notice,		
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	PLUG AND ABANDON CHANGE PLANS CMULTIPLE COMPLETION	REMEDIAL WORK COMMENCE DRILLII CASING TEST AND CEMENT JOB		ALTERING CASING [PLUG AND [ABANDONMENT
OTHER: 12. Describe Proposed or Completed of starting any proposed work). Some or recompilation.	SEE RULE 1103. For Multip			
I hereby certify that the information above i SIGNATURE Type or print name David Stewart		of my knowledge and belief.	nalyst D Telephon	DATE <u>そんとして</u> ne No. 915-685-5717
(This space for State use) APPROVED BY Conditions of approval, if ar.y.	lohu- TI	TLEDISTRICT SU		, ,

BDCDGU 2034 #282

09/14/2002

CMIC:

Wayne Lucas

Present operation: Running 8 5/8 casing. Progress: Spud 12 1/4" hole at 15:30 hours on 09/13/2002. TD 12 1/4 hole at 739', 01:45 hours on 09/14/2002. Rig up and 19 joints 8 5/8 #24 J-55 ST&C casing. Set at 739.37.

09/15/2002

CMIC:

Wayne Lucas

Present operation: Drilling at 1610'. Progress: Cement 8 5/8 casing with 300sx Premium Plus (14.8 lbs/gal, 1.34 cuft/sx) Circulated 40 sx to surface. Plug down at 08:27 hours on 09/14/2002. Drill new formation at 18:00 hours on 9/14/2002. Drilling from 739' - 1610'. (871'). Last survey at 1227' 1 deg.

09/16/2002

CMIC:

Wayne Lucas

Present operation: Running 5 1/2" casing. Progress: Drill to 2488'. TD 7 7/8" hole at 23:15 hours on 09/15/2002., Pump sweep, circulate 1 hour. Trip out of hole. Rig up and run 5 1/2" casing. Last survey at 2471'.75 deg.

09/17/2002

CMIC:

Wayne Lucas

Present operation: Rig released. Progress: Run 9 joints 5 1/2" 15.50# J55 LT&C From 2488' to 2237'. Run 76 joints fiber glass, chrome sub and landing joint. Fiber glass 2' to 2237'. Cement with 200sx Premium Plus (11.1 ppg, 3.27 cuft/sx) 3% CaCl, 025#/sx Poly Flake. Followed with 150sx Premium Plus (13.2 ppg, 1.86 cuft/sx) with 3% CaCl, .25#/sx Poly E Flake. Circulated 65sx to surface. land plug at 10:57 hours on 09/16/2002. Float did not hold. Land plug again and shut cement head for four hours. Nipple down set slips. Rig released at 16:00 hours on 09/16/2002.