

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

FEB 15 1947

HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Keyes, Oklahoma

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Black Mesa Unit Well No. **1** in the _____

Company or Operator **NE NE SE** of Sec. **15**, T. **31 N**, R. **36 E**, N. M. P. M.,
wildcat Field, _____ Union. _____ County.

The dates of this work were as follows: **February 7, 1947 -**

Notice of intention to do the work was (was not) submitted on Form C-102 on **February 6** 19 **47**
 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED
 Set 80 jts 5 1/2" OD 14 1/2" & 15 1/2" H-40 & J55 R2 & R3 NSS New Casing @ 2686' in Line.- Cemented by Halliburton with 125sx. Ashgrove Portland Cement- completed job @ 7AM- 2/7/47. Released pressure @ 7PM 2/7/47. Ran Temperature survey- Indicated top of cement behind 5 1/2" Casing string- @ 2270'. At 7AM 2/9/47 checked and found top of cement in 5 1/2" casing @ 2589'. Drld cement from 2589' to 2664' then tested casing shut-off with 1000# pump pressure for 30 min.-held OK. Drld cement from 2664' to 2688'-bottom of cement. Job completed at 2:10PM 2/9/47.

Witnessed by A.B. Weiss Name The Pure Oil Company Company Dist. Supt. Title

Subscribed and sworn before me this _____

10th day of February, 1947

Elmer Mackey
 Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name H. L. BartonPosition Chief Field Clerk.Representing The Pure Oil Company Company or OperatorMy commission expires 8-10-47Address Box 101 - Keyes, Oklahoma.

Remarks:

APPROVED
 Date FEB 13 1947

Roy Yankowski
 Name
 611 & Gas Inspector
 Title