

(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

MOO-C-1420-0982

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Islata Pueblo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Islata Central

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Cactus Area

11. SEC., T., R., M., OR BLE. AND  
SURVEY OR AREA

NW/4 NW/4 Section 7-  
T7N-R2E

12. COUNTY OR PARISH

13. STATE

Valencia

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. **Drilling**

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Shell Oil Company

3. ADDRESS OF OPERATOR

1700 Broadway, Denver, Colorado 80202 OIL CONSERVATION COMM.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

810' FNL and 640' FWL Section 7, NW/4 NW/4

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5066 KB, 5044 GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Present Status: 11/11/74 13-3/8" csg at 504'  
12-1/4" hole to 5200'  
9-5/8" csg stuck from 1277 to 3770 (recovered top 1277')

Proposed Work: Set 600'± cement plug in 9-5/8" csg from top to 1900'±  
Set 600'± cement plug in open hole from 700'± to 1300'±  
Sidetrack hole to bypass stuck casing.

VERBAL APPROVAL RECEIVED FROM E. A. SCHMIDT BY R. D. GRAHAM ON 11/11/74.

NOV 14 1974

U. S. GEOLOGICAL SURVEY  
DENVER, COLO.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Division Operations Engr.

DATE

11/12/74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

cc: New Mexico Oil Conservation Commission (for information)  
cc: Southern Pueblos Agency - Albuquerque

NOV 1 1974

\*See Instructions on Reverse Side

E. A. SCHMIDT

ACTING DIRECTOR