

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

NOV 19 1981

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 11728

6. INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

REESE AND JONES

3. ADDRESS OF OPERATOR

20 First Plaza, Suite 402, Albuquerque, NM 87102

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FNL & 2313' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5956' Ungraded ground

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

NZ

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

22-6N-3W-NMPM

12. COUNTY OR PARISH

Valencia

13. STATE

Nm

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☒
☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set cement plugs on 4/23/80 as follows:

Plug #1 - 1340'-1120' - 25 sx., filled interval w/8.9# drilling mud.
Plug #2 - 220' to surface - 30 sx.
Plug #3 - in the cellar - 15 sx.

4/30/80 Installed dry hole marker and cleaned location in conformance with USGS requirements. Will reseed location according to BLM special stipulations between July 1, 1980 and September 15, 1980. When seeding is completed, subsequent notice will be sent to the USGS

TD 2725'. 5½" casing set at 2716' and cemented with 300 sx cement. Top of cement, from bond log, is 1110'.

Reason for plugging: No hydrocarbons.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Petroleum Engineer

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL IF ANY:

NOV 16 1981

Dean Elliott
DISTRICT ENGINEER

*See Instructions on Reverse Side

