(May 1963) DEPARTME	NITED STATE IN LERIOR (Other instru ENT OF THE INTERIOR verse side)	on re 5, LEASE DESIGNATION AND SERIAL NO.
, GE	OLOGICAL SURVEY	NM 11728
SUNDRY NOTIC	ES AND REPORTS ON WELLS to drill or to deepen or plug back to a different re	6. IF INDIAN, ALLOTTEE OR TRIBE NAMES
1. GIL GAS	ON FOR PERMIT— 101 Such proposition,	7. UNIT AGREEMENT NAME
WELL X WELL OTHER 2. NAME OF OPERATOR		8. FARM OR LEASE NAME
REESE AND JONES		NZ 9. WELL NO.
3. ADDRESS OF OPERATOR	100 AN 07100	
20 First Plaza, Suite 4. LOCATION OF WELL (Report location clean	402, Albuquerque, N.M. 87102 rly and in accordance with any State requirements.	10. FIELD AND POOL, OR WILDCAT
See also space 17 below.) At surface		Wildcat 11. SEC., T., R., M., OE BLK. AND SURVEY OR AREA
660'FNL & 2312'	FWL	22-6N-3W-NMPM
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR 1 21SA 13. STATE
	5956 Ungraded ground	Valencia NM
16. Check App	ropriate Box To Indicate Nature of Notice,	Report, or Other Data
NOTICE OF INTENTI	ON TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF PU	LL OR ALTER CASING WATER SHUZ	C-OFF REPAIRING WELL
FRACTURE TREAT	ULTIPLE COMPLETE FRACTURE TO	
	ANDON* SHOOTING OF	A ACIDIZING ABANDONMENT* Production casing X
REPAIR WELL CE	(Momn	: Report results of multiple completion on Weil etion or Recompletion Report and Log form.)
proposed work. If well is direction nent to this work.)*	ally drilled, give subsurface locations and measured	pertinent dates, including estimated date of starting and true vertical depths for all markers and zones p
Induction-SFL and Sor Ran 85 joints of cas of 5½11, K-55, 14#, 8 Guide shoe at 27161 of Cemented casing with cementing operations After 16 hours, WOC, pressure drop.	to 2725 TD. Ran electric logs nic) to total depth. ing (384 of $5\frac{1}{2}$, K-55, 15.5#, 8 Rd, Range 2) Total equipment and float collar at 2665. 300 sacks of Class B cement, for POB at 3:30 PM, March 25, 198 tested casing with 1600 psi for top of cement at 1100 feet.	Rd, Range 2 and 2326' 2710 feet set @ 2716'. Full returns during 30. Float held.
Now waiting on compl	and the second s	RELEIVED
A MICH FOR DIRECTO		APR 3 1980 OIL CON. COM.
		DIST. 3
con the	77	
SIGNED Just the foregoing	true and correct TITLEMorris B. Jor	nes, Engineer DATE March 28
(This style for Federal or State office	e use)	
APPROVED BY	NY:	APR 1 1980
	stato	, A. GOORGODAL SURVEY

*See Instructions on Reverse Side

ingo, outo.

(Mi	ແປ ປີປີປີ)	UN DEPARTME	NTED STATE	S NTERIOR	SUBMIT IN TRIPLIC (Other instructions overse side)	on re-	Form approve Budget Bureau SE DESIGNATION	u No. 42-R1424.			
	DEPARTMENT OF THE INTERIOR verse side) GEOLOGICAL SURVEY							NM 11728			
	SUNZ (Do not use this f	ORY NOTICE	to drill or to deeper	ORTS ON or plug back to for such propose	WELLS o a different reservoir.	6. IF 1	NDIAN, ALLOTTEE	OR TRIBE NAME			
1	1.							7. UNIT AGREEMENT NAME			
2.	NAME OF OPERATOR	OTHER				8. FAR	M OR LEASE NAM	E			
	REESE AND JO	NES					NZ				
3.	ADDRESS OF OPERATOR					9. WE	LL NO.	<u>.</u>			
4.	20 First Plaza, Suite 402, Albuquerque, N.M. 87102 4. LECATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)							10. FIELD AND POOL, OR WILDCAT			
	At surface	,				11. SI	ildcat c., t., R., M., OR B	LK. AND			
	660 ' i	NL & 2312'	FWL				SURVEY OR AREA				
7.7			15. ELEVATIONS (Show	whether DF. RT.	GR. etc.)	22- 12. co	6N-3W-NMPN OUNTY OR PARISH	13. STATE			
14	. PERMIT NO.			Ungraded		Va	lencia	NM			
 16.		Check Appr			e of Notice, Report						
		OTICE OF INTENTIO					QUENT REPORT OF:				
	TEST WATER SHUT-OF	r PUI	L OR ALTER CASING		WATER SHUT-OFF		REPAIRING V	VELL			
	FRACTURE TREAT		LTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CA	ASING			
	SHGOT OR ACIDIZE	ABA	ANDON*		SHOOTING OR ACIDIZI	-	ABANDONME	NT*			
	REPAIR WELL	СН	ANGE PLANS		(Nows · Report	ction cas	tiple completion	on Well			
17	(Other) . DESCRIBE PROPOSED OR	COMPLETED OPERA	rions (Clearly state	ll pertinent de		dates includi	eport and Log for ng estimated dat	e of starting any			
	Induction—S Ran 85 join of 5½11, K— Guide shoe Cemented ca cementing of After 16 ho pressure d	SFL and Son ts of casi 55, 14#, 8 at 2716' a asing with operations. ours, WOC, rop.	ic) to total ng(384 of 5 Rd, Range 2) nd float col 300 sacks of POB at 3:30	depth. 12", K-55, Total e lar at 26 Class B PM, Marc g with 16	cement, full r h 25, 1980. F 00 psi for 30	Range 2 a feet set eturns du loat held	and 2326' @ 2716'. uring				
						A STATE OF THE STA					
ACCEPTED	Now waiting	g on compile	etron rig.								
400	2 122	i,			a tota i	API	- 1900				
Arn	2 '80			*		ANT O	ON. COM.	/			
Com				AC.			IST. 3	•			
BY	Annua de la companya della companya		<i>7</i>		F ₁						
1:	11/1-	the foregoing		TTLE MOTT	is B. Jones, E	ngineer	DATE _ Mar	ch 28, 1980			
=	(This s) ce for Fede	ral or State office				- 1	Ø 53 B 84	EM			
	1			ITLE		La	DATE	<u> </u>			
	APPRÓVED BY CONJITIONS OF A	PPROVAL, IF AN		A A A4X4		AF	R 1 1980) .ም/			
			_	state		L.I.	11 2 1000	,			
`			*See I	nstructions of	n Reverse Side		ologioa l Sua Tilg <mark>o, C</mark> ulo.	VEY .			