

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		<input checked="" type="checkbox"/>
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator BRANA CORPORATION 3. Address of Operator 1223 First Interstate Bldg, 320 Gold Ave. SW, Albuquerque, NM 87102 4. Location of Well UNIT LETTER <u>G</u> <u>2500</u> FEET FROM THE <u>North</u> LINE AND <u>2330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>19</u> TOWNSHIP <u>6N</u> RANGE <u>2W</u> NMPM.	7. Unit Agreement Name 8. Farm or Lease Name Penteco-Trinity 9. Well No. 1 10. Field and Pool, or Wildcat Wildcat 15. Elevation (Show whether DF, RT, GR, etc.) 5572 Grnd.	12. County Valencia
--	--	------------------------

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER _____ <input type="checkbox"/>	OTHER _____ <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8 5/8" casing set @ 200' and cement circulated to surface.
6 3/4" hole drilled to 337'.
Moved in J.C. Well Service rig on August 31, 1985 and set the following plugs:
Plug #1: 50 sxs of Class A from 337' to 177'
Plug #2: 10 sxs of Class A in top of 8 5/8" casing.
Installed regulation dry hole marker.
Interval between plugs filled with 9.4#/gal gel drilling mud with no toxic additives.
Pits filled and location cleaned up. Ready for inspection 9-11-85.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Morris B. Jones TITLE Morris B. Jones, Engineer DATE 9-06-85
APPROVED BY Ray E. Johnson TITLE Senior Geologist DATE 10-25-85
CONDITIONS OF APPROVAL, IF ANY: