

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator BRANA CORPORATION		8. Farm or Lease Name Penteco
3. Address of Operator 1223 First Interstate Bldg, 320 Gold Ave. SW, Albuquerque, NM 87102		9. Well No. 4
4. Location of Well UNIT LETTER <u>E</u> <u>2600</u> FEET FROM THE <u>North</u> LINE AND <u>1230</u> FEET FROM THE <u>West</u> LINE, SECTION <u>19</u> TOWNSHIP <u>6N</u> RANGE <u>2W</u> NMPM.		10. Field and Pool, or Wildcat Wildcat-Penn.
15. Elevation (Show whether DF, RT, GR, etc.) 5986 Grnd.		12. County Valencia

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in J. C. Well Service Rig on August 30, 1985 and P & A well in the following manner:

Plug #1: 25 sxs of Class A cement from 1720' to 1790',
Plug #2: 25 sxs of Class A cement from 575' to 645' (bottom of surface casing)
Plug #3: 10 sxs of Class A cement in top of 8 5/8" casing.
Installed regulation dry hole marker.
Interval between plugs was filled with 9.1#/gal drilling mud-gel with no toxic additives.

Pits filled and location cleaned up. Ready for inspection 9-11-85.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Morris B. Jones TITLE Morris B. Jones, Engineer DATE 9-06-85

APPROVED BY R. E. Johnson TITLE Senior Geologist DATE 10-25-85

CONDITIONS OF APPROVAL, IF ANY: