## MUDDING AND CEMENTING BECORD

		*	MODDIN	G AND CERENT					
SIZE OF HOLE	SIZE OF CASING	WHERE SE	NO. SACKS OF CEMENT	METHODS USED	мир	RAVITY	AMOUNT OF MUD USED		
<b>5"</b>	4 11	705	1 50	Halliburt	ns				
					:				
	<u> </u>		P	LUGS AND ADAP	TERS				
esvino	nluo-Ma	iterial	•••••			Depth Set.			
			d bittom hol		in pipe	with cem			
SIZE	SIZE SHELL USED		EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH	DEPTH CLEANED OUT	
	-				<u> </u>				
					··				
						•			
otary to able to ut to p he prod nulsion	ools were cols were roducing	used from used from the first 24	feet to  All feet to  hours was	PRODUCTION  19barrels  sediment. Gravit	eet, and from eet, and from  of fluid of	which	feet to	fee	
	100		ira.	Galloni	gasoline per	: 1,000 cu. ft. of	gas	<del></del>	
ock pre	ssure, lbs	. per sq. in.	*						
, 	- 0.13		F	EMPLOYEES	1 ,			Driller	
Ceci	12R	ingle.		, Driller				Drille	
			**************************************	•			***************************************	1	
				YON RECORD ON			'a fine flaw a	ll work done o	
			the information given		biere wire cor	, ,	· ·	n work done o	
80 181	as can be	defermine.	d Hom wandble recor	1		: !		. '	
ubscrib	ed and sw	orn to befo	re me this 22nd	· · · · · · · · · · · · · · · · · · ·	Albuque	rque N.	4	22/1	
ay of		April	Mouns	., 1948. Nai	ition	el 2	) / Z.	<i>y</i> 6	
	ילייל איניים לייניים ל		Notary Public	Rep 1948	presenting	Company or	Operator	, 101	

11