

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 4992 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing Plugged & Abandoned 19

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Drilled as Tight Hole	Northwestern New Mexico		
T. Anhy.			T. Devonian			T. Ojo Alamo
T. Salt.			T. Silurian			T. Kirtland-Fruitland
B. Salt.			T. Montoya			T. Farmington
T. Yates			T. Simpson			T. Pictured Cliffs
T. 7 Rivers			T. McKee			T. Menefee
T. Queen			T. Ellenburger			T. Point Lookout
T. Grayburg			T. Gr. Wash			T. Mancos
T. San Andres			T. Granite			T. Dakota
T. Glorieta			T.			T. Morrison
T. Drinkard			T.			T. Penn
T. Tubbs			T.			T.
T. Abo			T.			T.
T. Penn			T.			T.
T. Miss			T.			T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	335	335	Sand Redbeds & Shales				
335	1430	1095	Sand & Redbeds				
1430	2111	681	Shale, Anhydrite & Gyp.				
2111	2210	99	Lost Circulation - no samples				
2210	2368	158	Shale & Dolomite				
2368	2398	30	Sand & Dolomite				
2398	2423	25	Sand				
2423	2501	78	Sand and Dolomite				
2501	2538	37	Sand				
2538	2593	55	Sand, Shale & Dolomite				
2593	2606	13	Dolomite				
2606	3005	499	Dolomite, Shale & Anhydrite				
3005	3500	495	Sand, Shale & Lime				
3500	3606	106	Sand, some Dolomite streaks.				
3606	3813	207	Sand and Dolomite				
3813	3958	145	Sand				
3958	4015	57	Shale & Dolomite				
4015	4090	75	Lime, Shale & Dolomite				
4090	4992	102	Lime, Shale & Granite Wash				
4992			Granite P & A				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

August 30, 1959

Company or Operator A. N. Spindel - W. O. Heinze Address Rm 6420 - 350 Fifth Ave., New York
New York