

**3R - 071**

**2013 AGWMR**

**03 / 21 / 2014**





**Terry S. Lauck**  
**Program Manager**

ConocoPhillips Company  
Risk Management & Remediation  
1380G Plaza Office Building  
315 Johnstone Avenue  
Bartlesville, OK 74004  
Phone: 918.661.0935  
E-mail: Terry.S.Lauck@cop.com

Mr. Glenn von Gonten  
New Mexico Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

March 21, 2014

**Re: NMOCD Case No. 3RP-071, 2013 Annual Remediation and Groundwater Monitoring Report**

Dear Mr. von Gonten:

Enclosed is the 2013 Annual Groundwater Monitoring Report for the Johnston Federal No. 4 Metering Station site. This report, prepared by Conestoga-Rovers & Associates (CRA), contains the results of the mobile dual phase extraction event and annual groundwater monitoring conducted during August and September 2013, respectively.

Please let me know if you have any questions.

Sincerely,

A handwritten signature in blue ink, appearing to read "Terry S. Lauck", written over a faint, larger blue outline of the signature.


Terry S. Lauck

Enc





[www.CRAworld.com](http://www.CRAworld.com)



## 2013 Annual Remediation and Groundwater Monitoring Report

ConocoPhillips Johnston Federal No. 4 Metering Station  
San Juan County, New Mexico  
API# 30-045-10130  
NMOCD # 3RP-71

Prepared for: ConocoPhillips Risk Management and Remediation

### Conestoga-Rovers & Associates

6121 Indian School Road, NE Suite 200  
Albuquerque, New Mexico 87110

January 2014 • 074925 • Report No. 4





## Table of Contents

	Page
<b>Section 1.0 Introduction.....</b>	<b>1</b>
1.1 Background .....	1
<b>Section 2.0 Mobile Dual Phase Extraction.....</b>	<b>2</b>
<b>Section 3.0 Groundwater Sampling Methodology and Analytical Results .....</b>	<b>2</b>
3.1 Groundwater Sampling Methodology .....	2
3.2 Groundwater Analytical Results .....	3
<b>Section 4.0 Conclusions and Recommendations.....</b>	<b>4</b>

## List of Figures (Following Text)

Figure 1	Site Location Map
Figure 2	Site Plan
Figure 3	Geological Cross Section
Figure 4	September 2013 Groundwater Potentiometric Surface Map
Figure 5	September 2013 Benzene Concentration Map

## List of Tables (Following Text)

Table 1	Site History Map
Table 2	Monitor Well Specifications and Groundwater Elevations
Table 3	Groundwater Laboratory Analytical Results Summary

## List of Appendices

Appendix A	August 2013 Mobile Dual Phase Extraction Report
Appendix B	September 2013 Annual Groundwater Sampling Field Forms
Appendix C	September 2013 Annual Groundwater Laboratory Analytical Report



## Section 1.0 Introduction

This report presents the results of a mobile dual phase extraction (MDPE) event and annual groundwater monitoring conducted by Conestoga-Rovers & Associates (CRA) on August 24<sup>th</sup>, 25<sup>th</sup>, and 27<sup>th</sup> and September 17, 2013, respectively, at the ConocoPhillips Company (ConocoPhillips) Johnston Federal No. 4 Metering Station (Site) located on Bureau of Land Management (BLM) land, approximately 13 miles east-northeast of Aztec, San Juan County, New Mexico in Unit Letter M, Section 27, Township 31N, Range 9W (**Figure 1**). A Site detail map is included as **Figure 2**. The Johnston Federal No. 4 wellhead, API # 30-045-10130, is located approximately one-half mile to the southwest of the metering station.

### 1.1 Background

Burlington Resources (Burlington) conducted initial site assessments of two production pits in August 1998. Soil from the separator pit was collected and analyzed for total petroleum hydrocarbons (TPH). The concentration of TPH in separator pit (Production Pit #1, Figure 2) soil was found to be below New Mexico Oil Conservation Division (NMOCD) recommended action levels for this constituent, and the pit was subsequently granted closure by NMOCD. Soil from the tank drain pit (Production Pit #2, Figure 2) was collected and analyzed for benzene, toluene, ethylbenzene, and total xylenes (BTEX) and TPH. Concentrations of these constituents were found to be above NMOCD recommended action levels. Following laboratory results, approximately 3,055 cubic yards of hydrocarbon-impacted soil was excavated in December 1998. Once complete, the excavation was backfilled with clean fill material, and the NMOCD granted pit closure.

A groundwater monitor well, MW-1, was installed at the Site to a depth of 50 feet below ground surface (bgs) in May of 1999. Burlington sampled Monitor Well MW-1 on a quarterly basis until the acquisition of Burlington by ConocoPhillips in March of 2006. Tetra Tech, Inc. (Tetra Tech) began sampling MW-1 in November 2007. In August 2008, three additional groundwater monitor wells were installed under the supervision of Tetra Tech by WDC Exploration and Drilling of Peralta, NM. With information obtained during monitor well installation in 2008, a generalized geologic cross section was completed for the Site and is presented as Figure 3. The existing Burlington/ConocoPhillips monitor well network at the Site includes MW-1, MW-2, MW-3, and MW-4. El Paso Natural Gas (El Paso) owns three additional Site monitor wells. The monitoring schedule of the El Paso-owned monitor wells is not known. Monitor Wells MW-1, MW-2, MW-3, and MW-4 were incorporated into an annual sampling schedule beginning on October 24, 2008.



On June 15, 2011, Site consulting responsibilities were transferred from Tetra Tech to CRA of Albuquerque, NM.

A historical timeline for the Site is presented in Table 1

## Section 2.0 Mobile Dual Phase Extraction

In addition to annual groundwater sampling during September 2013, CRA provided oversight for an MDPE event conducted on August 23<sup>rd</sup>, 24<sup>th</sup>, and 27<sup>th</sup> 2013 by AcuVac of Houston, TX. MDPE is a process combining soil vapor extraction (SVE) with groundwater depression to maximize mass removal of liquid and vapor phase hydrocarbons. A submersible pump is used to simultaneously remove dissolved-phase contaminated groundwater, induce a hydraulic gradient toward the extraction well, and to create the groundwater depression, exposing the capillary fringe or smear zone to SVE. Recovered liquids were discharged to the on-site evaporation tank. Recovered vapors were used as fuel and burned in the MDPE internal combustion engine (ICE). Power generated by the ICE is used to create the induced vacuum for SVE.

During the three days of MDPE, approximately 94 gallons of hydrocarbons (liquid and vapor) were extracted from Monitor Well MW-1. Data from the September 2013 groundwater monitoring event indicate that, while the MDPE event was very effective in removing a significant mass of hydrocarbons, elevated concentrations remain in the groundwater in the vicinity of MW-1 (see Section 3.2). The complete report for MDPE activities performed at the Site was provided by AcuVac and is included as **Appendix A**.

## Section 3.0 Groundwater Sampling Methodology and Analytical Results

### 3.1 Groundwater Sampling Methodology

#### **Groundwater Elevation Measurements**

On September 17, 2013, groundwater elevation measurements were obtained for Monitor Wells MW-1, MW-2, MW-3, and MW-4 using an oil/water interface probe. Groundwater elevations are detailed in **Table 2**. A groundwater potentiometric surface map is presented as **Figure 4**. Based on September 2013 monitoring event data, groundwater flow remains to the east-southeast and is consistent with recent and historical records at this Site. There was no measurable thickness of product present in the Site monitor wells during the 2013 annual groundwater sampling event; however, a slight but continuous hydrocarbon sheen was observed in the purge water generated from Monitor Well MW-1.



**Groundwater sampling**

Groundwater samples were collected from Monitor Wells MW-1, MW-2, MW-3, and MW-4. Approximately three well volumes were purged from each monitor well with a dedicated polyethylene 1.5-inch disposable bailer. Groundwater samples were placed in laboratory prepared bottles, packed on ice, and shipped under chain of custody documentation to Pace Analytical Services, Inc. of Lenexa, Kansas. The samples were analyzed for the presence of BTEX in accordance with Environmental Protection Agency (EPA) Method 8260, naphthalene by EPA Method 8270, sulfate by EPA Method 300.0, and for dissolved manganese and iron by EPA Method 6010. Groundwater sampling field forms are included as **Appendix B**. The associated laboratory analytical report is included as **Appendix C**.

**3.2 Groundwater Analytical Results**

The New Mexico Water Quality Control Commission (NMWQCC) mandates that groundwater quality in New Mexico be protected, and has issued groundwater quality standards in Title 20, Chapter 6, Part 2, Section 3103 of the New Mexico Administrative Code (20.6.2.3103 NMAC). Groundwater quality standards have been set for the protection of human health, domestic water supply, and irrigation use. Exceedences of NMWQCC groundwater quality standards in Site monitor wells are discussed below. Results are summarized in **Table 3**.

- **Benzene**
  - The NMWQCC standard for benzene is 0.010 milligrams per liter (mg/L). The groundwater sample collected from MW-1 in September 2013 contained benzene at a concentration of 4.69 mg/L.
- **Toluene**
  - The NMWQCC standard for toluene is 0.75 mg/L. The groundwater sample collected from MW-1 contained toluene at a concentration of 7.55 mg/L.
- **Ethylbenzene**
  - The NMWQCC standard for ethylbenzene is 0.75 mg/L. The groundwater sample collected from MW-1 contained a concentration of ethylbenzene of 1.17 mg/L.
- **Total Xylenes**
  - The NMWQCC standard for total xylenes is 0.620 mg/L. The groundwater sample collected from MW-1 contained xylenes at a concentration of 11.0 mg/L.



- **Naphthalenes**

- The NMWQCC standard for naphthalenes is 0.03 mg/L. The groundwater sample collected from MW-1 contained naphthalenes at a concentration of 0.0365 mg/L.

- **Sulfate**

- The NMWQCC standard for sulfate is 600 mg/L. Groundwater collected from Monitor Wells MW-2, MW-3, and MW-4 was found to exceed the standard for sulfate during September 2013. Sulfate concentrations were 1,230 mg/L, 808 mg/L, and 925 mg/L, respectively.

- **Dissolved Manganese**

- The NMWQCC standard for dissolved manganese is 0.2 mg/L. Groundwater collected from Monitor Wells MW-1, MW-3, and MW-4 was found to exceed the standard for dissolved manganese during September 2013. Dissolved manganese concentrations were 0.89 mg/L, 0.67 mg/L, and 1.6 mg/L, respectively.

## **Section 4.0 Conclusions and Recommendations**

Approximately 94 gallons of hydrocarbons were successfully removed from the subsurface at Monitor Well MW-1 during the August 2013 MDPE event. The concentration of benzene in groundwater of Monitor Well MW-4, downgradient from MW-1, has also been significantly reduced to below the NMWQCC standard. This serves as further evidence of the beneficial plume-shrinking effect of the induced gradient toward the extraction well as a result of the MDPE event.


CRA recommends conducting additional MDPE events at the Site to attempt to remove additional hydrocarbons from the subsurface. AcuVac, subsequent to their final September 2013 MDPE event report (Appendix A), further evaluated Site data and recommended a modification to MDPE event methodology. Enhanced Vacuum Recovery, in combination with the MDPE, is recommended to maximize overall mass removal of hydrocarbons and, more specifically, to more efficiently volatilize and remove the dissolved-phase BTEX constituents in the groundwater of MW-1.



Monitor Well MW-1 continues to exceed NMWQCC standards for BTEX constituents. Concentrations of sulfate and dissolved manganese also continue to be detected above NMWQCC groundwater quality standards in Site monitor wells. CRA recommends continued annual sampling of Site monitor wells until all monitored groundwater quality parameters approach NMWQCC standards. CRA will begin a quarterly sampling schedule once all parameters are near or below NMWQCC standards or background levels.

The next groundwater monitoring event at the Johnston Federal No. 4 Metering Station is scheduled to take place during September of 2014 and will include analyses for BTEX, naphthalene, dissolved manganese, dissolved iron, and sulfate.





SOURCE: USGS 7.5 MINUTE QUAD  
"TURLEY, NEW MEXICO"

LAT/LONG: 36.8626° NORTH, 107.7723° WEST  
COORDINATE: NAD83 DATUM, U.S. FOOT  
STATE PLANE ZONE - NEW MEXICO WEST

Figure 1

**SITE LOCATION MAP**  
**JOHNSTON FEDERAL No. 4 METERING STATION**  
**SECTION 27, T31N-R09W, SAN JUAN COUNTY, NEW MEXICO**  
*ConocoPhillips Company*









Figure 2  
SITE PLAN  
JOHNSTON FEDERAL No. 4 METERING STATION  
SECTION 27, T31N-R09W, SAN JUAN COUNTY, NEW MEXICO  
*ConocoPhillips Company*












Figure 4

SEPTEMBER 2013 GROUNDWATER POTENTIOMETRIC SURFACE MAP  
 JOHNSTON FEDERAL No. 4 METERING STATION  
 SECTION 27, T31N-R09W, SAN JUAN COUNTY, NEW MEXICO  
*ConocoPhillips Company*








Figure 5

SEPTEMBER 2013 BENZENE CONCENTRATION MAP  
 JOHNSTON FEDERAL No. 4 METERING STATION  
 SECTION 27, T31N-R09W, SAN JUAN COUNTY, NEW MEXICO  
*ConocoPhillips Company*





TABLE 1

**SITE HISTORY TIMELINE  
CONOCOPHILLIPS COMPANY  
JOHNSTON FEDERAL No. 4 METERING STATION  
SAN JUAN COUNTY, NM**

<i>Date/Time Period</i>	<i>Event/Action</i>	<i>Description/Comments</i>
August 1952	Well Spudded	Well was spudded by Anderson-Prichard Oil Corporation on August 21, 1952.
April 1961	Transfer of Well Ownership	Ownership of the well transferred from Anderson-Prichard Oil Corporation to Union Texas Natural Gas Corporation on April 26, 1961.
September 1971	Transfer of Well Ownership	Meridian Oil Inc., a wholly-owned subsidiary of Burlington Resources, took over operation of well from Union Texas Petroleum Corporation on September 17, 1991.
August 1994	Initial Site Assessment	El Paso Energy conducted a site assessment of a former unlined pit near the metering station.
September 1994	Pit Excavation	El Paso Energy excavated ~60 cubic yards of soil from their former unlined pit.
August 1995	Monitor Well Installation	El Paso contracted Philip Environmental Services Corporation to install a monitor well in the vicinity of their former pit on August 9, 1995.
December 1995	Monitor Well Installation	El Paso contracted Philip Environmental Services Corporation to install two downgradient monitor wells between December 12 and 15, 1995.
August 1997	Product Removal	El Paso Energy commenced product removal from their MW-1 on August 26, 1997.
September 1997	Piezometer Installation	El Paso contracted Philip Environmental Services Corp. to install 3 temporary piezometers on September 15, 1997.
July 1998	NMOCD Communication With Site Operators	New Mexico Oil Conservation Division (NMOCD) issued a response letter to El Paso Field Services (EPFS) on July 8, 1998, indicating that they would be sending letters to the operators of the sites (including Burlington Resources) and that EPFS should work cooperatively with the operators on investigation and remediation activities.
July 1998	NMOCD Requests Groundwater Investigation by Burlington Resources	NMOCD issued a letter to Burlington Resources on July 9, 1998, referencing work done at the Site by EPFS and requiring Burlington Resources (BR) to immediately implement their previously approved pit closure plan. The letter also required BR to submit a comprehensive groundwater investigation and remediation plan for all pit closure Sites in the San Juan Basin that encounter groundwater.
August 1998	Burlington Resources Granted Closure of Pit #1	Burlington Resources sampled Pit #1 on August 10, 1998 and laboratory analytical results indicated closure was warranted.
August 1998	Initial Site Assessment	Initial site assessment conducted on the site separator pit. Soil from this area was collected and analyzed for total petroleum hydrocarbons (TPH) and was found to contain TPH below NMOCD recommended action levels. The pit was subsequently granted closed status by NMOCD.
August 1998	Initial Site Assessment	Initial site assessment conducted on the tank drain pit. Soil from this area was collected and analyzed for benzene, toluene, ethylbenzene, and total xylenes (BTEX) and for TPH. Concentrations of these constituents were found to be above NMOCD recommended action levels.
December 1998	Pit Excavation	Burlington Resources excavated ~3,055 cubic yards of hydrocarbon-impacted soil from Pit #2 (58 ft x 45 ft x 30 ft deep), starting on December 17, 1998. The excavation extended to ~30 feet below ground surface (practical extent). The bottom of the excavation was sampled on December 28, 1998.
May 1999	Monitor Well Installation	Monitor Well MW-1 installed to a depth of 50 feet below ground surface (bgs); the screened interval was placed from 35 to 50 feet bgs, and was installed in the center of pit #2. Burlington Resources began monitoring MW-1 on a quarterly basis.
June 1999	Confirmation of Groundwater Impacts	Laboratory analysis of groundwater from MW-1 shows levels of benzene, toluene, and total xylenes in excess of New Mexico Water Quality Control Commission (NMWQCC) groundwater quality standards. Burlington Resources notified NMOCD via E-mail on June 1, 1999.
July 2001	NMOCD Communication With Site Operators	NMOCD response letter sent to EPFS on July 18, 2001 again urges EPFS to work cooperatively with the operators to investigate and remediate contaminated groundwater.



TABLE 1

**SITE HISTORY TIMELINE  
CONOCOPHILLIPS COMPANY  
JOHNSTON FEDERAL No. 4 METERING STATION  
SAN JUAN COUNTY, NM**

<i>Date/Time Period</i>	<i>Event/Action</i>	<i>Description/Comments</i>
April 2003	NMOCD Requests Monitor Well Installation	NMOCD response letter to EPFS sent on April 3, 2003, requires EPFS to install additional monitor wells to determine the real extent of groundwater impacts.
March 2006	Acquisition of Burlington Resources by ConocoPhillips Company	ConocoPhillips Company acquired Burlington Resources on March 31, 2006.
November 2007 and January 2008	3rd and 4th Quarter 2007 Groundwater Monitoring	Johnston Federal No. 4 Monitoring Station groundwater sampled during November 2007 and January 2008 by Tetra Tech.
March 2008	Reporting	2007 Annual Groundwater Monitoring Report submitted to NMOCD.
March 2008	Groundwater Monitoring	Tetra Tech conducts quarterly groundwater monitoring at the Site for BTEX.
April 2008	NMOCD Requests Further Investigation	NMOCD indicates additional investigation and sampling is necessary for closure consideration during a meeting with Glenn Von Gonten.
April 2008	1st Quarter 2008 Groundwater Monitoring	Tetra Tech conducts quarterly groundwater monitoring at the Site for BTEX in MW-1 on April 30, 2008. Note: Prior to this date the location of MW-1 was not clear and the incorrect well was sampled. This was the first quarter that ConocoPhillips MW-1 was sampled. BTEX constituents were found to be above NMWQCC standards in MW-1.
July 2008	2nd Quarter 2008 Groundwater Monitoring	Tetra Tech conducts quarterly groundwater monitoring at the Site for BTEX in MW-1.
August 2008	Groundwater Monitor Well Installation	Monitor Wells MW-2, MW-3, and MW-4 installed under the supervision of Tetra Tech by WDC Exploration and Wells of Peralta, NM.
October 2008	3rd Quarter 2008 groundwater Monitoring	Tetra Tech conducts quarterly monitoring at the Site for MW-1 through MW-4. MW-2, MW-3 and MW-4 groundwater samples are analyzed for baseline parameters including major ions, total metals, semi-volatile organic compounds (SVOCs), volatile organic compounds (VOCs) including BTEX, diesel range organics, and gasoline range organics as requested by the NMOCD. In addition, an expanded list (beyond BTEX analysis) of VOCs were included for MW-1.
January 2009	4th Quarter 2008 Groundwater Monitoring	Tetra Tech conducts quarterly monitoring at the Site for MW-1 through MW-4. The groundwater sample obtained for MW-1 is analyzed for baseline parameters including major ions, total metals, SVOCs, VOCs, diesel range organics, and gasoline range organics. As of January 2009, baseline parameters have been collected for all 4 groundwater monitor wells at the Site.
September 25, 2009	2009 Annual Groundwater Monitoring	Tetra Tech conducts annual groundwater monitoring at the Site for MW-1 through MW-4 with analyses for BTEX, naphthalene, dissolved Fe and Mn and sulfate.
September 22, 2010	2010 Annual Groundwater Monitoring	Tetra Tech conducts annual groundwater monitoring at the Site for MW-1 through MW-4 with analyses for BTEX, naphthalene, dissolved Mn and sulfate.
June 15, 2011	Transfer of Site Consulting Responsibilities	Site consulting responsibilities transferred from Tetra Tech, Inc. to Conestoga-Rovers & Associates, Inc. (CRA) of Albuquerque, NM.
September 28, 2011	2011 Annual Groundwater Monitoring	CRA conducts annual groundwater monitoring at the Site for MW-1 through MW-4 with analyses for BTEX, naphthalene, dissolved Mn, dissolved Fe, and sulfate.
September 26, 2012	2012 Annual Groundwater Monitoring	CRA conducts annual groundwater monitoring at the Site for MW-1 through MW-4 with analyses for BTEX, naphthalene, dissolved Mn, dissolved Fe, and sulfate.
August 23, 2013 - August 27, 2013	Dual-Phase Extraction	AcuVac, under CRA oversight, performs three days of dual-phase extraction on MW-1.
September 17, 2013	2013 Annual Groundwater Monitoring	CRA conducts annual groundwater monitoring at the Site for MW-1 through MW-4 with analyses for BTEX, naphthalene, dissolved Mn, dissolved Fe, and sulfate.



TABLE 2

**MONITOR WELL SPECIFICATIONS AND GROUNDWATER ELEVATIONS**  
**CONOCOPHILLIPS COMPANY**  
**JOHNSTON FEDERAL No. 4**  
**SAN JUAN COUNTY, NM**

<i>Well ID</i>	<i>Total Depth (ft bgs)</i>	<i>Screen Interval (ft)</i>	<i>*Elevation (ft) (TOC)</i>	<i>Date Measured</i>	<i>Depth to Groundwater (ft below TOC)</i>	<i>Relative Groundwater Elevation</i>
MW-1	51.79	35 - 50	100	5/25/1999	NM	NM
				9/1/1999	47.02	52.98
				12/1/1999	46.96	53.04
				1/18/2000	44.05	55.95
				5/17/2000	46.90	53.10
				9/8/2000	46.91	53.09
				12/20/2000	46.88	53.12
				3/27/2001	NM	NM
				6/27/2001	47.05	52.95
				9/17/2001	46.93	53.07
				12/19/2001	46.97	53.03
				3/25/2002	46.99	53.01
				6/25/2002	47.01	52.99
				9/24/2002	46.98	53.02
				12/30/2002	47.40	52.60
				3/27/2003	NM	NM
				6/27/2003	NM	NM
				10/10/2003	NM	NM
				12/10/2003	NM	NM
				3/16/2004	47.28	52.72
				6/22/2004	47.06	52.94
				9/30/2004	47.24	52.76
				12/13/2004	47.14	52.86
				3/23/2005	46.91	53.09
				6/22/2005	46.93	53.07
				10/28/2005	46.87	53.13
				12/14/2005	46.72	53.28
				3/20/2006	46.75	53.25
				6/21/2006	46.84	53.16
				10/20/2006	46.89	53.11
				12/13/2006	46.92	53.08
				11/9/2007	NM	NM
				1/15/2008	NM	NM
				4/30/2008	46.45	53.55
				7/23/2008	46.63	53.37
				10/24/2008	46.60	53.40
				1/29/2009	46.57	53.43
				4/23/2009	46.40	53.60
				9/25/2009	46.52	53.48
				9/22/2010	46.60	53.40
				9/28/2011	46.65	53.35
				9/26/2012	46.80	53.20
				9/17/2013	46.88	53.12



TABLE 2

**MONITOR WELL SPECIFICATIONS AND GROUNDWATER ELEVATIONS**  
**CONOCOPHILLIPS COMPANY**  
**JOHNSTON FEDERAL No. 4**  
**SAN JUAN COUNTY, NM**

<i>Well ID</i>	<i>Total Depth (ft bgs)</i>	<i>Screen Interval (ft)</i>	<i>*Elevation (ft) (TOC)</i>	<i>Date Measured</i>	<i>Depth to Groundwater (ft below TOC)</i>	<i>Relative Groundwater Elevation</i>
MW-2	65.5	41.5 - 61.5	97.71	10/24/2008	42.85	54.86
				1/29/2009	42.83	54.88
				4/23/2009	42.75	54.96
				9/25/2009	42.82	54.89
				9/22/2010	43.01	54.70
				9/28/2011	43.14	54.57
				9/26/2012	43.33	54.38
				9/17/2013	43.51	54.20
MW-3	59	35 - 55	94.65	10/24/2008	43.91	50.74
				1/29/2009	41.97	52.68
				4/23/2009	41.87	52.78
				9/25/2009	42.04	52.61
				9/22/2010	42.17	52.48
				9/28/2011	42.22	52.43
				9/26/2012	42.36	52.29
				9/17/2013	42.47	52.18
MW-4	61	37 - 57	94.79	10/24/2008	43.11	51.68
				1/29/2009	43.11	51.68
				4/23/2009	43.06	51.73
				9/25/2009	43.20	51.59
				9/22/2010	43.39	51.40
				9/28/2011	43.45	51.34
				9/26/2012	43.57	51.22
				9/17/2013	43.65	51.14

**Notes:**

ft = Feet

TOC = Top of casing

bgs = below ground surface

\* Elevation relative to the TOC of MW-1, set at arbitrary 100 feet.

NM = Not measured



GROUNDWATER LABORATORY ANALYTICAL RESULTS SUMMARY  
CONOCOPHILLIPS COMPANY  
JOHNSTON FEDERAL No. 4  
SAN JUAN COUNTY, NM

Well ID	Sample ID	Date	Sample Type	Benzene (mg/L)	Toluene (mg/L)	Ethylbenzene (mg/L)	Xylenes (total) (mg/L)	Napthalene (mg/L)	Sulfate (mg/L)	Iron (dissolved) (mg/L)	Manganese (dissolved) (mg/L)
MW-1	MW-1	5/25/1999	(orig)	8.7	2.9	2.8	2.9	--	--	--	--
	MW-1	12/1/1999	(orig)	4.7	1.3	0.9	10	--	--	--	--
	MW-1	1/18/2000	(orig)	3.6	0.82	0.84	7.5	--	--	--	--
	MW-1	5/17/2000	(orig)	6.9	1.1	1.5	17	--	--	--	--
	MW-1	9/8/2000	(orig)	4.6	0.62	0.93	10	--	--	--	--
	MW-1	12/20/2000	(orig)	< 0.0002	0.0005	0.034	0.061	--	--	--	--
	MW-1	3/27/2001	(orig)	5.43	0.641	0.991	9.83	--	--	--	--
	MW-1	6/27/2001	(orig)	5.87	0.9	0.99	10.4	--	--	--	--
	MW-1	9/17/2001	(orig)	5.91	0.75	0.98	10.7	--	--	--	--
	MW-1	12/19/2001	(orig)	7.2	0.65	1.02	11.3	--	--	--	--
	MW-1	3/25/2002	(orig)	5.52	0.83	1.19	10.5	--	--	--	--
	MW-1	6/26/2002	(orig)	0.516	0.0662	0.0787	0.863	--	--	--	--
	MW-1	9/24/2002	(orig)	5.31	8	0.88	13.96	--	--	--	--
	MW-1	12/30/2002	(orig)	7.66	10.2	0.76	14.14	--	--	--	--
	MW-1	6/22/2004	(orig)	6.16	8.1	0.47	15.84	--	--	--	--
	MW-1	3/20/2006	(orig)	3.17	3.74	1.06	30.13	--	--	--	--
	MW-1	6/21/2006	(orig)	4.9	3.28	0.448	2.39	--	--	--	--
	MW-1	12/13/2006	(orig)	5.3	7.2	0.87	15.45	--	--	--	--
	MW-1	3/27/2007	(orig)	6.87	5.72	0.21	12.16	--	--	--	--
	MW-1	6/25/2007	(orig)	5.68	1.83	0.4	9.48	--	--	--	--
	MW-1	4/30/2008	(orig)	6.3	1.8	0.28 J	8.6	--	--	--	--
	MW-1	7/23/2008	(orig)	7.1	2.2	0.45	10.6	--	--	--	--
	MW-1	10/24/2008	(orig)	6	2.1	0.4	9	0.044	--	--	--
	MW-1	1/29/2009	(orig)	6.7	2.2	0.63	14.5	0.061	315	--	--
	MW-1	9/25/2009	(orig)	3.9	1.5	0.68	9.8	0.04	429	< 0.02	1.11
	MW-1	9/22/2010	(orig)	3.5	0.98	0.63	7.5	0.049	190	--	0.752
	GW-074925-092811-CM-004	9/28/2011	(orig)	3.36	1.05	0.667	6.81	0.037	202	< 0.05	0.774
	GW-074925-092811-CM-005	9/28/2011	(Duplicate)	3.43	1.12	0.779	8.29	--	--	--	--
MW-2	GW-074925-092612-CM-MW-1	9/26/2012	(orig)	3.07	0.599	0.577	5.16	0.0398	113	< 0.05	0.67
	GW-074925-091713-CM-MW-1	9/17/2013	(orig)	4.69	7.55	1.17	11.0	0.0365	371	< 0.05	0.89
	GW-074925-091713-CM-DUP	9/17/2013	(Duplicate)	4.70	7.21	1.04	9.97	--	--	--	--
	MW-2	10/24/2008	(orig)	< 0.0005	< 0.0005	< 0.0005	< 0.0005	< 0.005	974	--	--
	MW-2	1/29/2009	(orig)	< 0.0005	< 0.0005	< 0.0005	< 0.0005	--	--	--	--
	MW-2	9/25/2009	(orig)	< 0.001	< 0.001	< 0.001	< 0.002	< 0.001	1260	< 0.02	0.04
MW-3	MW-2	9/22/2010	(orig)	< 0.001	< 0.001	< 0.001	< 0.001	< 0.001	1350	--	0.0074
	GW-074925-092811-CM-002	9/28/2011	(orig)	< 0.001	< 0.001	< 0.001	< 0.003	< 0.0001	1290	2.49	0.0956
	GW-074925-092612-CM-MW-2	9/26/2012	(orig)	< 0.001	< 0.001	< 0.001	< 0.003	< 0.0005	1210	< 0.05	< 0.005
	GW-074925-091713-CM-MW-2	9/17/2013	(orig)	< 0.001	< 0.001	< 0.001	< 0.003	< 0.0005	1230	< 0.05	< 0.005
	MW-3	10/24/2008	(orig)	0.02	< 0.0005	< 0.0005	0.024	< 0.005	714	--	--
	MW-3	1/29/2009	(orig)	0.012	< 0.0005	< 0.0005	0.005	--	--	--	--
MW-4	MW-3	9/25/2009	(orig)	0.0021	< 0.001	< 0.001	< 0.002	< 0.001	1070	< 0.02	1.24
	MW-3	9/22/2010	(orig)	0.0042	< 0.001	< 0.001	< 0.001	< 0.001	1060	--	1.11
	GW-074925-092811-CM-003	9/28/2011	(orig)	0.0038	< 0.001	< 0.001	< 0.003	< 0.0001	809	1.58	0.704
	GW-074925-092612-CM-MW-3	9/26/2012	(orig)	0.0016	< 0.001	< 0.001	< 0.003	< 0.0005	892	0.063	0.67
	GW-074925-091713-CM-MW-3	9/17/2013	(orig)	0.0012	< 0.001	< 0.001	< 0.003	< 0.0005	808	0.80	0.67
	MW-4	10/24/2008	(orig)	0.024	< 0.0005	0.006	0.01	< 0.005	678	--	--
MW-4	MW-4	1/29/2009	(orig)	0.11	0.006	0.009	0.147	< 0.005	--	--	--
	MW-4	9/25/2009	(orig)	0.0088	< 0.001	0.0057	0.002	< 0.001	968	0.508	1.24
	MW-4	9/22/2010	(orig)	0.019	0.005	0.0069	0.0057	< 0.001	1040	--	1.27
	GW-074925-092811-CM-001	9/28/2011	(orig)	0.0256	0.0078	0.0017	0.0106	< 0.0001	960	0.532	1.82
	GW-074925-092612-CM-MW-4	9/26/2012	(orig)	0.0124	0.0023	< 0.001	< 0.003	< 0.0005	949	0.57	1.5
	GW-074925-092612-CM-DUP	9/26/2012	(Duplicate)	0.0130	0.0022	< 0.001	0.0031	--	--	--	--
	GW-074925-091713-CM-MW-4	9/17/2013	(orig)	0.0065	< 0.001	< 0.001	< 0.003	< 0.0005	925	0.51	1.6
NMWQCC Groundwater Quality Standards				0.01	0.75	0.75	0.62	0.03	600	1	0.2

**Notes:**

NMWQCC = New Mexico Water Quality Control Commission

mg/L = milligrams per liter (parts per million)

&lt;0.7 = Below laboratory detection limit of 0.7 mg/L

J = Estimated value between MDL and PQL

**Bold** = concentrations that exceed the NMWQCC groundwater quality standard



## **Appendix A**

### **August 2013 Mobile Dual Phase Extraction Report**





## AcuVac Remediation, LLC.

1656-H Townhurst, Houston, Texas 77043  
713.468.6688 • Fax: 713.468.6689 • [www.acuvac.com](http://www.acuvac.com)

August 30, 2013

Mr. Jeff Walker  
Project Manager  
Conestoga-Rovers & Associates  
6121 Indian School Road NE  
Albuquerque, NM 87110

Dear Jeff:

Re: MDP Events, Johnston Federal No. 4, Aztec, NM

Enclosed is a copy of the Operating Data collected during the Mobile Dual Phase (MDP) Events #1, 2 and 3, at the above location on August 23, 24 and 27, 2013. Table #1 is the Well Data Information on well MW-1. PSH is referred to LNAPL in this report. GW samples are taken frequently in a 2,000 ml beaker, to determine the average LNAPL percentage and volume.

### **Summary of MDP Event #1 - Well MW-1**

- The total Event time was 8.0 hours. There is no comparative data. The Event was conducted on August 23, 2013.
- The total liquid volume recovered was 191 gals, with an estimated volume of 1.0 gal of LNAPL.
- Total vapor LNAPL burned as IC engine fuel was 29.95 gals, **for a total liquid and vapor LNAPL recovery of 30.95 gals. This equates to an average of 3.87 gals/hr.**
- Average HORIBA Analytical Data from the influent vapor samples was:  
HC = 61,801 ppmv, CO<sub>2</sub> = 7.59%, CO = 2.17%, O<sub>2</sub> = 4.7% and H<sub>2</sub>S = 19.53 ppm.
- The Average Induced Vacuum was 71.0"H<sub>2</sub>O with a maximum vacuum of 75"H<sub>2</sub>O and the average EW well vapor flow was 31.14 scfm.
- The GW pump was set at 50.5 ft BTOC. The average GW pump rate was 0.39 gpm.
- The average GW depression, based on the positioning of the GW pump, was 5.50 ft below static level.
- A LNAPL thickness of 0.02 ft was recorded prior to the start of Event #1 and no LNAPL was recorded at the conclusion of the Event.

**The total LNAPL removed, including liquid and vapor, during the 8.0 hour Event #1 Well MW-1 was 30.95 gals.**



#### **Additional Information:**

- An estimated volume of 1.0 gal of liquid LNAPL was recovered during the 8.0 hour Event.
- The recovered groundwater was dark with biomass at the start of the Event and then cleared after approximately 1.0 hr.
- The high HC (TPH) levels indicate contaminant in the LNAPL range.
- The HC (TPH) levels remained mostly steady throughout the Event.
- The low O<sub>2</sub> levels in the influent vapors indicate SVE short circuiting from the ground surface did not occur.
- The H<sub>2</sub>S levels varied from a high of 24.0 ppm to a low of 13.0 ppm.

#### **Summary of MDP Event #2: Well MW-1**

- The total Event time was 8.0 hours. The Event was conducted on August 24, 2013. The data is compared to Event #1 conducted on August 23, 2013 which had a total Event time of 8.0 hours.
- The total liquid volume recovered was 108 gals, of which 1.5 gals were LNAPL.
- Total vapor LNAPL burned as IC engine fuel was 30.10 gals, **for a total liquid and vapor LNAPL recovery of 31.60 gals. This equates to an average of 3.95 gals/hr.**
- Average HORIBA Analytical Data from the influent vapor samples was:  
HC = 58,276 ppmv, CO<sub>2</sub> = 7.95%, CO = 1.88%, O<sub>2</sub> = 5.0% and H<sub>2</sub>S = 13.71 ppm.
- Compared with MDP Event #1 data, the TPH levels decreased 3,524 ppmv, CO<sub>2</sub> increased 0.40%, CO decreased 0.29%, O<sub>2</sub> increased 0.3% and H<sub>2</sub>S decreased 5.82 ppm.
- The Average Induced Vacuum was 70"H<sub>2</sub>O with a maximum vacuum of 70"H<sub>2</sub>O and the average EW well vapor flow was 33.20 scfm.
- Compared with Event #1 data, the Average Induced Vacuum decreased 1.0"H<sub>2</sub>O, and the average well vapor flow increased 2.06 scfm.
- The GW pump was set at 50.5 ft BTOC. The average GW pump rate was 0.22 gpm.
- The average GW depression, based on the positioning of the GW pump, was 5.5 ft below static level.
- A LNAPL thickness of 0.03 ft was recorded prior to the start of Event #2 and no LNAPL was recorded at the conclusion of the Event.

**The total LNAPL removed, including liquid and vapor, during the 8.0 hour Event #2 Well MW-1 was 31.60 gals.**

#### **Additional Information:**

- An estimated volume of 1.5 gals of liquid LNAPL were recovered during the 8.0 hour Event.
- The high HC (TPH) levels indicate contaminant in the LNAPL range.
- The HC (TPH) levels remained mostly steady throughout the Event.
- The low O<sub>2</sub> levels in the influent vapors indicate SVE short circuiting from the ground surface did not occur.



- Well MW-3 (57.0 ft) and Well MW-4 (61.1 ft from Well MW-1) were sealed with plugs designed to accept magnehelic gauges or digital manometers. The wells were then monitored on a periodic basis to determine the influence of the induced vacuum that was applied to Well MW-1. Wells MW-3 and MW-4 were slightly influenced by the induced vacuum, but not to the extent to be considered in the radius of influence.

#### **Summary of MDP Event #3: Well MW-1**

- The total Event time was 8.0 hours. The Event was conducted on August 27, 2013. The data is compared to Event #2 conducted on August 24, 2013 which had a total Event time of 8.0 hours.
- The total liquid volume recovered was 106 gals, of which an estimated 2.0 gals were LNAPL.
- Total vapor LNAPL burned as IC engine fuel was 29.01 gals, **for a total liquid and vapor LNAPL recovery of 31.01 gals. This equates to an average of 3.88 gals/hr.**
- Average HORIBA Analytical Data from the influent vapor samples was:  
HC = 56,152 ppmv, CO<sub>2</sub> = 7.34%, CO = 1.62%, O<sub>2</sub> = 4.5% and H<sub>2</sub>S = 0 ppm.
- Compared with MDP Event #2 data, the TPH levels decreased 2,110 ppmv, CO<sub>2</sub> decreased 0.58%, CO decreased 0.23%, O<sub>2</sub> decreased 0.5% and H<sub>2</sub>S decreased 13.59 ppm.
- The Average Induced Vacuum was 70"H<sub>2</sub>O with a maximum vacuum of 70"H<sub>2</sub>O and the average EW well vapor flow was 33.20 scfm.
- Compared with Event #2 data, the Average Induced Vacuum and the average well vapor flow remained steady.
- The GW pump was set at 50.5 ft BTOC. The average GW pump rate was 0.22 gpm.
- The average GW depression, based on the positioning of the GW pump, was 5.5 ft below static level.
- No LNAPL was recorded prior to the start of Event #3 and a LNAPL thickness of 0.01 ft was recorded at the conclusion of the Event.

**The total LNAPL removed, including liquid and vapor, during the 8.0 hour Event #3 (Well MW-1) was 31.01 gals.**

#### **Additional Information:**

- An occasional slug of LNAPL was recovered with the ground water. Total LNAPL recovered during the 8.0 hour Event is estimated to be 2.0 gals.
- The high HC (TPH) levels indicate contaminant in the LNAPL range.
- The HC (TPH) levels remained mostly steady throughout the Event.
- The low O<sub>2</sub> levels in the influent vapors indicate SVE short circuiting from the ground surface did not occur.

#### **Other Information - Events #1, 2 & 3**

**The total LNAPL removed, including liquid and vapor, during the 24.0 hr Events #1, 2 & 3 (Well MW-1) was 93.56 gals. This equates to 3.90 gals/hr.**



### **General Overview**

The vadose zone and the exposed saturated zone is highly contaminated with LNAPL. This conclusion is based on the high TPH levels and the fact that the influent LNAPL vapors provided 100% of the Internal Combustions Engine's fuel, i.e., no propane was required. There may be some liquid LNAPL pooled in an area outside of the Induced Hydraulic Gradient (IHG) Radius of Influence (ROI). The IHG occurs when the LNAPL/GW depression in the extraction well is maintained during the Event period. The IHG at this site is estimated to have an ROI of 25 to 30 ft. The estimated total liquid LNAPL recovery of 5.0 gals during the three Event periods was based on the sheen of LNAPL observed in the collection tank and observed slugs of LNAPL passing through the clear sight tube of the liquid volume discharge line.

Schedule A illustrates the changes in the TPH levels during each of the three Events. During Event #1, the TPH levels increased during the first hour as the Induced Well Vacuum drew the LNAPL vapors into the well bore, and were then on an overall decreasing trend for the remainder of the Event. The TPH levels at the end of Event #1 were at approximately the same level as the start. There was a recovery time of approximately 14 hours between the end of Event #1 and the start of Event #2. At the start of Event #2, the TPH levels were approximately 1,460 ppmv lower than the end of Event #1. For Events #2 and #3, the TPH levels were on a mostly decreasing trend during each Event. The TPH in the formation rebounded slightly as the beginning levels for Event #3 were slightly higher (400 ppmv), than at the end of Event #2.

The average TPH levels for Events #1, 2 & 3 were, 61,801, 58,263 and 56,152, respectively.

The ending TPH levels for Events #1, 2 & 3 were, 60,420, 57,220 and 54,180, respectively.

Given the decrease in the average TPH levels measured in ppmv from Event #1 to the subsequent Events, as well as the ending TPH level for each Event, this site would benefit from a program of regular MDP Events to fully remediate the site.

The HORIBA Analytical instrument is calibrated with Hexane and CO<sub>2</sub>. In all subsequent Events, the test data will be compared to the previous Event to evaluate the progress for this remediation project.

The formula used to calculate the emission rate is:

$$ER = HC \text{ (ppmv)} \times MW \text{ (Hexane)} \times \text{Flow Rate (scfm)} \times 1.58E^{-7} \frac{(\text{min})(\text{lb mole})}{(\text{hr})(\text{ppmv})(\text{ft}^3)} = \text{lbs/hr}$$


### **Additional information included with Report**

- Schedule A- Summary of the Influent Well Vapors
- Recorded Data
- Photographs of the MDP System and well MW-1.



After you have reviewed the report and if you have any questions, please contact me. We appreciate you selecting AcuVac to provide this service.

Sincerely,

A handwritten signature in blue ink, appearing to read "James E. Sadler", with a stylized flourish at the end.

James E. Sadler, VP  
Engineering/Environmental

130037.REP



## Well and Recovery Data Information


**Table #1**

Event		1	2	3
<b>WELL NO.</b>		<b>MW-1</b>	<b>MW-1</b>	<b>MW-1</b>
Total Event Hours		8.0	8.0	8.0
TD	ft	52.30	52.30	52.30
Well Screen	ft	15' to 45'	15' to 45'	15' to 45'
Well Size	in	2.0	2.0	2.0
DTGW - Static - Start Event	ft	46.85	47.18	46.89
DTLNAPL - Static - Start Event	ft	46.83	47.15	-
LNAPL	ft	0.02	0.03	-
DTGW - End Event	ft	47.68	47.38	47.38
DTLNAPL - End Event	ft	-	-	47.37
LNAPL	ft	-	-	.01
Average Extraction Well Vacuum	"H <sub>2</sub> O	71.0	70.0	70.0
Average Extraction Well Vapor Flow	scfm	31.14	33.20	33.20
Average GW/LNAPL Pump Rate	gpm	0.39	0.22	0.22
Total Liquid Volume Recovered	gals	191	108	106
Average TPH	ppmv	61,801	58,263	56,152
Average CO <sub>2</sub>	%	7.59	7.92	7.34
Average CO	%	2.17	1.85	1.62
Average O <sub>2</sub>	%	4.7	5.0	4.5
Average H <sub>2</sub> S	ppm	19.53	13.59	-
Total Liquid LNAPL Recovered	gals	1.0	1.5	2.0
Total Liquid LNAPL Recovered	%	0.52	1.39	1.89
Total Vapor and Liquid LNAPL Recovered	gals	30.95	31.60	31.01
Total LNAPL Recovered	lbs	216.6	221.2	217.1
Total Volume of Well Vapors	cu. ft	14,947	15,936	15,936



**SCHEDULE A**  
**SUMMARY of MDP TESTS**  
**#1, #2 and #3**

JOHNSTON FEDERAL NO. 4  
 AZTEC, NEW MEXICO  
 August 23, 24 and 27, 2013







Location: Johnston Federal #4, San Juan County, NM			Project Managers: Sadler/Faucher				
Date: 8-23-13			-	-	-	-	-
Parameters	Time	0900	0930	1000	1030	1100	1130
	Hr Meter	6538.0	6538.5	6539.0	6539.5	6540.0	6540.5
WELL # MW- 1							
ENGINE/BLOWER	R.P.M.	2300	2200	2200	2200	2300	2300
	Oil Pressure psi	50	50	50	50	50	50
	Water Temp °F	140	160	160	160	160	160
	Volts	13	13	13	13	13	13
	Intake Vacuum "Hg	17	17	17	17	17	16
	Gas Flow Fuel/Propane cfh	10	10	5	5	5	0
ATMOSPHERE/VACUUM/AIR PUMP/VOLUME	GW Pump ON/OFF	OFF/ON	ON	ON	ON	ON	ON
	Extraction Well Flow scfm	22.95	22.95	24.53	23.72	29.28	30.86
	Extraction Well Vacuum "H <sub>2</sub> O	70	70	70	70	70	70
	Pump Rate gals/min	0/0.5	0.5	0.5	0.5	0.5	0.5
	Total Volume gals	-	7.5	22.5	38	53	68
	Influent Vapor Temp. °F	64	64	64	64	64	64
	Air Temperature °F	72.6	74.4	77.9	74.9	81.1	83.5
	Barometric Pressure "Hg	30.18	30.18	30.18	30.18	30.17	30.16
	Absolute Pressure "Hg	24.11	24.11	24.11	24.11	24.10	24.10
VAPOR/INFLUENT	HC ppmv	60,300	61,630	63,230	62,380	61,910	62,550
	CO <sub>2</sub> %	7.44	7.58	6.54	6.48	7.70	7.37
	CO %	2.11	2.11	2.24	2.22	2.16	2.24
	O <sub>2</sub> %	5.2	5.1	5.6	5.2	4.7	5.0
	H <sub>2</sub> S ppm	13	18	15	20	22	23
NOTES	0830 Arrived e location - 1.2 hr drive - Positioned Acuvac System near well MW-1 - Tailgate safety - Mobilized DualPhase equipment - Set GW/LNAPL pump inlet @ 30.5 ft BTOC - TD = 52.30 ft - <sup>0900</sup> START EVENT - SURF only to vaporize LNAPL on GW <sup>0915</sup> START GW recovery - No LNAPL in liquid						
	Initial FW induced vacuum set @ 70" H <sub>2</sub> O, UWF = 22.95 scfm - GWPR = 0.5 gpm						
	NOTE RAPID INCREASE IN VWF @ constant induced vacuum of 70" H <sub>2</sub> O						
	NOTE GW dark with biomass at start, clearing after 1 hour						
MANIFOLD	LNAPL % Vol Gals	-	-	-	-	-	-
	Depth of GW Depression ft	-5.5	-5.5	-5.5	-5.5	-5.5	-5.5
	Extraction Well DTLNAPL ft	46.83					
	Extraction Well DTGW ft	46.85					

() Indicates Well Pressure

LNAPL = 0.02'





Location: Johnston Federal #4, San Juan County, NM			Project Managers: Sadler/Faucher				
Date: 8-23-13			-	-	-	-	-
Parameters	Time	Time	Time	Time	Time	Time	
	1200	1230	1300	1330	1400	1430	
WELL # MW- 1	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	
	6541.0	6541.5	6542.0	6542.5	6543.0	6543.5	
ENGINE/BLOWER	R.P.M.	2300	2300	2300	2300	2300	2300
	Oil Pressure psi	50	50	50	50	50	50
	Water Temp °F	160	160	160	160	160	160
	Volts	13	13	13	13	13	13
	Intake Vacuum "Hg	15	15	15	15	15	15
	Gas Flow Fuel/Propane cfh	0	0	0	0	0	0
ATMOSPHERE/VACUUM/AIR PUMP/VOLUME	GW Pump ON/OFF	ON	ON	ON	ON	ON	ON
	Extraction Well Flow scfm	31.65	31.65	31.65	31.65	31.65	31.65
	Extraction Well Vacuum "H <sub>2</sub> O	20	20	20	20	20	20
	Pump Rate gals/min	0.5	0.5	0.5	0.4	0.4	0.4
	Total Volume gals	83	98	113	125	137	149
	Influent Vapor Temp. °F	64	64	64	65	65	65
	Air Temperature °F	84.6	85.8	87.9	90.1	91.2	92.3
	Barometric Pressure "Hg	30.14	30.11	30.09	30.08	30.08	30.07
	Absolute Pressure "Hg	24.09	24.07	24.05	24.04	24.04	24.03
VAPOR /INFLUENT	HC ppmv	62,320	61,610	60,670	62,010	61,990	62,450
	CO <sub>2</sub> %	8.02	7.96	7.92	7.84	7.72	7.58
	CO %	2.30	2.26	2.14	2.16	2.08	1.96
	O <sub>2</sub> %	3.9	4.1	4.4	4.5	4.5	4.6
	H <sub>2</sub> S ppm	24	24	23	21	18	15
NOTES	EW induced vacuum steady @ 20" H <sub>2</sub> O, UWP @ 31.65 scfm - GW PR = 0.5 gpm						
	NOTE UWP now mostly steady - GW clear - NO LNAPL						
	1430 hrs - <u>INCREASED</u> EW induced vacuum = 25" H <sub>2</sub> O, UWP = 36.65 scfm						
	GW PR @ 0.4 gpm						
MANIFOLD	LNAPL % Vol Gals	-	-	-	-	-	-
	Depth of GW Depression ft	-5.5	-5.5	-5.5	-5.5	-5.5	-5.5
	Extraction Well DTLNAPL ft						
	Extraction Well DTGW ft						





Location: Johnston Federal #4, San Juan County, NM			Project Managers: Sadler/Faucher					
Date: 8-23-13		-	-	-	-	-		
Parameters	Time	1500	1530	1600	1630	1700	Time	
	WELL # MW-	Hr Meter 65440	Hr Meter 65445	Hr Meter 65450	Hr Meter 65455	Hr Meter 65460	Hr Meter	
ENGINE/BLOWER	R.P.M.	2400	2400	2400	2400	2400		
	Oil Pressure psi	50	50	50	50	50		
	Water Temp °F	170	170	170	170	170		
	Volts	13	13	13	13	13		
	Intake Vacuum "Hg	12	12	12	12	12		
	Gas Flow Fuel/Propane cfh	0	0	0	0	0		
ATMOSPHERE/VACUUM/AIR PUMP/VOLUME	GW Pump ON/OFF	ON	ON	ON	ON	ON		
	Extraction Well Flow scfm	36.65	36.65	36.65	36.65	36.65		
	Extraction Well Vacuum "H <sub>2</sub> O	75	75	75	75	75		
	Pump Rate gals/min	0.4	0.3	0.3	0.2	0.2		
	Total Volume gals	161	170	179	188	191		
	Influent Vapor Temp. °F	65	65	65	65	65		
	Air Temperature °F	92.7	93.1	92.9	93.7	91.8		
	Barometric Pressure "Hg	30.05	30.04	30.03	30.02	30.01		
	Absolute Pressure "Hg	24.01	24.00	24.00	23.99	23.98		
	VAPOR /INFLUENT	HC ppmv	62,370	62,040	61,750	60,980	60,420	
CO <sub>2</sub> %		7.42	7.97	7.52	7.62	7.78		
CO %		2.20	2.26	2.18	2.16	2.09		
O <sub>2</sub> %		4.6	4.7	4.8	4.7	4.7		
H <sub>2</sub> S ppm		24	20	18	18	16		
NOTES	<p>Flow induced vacuum = 75" H<sub>2</sub>O, UWF = 36.65 scfm - GWP = 0.4.</p> <p><u>NOTE</u>, GWP = 0.39 gpm - Decreased to 0.2 gpm</p> <p><u>NOTE</u> Influent vapor T111 levels on slight decreasing trend</p> <p>At 75" H<sub>2</sub>O, UWF of 36.65, the LNAPL vapor recovery rate equals approximately +4.00 gpm - <u>NOTE</u> Very difficult to measure the amount of liquid LNAPL recovered as a % of the total 161 liquid gals. Site tube indicated slight amount of liquid LNAPL estimated at 1.0 gals</p>							
	MANIFOLD	LNAPL % Vol Gals	-	-	See	NOTE	ABOVE	
		Depth of GW Depression ft	-5.5	-5.5	-5.5	-5.5	-5.5	
		Extraction Well DTLNAPL ft					Trace	
		Extraction Well DTGW ft					47.68	





Location: Johnston Federal #4, San Juan County, NM			Project Managers: Sadler/Faucher				
Date: 8-24-13			-	-	-	-	-
Parameters	Time	Time	Time	Time	Time	Time	
	0730	0800	0830	0900	0930	1000	
WELL # MW-1	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	
	6546.0	6546.5	6547.0	6547.5	6548.0	6548.5	
ENGINE/BLOWER	R.P.M.	2100	2200	2200	2200	2300	2300
	Oil Pressure psi	50	50	50	50	50	50
	Water Temp °F	140	160	160	160	160	160
	Volts	13	13	13	13	13	13
	Intake Vacuum "Hg	13	15	15	13	13	13
	Gas Flow Fuel/Propane cfh	20	10	0	0	0	0
ATMOSPHERE/VACUUM/AIR PUMP/VOLUME	GW Pump ON/OFF	OFF	ON	ON	ON	ON	ON
	Extraction Well Flow scfm	22.95	25.72	29.27	31.43	34.61	34.61
	Extraction Well Vacuum "H <sub>2</sub> O	70	70	70	70	70	70
	Pump Rate gals/min	OFF	0.3	0.3	0.3	0.3	0.2
	Total Volume gals	-	9	18	27	36	42
	Influent Vapor Temp. °F	61	61	62	62	62	62
	Air Temperature °F	69.6	70.3	71.7	72.6	72.8	71.4
	Barometric Pressure "Hg	30.19	30.20	30.20	30.20	30.21	30.21
	Absolute Pressure "Hg	24.13	24.13	24.13	24.13	24.14	24.14
VAPOR /INFLUENT	HC ppmv	58,960	59,140	59,610	58,810	59,040	58,550
	CO <sub>2</sub> %	7.46	7.91	7.86	7.42	7.46	7.88
	CO %	1.98	2.00	2.04	1.90	1.86	1.81
	O <sub>2</sub> %	5.0	4.9	4.7	4.5	4.4	4.5
	H <sub>2</sub> S ppm	16	14	15	15	13	13
NOTES	0715 - Arrived e location - SAFETY MEETING - Mobilized SVE for quick start. Gauged well - 0730 hrs. [START EVENT] #2 - SVE only (NO new pumping) to remove free phase LNAPL 0800 hrs [START GW RECOVERY] Initial EW induced vacuum set @ 70" H <sub>2</sub> O, UWF @ 22.95 scfm - GWR @ 0.3 gpm NOTE: Increasing UWF from 22.95 to 34.61 scfm, vacuum @ 70" H <sub>2</sub> O NOTE - WEATHER COOL AND CLOUDY OVERCAST 57.10 = 61.1 ft vacuum WALLS MW-35.4 0   -110/710   -112/712   -112/415   -113/713   -613/713						
MANIFOLD	LNAPL % Vol Gals	-	-	-	-	-	-
	Depth of GW Depression ft	N/A	-5.5	-5.5	-5.5	-5.5	-5.5
	Extraction Well DTLNAPL ft	47.15					
	Extraction Well DTGW ft	47.18					

() Indicates Well Pressure

LNAPL = 0.03





Location: Johnston Federal #4, San Juan County, NM			Project Managers: Sadler/Faucher				
Date: 8-24-13		-	-	-	-	-	
Parameters	Time	1030	1100	1130	1200	1230	1300
	WELL # MW-1	Hr Meter 6549.0	Hr Meter 6549.5	Hr Meter 6550.0	Hr Meter 6550.5	Hr Meter 6551.0	Hr Meter 6551.5
ENGINE/BLOWER	R.P.M.	2300	2300	2300	2300	2300	2300
	Oil Pressure psi	50	50	50	50	50	50
	Water Temp °F	160	160	160	160	160	160
	Volts	13	13	13	13	13	13
	Intake Vacuum "Hg	13	13	13	13	13	13
	Gas Flow Fuel/Propane cfh	0	0	0	0	0	0
ATMOSPHERE/VACUUM/AIR PUMP/VOLUME	GW Pump ON/OFF	ON	ON	ON	ON	ON	ON
	Extraction Well Flow scfm	34.61	34.61	34.61	34.61	34.61	34.61
	Extraction Well Vacuum "H <sub>2</sub> O	70	70	70	70	70	70
	Pump Rate gals/min	0.2	0.2	0.2	0.2	0.2	0.2
	Total Volume gals	48	54	60	66	72	78
	Influent Vapor Temp. °F	62	62	62	62	62	62
	Air Temperature °F	72.2	73.0	80.7	83.2	85.3	87.2
	Barometric Pressure "Hg	30.21	30.22	30.21	30.20	30.19	30.17
	Absolute Pressure "Hg	24.14	24.15	24.14	24.13	24.13	24.11
VAPOR /INFLUENT	HC ppmv	58,320	58,640	58,330	57,930	57,710	57,540
	CO <sub>2</sub> %	7.92	7.90	7.96	8.02	8.10	8.06
	CO %	1.92	1.94	1.90	1.88	1.86	1.76
	O <sub>2</sub> %	4.6	4.6	4.8	5.3	5.2	5.3
	H <sub>2</sub> S ppm	14	13	14	15	14	14
NOTES	EW induced vacuum steady @ 70 "H <sub>2</sub> O, VWF = 34.61 scfm - GWR = 0.2 gpm						
	NOTE - 79% levels in influent vapors mostly steady						
	NOTE - Outer well MW-3 on vacuum increase						
MANIFOLD	LNAPL % Vol Gals	-	-	-	-	-	-
	Depth of GW Depression ft	-5.5	-5.5	-5.5	-5.5	-5.5	-5.5
	Extraction Well DTLNAPL ft						
	Extraction Well DTGW ft						





Location: Johnston Federal #4, San Juan County, NM		Project Managers: Sadler/Faucher					
Date: 8-24-13		-		-		-	
Parameters	Time	Time	Time	Time	Time	Time	Time
WELL # MW-1	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter
R.P.M.	2330	2300	2300	2300	2300	2300	
Oil Pressure psi	50	50	50	50	50	50	
Water Temp °F	160	160	160	160	160	160	
Volts	13	13	13	13	13	13	
Intake Vacuum "Hg	13	13	13	13	13	13	
Gas Flow Fuel/Propane cfh	0	0	0	0	0	0	
GW Pump ON/OFF	ON	ON	ON	ON	ON	ON	
Extraction Well Flow scfm	35.65	35.65	35.65	35.65	35.65	35.65	
Extraction Well Vacuum "H <sub>2</sub> O	70	70	70	70	70	70	
Pump Rate gals/min	0.2	0.2	0.2	0.2	0.2	0.2	
Total Volume gals	84	90	96	102	108		
Influent Vapor Temp. °F	62	62	62	62	62		
Air Temperature °F	88.7	84.3	89.7	90.4	91.8		
Barometric Pressure "Hg	30.17	30.16	30.16	30.14	30.13		
Absolute Pressure "Hg	24.11	24.10	24.10	24.08	24.07		
HC ppmv	57,390	57,430	57,816	57,660	57,220		
CO <sub>2</sub> %	8.02	8.02	7.98	7.92	7.88		
CO %	1.68	1.88	1.89	1.87	1.78		
O <sub>2</sub> %	5.2	5.3	5.4	5.6	5.7		
H <sub>2</sub> S ppm	13	15	12	11	12		
NOTES	EW vacuum steady @ 20" H <sub>2</sub> O, VWF increased to 35.65 scfm						
	GWPR = 0.20 - NOTE Influent vapor TDA ppmv mostly steady - PR steady						
	1530 - EVRUC # 2 Completed						
	1615 - Secured all wells - departed site						
	NOTE: Observing the slight amount of LNAPL flowing through the clear sight tube, the estimated liquid volume of LNAPL is 1.5 gals. Also, seen in tank						
	WALLS MW-3 & 4						
MANIFOLD	LNAPL % Vol Gals	-		SEE	NOTE	ABOVE	
	Depth of GW Depression ft	-5.5	-5.5	-5.5	-5.5	-5.5	
	Extraction Well DTLNAPL ft					NO	
	Extraction Well DTGW ft					42.38	





Location: Johnston Federal #4, San Juan County, NM			Project Managers: Sadler/Faucher				
Date: 8-27-13			-	-	-	-	-
Parameters	Time	0730	0800	0830	0900	0930	1000
	Hr Meter	6562.5	6563.0	6563.0	6564.0	6564.5	6565.0
WELL # MW-1							
ENGINE/BLOWER	R.P.M.	2300	2300	2300	2300	2300	2300
	Oil Pressure psi	50	50	50	50	50	50
	Water Temp °F	130	150	160	160	160	160
	Volts	13	13	13	13	13	13
	Intake Vacuum "Hg	13	13	13	13	13	13
	Gas Flow Fuel/Propane cfh	0	0	0	0	0	0
ATMOSPHERE/VACUUM/AIR PUMP/VOLUME	GW Pump ON/OFF	ON	ON	ON	ON	ON	ON
	Extraction Well Flow scfm	37.58	37.58	37.58	37.58	37.58	37.58
	Extraction Well Vacuum "H <sub>2</sub> O	20	20	20	20	20	20
	Pump Rate gals/min	0.3	0.3	0.3	0.3	0.3	0.2
	Total Volume gals	-	9	18	27	36	42
	Influent Vapor Temp. °F	60	60	60	60	60	60
	Air Temperature °F	58.9	59.0	64.4	68.5	72.8	75.6
	Barometric Pressure "Hg	30.24	30.24	30.24	30.24	30.24	30.23
	Absolute Pressure "Hg	24.16	24.16	24.16	24.16	24.16	24.15
VAPOR /INFLUENT	HC ppmv	57,620	-	57,490	-	57,320	-
	CO <sub>2</sub> %	2.6	-	7.12	-	2.80	-
	CO %	1.62	-	1.70	-	1.84	-
	O <sub>2</sub> %	4.1	-	4.4	-	4.0	-
	H <sub>2</sub> S ppm	0	-	0	-	0	-
NOTES	Arrived @ site @ 0710 hrs - Tailgate Safety - Mobilized Acuvac System						
	Gauged well - MW-1 - Connected and checked all hoses. OK - Safety checked						
	0730 hrs - <u>START</u> EVENT #3 - Initial BW induced vacuum = 20 "H <sub>2</sub> O						
	UWF = 37.58 scfm - GWP = 0.3 gpm						
MANIFOLD	LNAPL % Vol Gals	-	-	-	-	-	-
	Depth of GW Depression ft	-5.5	-5.5	-5.5	-5.5	-5.5	-5.5
	Extraction Well DTLNAPL ft	-					
	Extraction Well DTGW ft	46.89					





Location: Johnston Federal #4, San Juan County, NM			Project Managers: Sadler/Faucher				
Date: 8-27-13			-	-	-	-	-
Parameters	Time	Time	Time	Time	Time	Time	
	1030	1100	1130	1200	1230	1300	
WELL # MW- 1	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	
	6565.5	6566.0	6566.5	6567.0	6567.5	6568.0	
ENGINE/BLOWER	R.P.M.	2300	2300	2300	2300	2300	2300
	Oil Pressure psi	50	50	50	50	50	50
	Water Temp °F	160	160	160	160	160	160
	Volts	13	13	13	13	13	13
	Intake Vacuum "Hg	13	13	13	13	13	13
	Gas Flow Fuel/Propane cfh	0	0	0	0	0	0
ATMOSPHERE/VACUUM/AIR PUMP/VOLUME	GW Pump ON/OFF	ON	ON	ON	ON	ON	ON
	Extraction Well Flow scfm	37.58	38.57	38.57	38.57	38.57	38.57
	Extraction Well Vacuum "H <sub>2</sub> O	70	70	70	70	70	70
	Pump Rate gals/min	0.2	0.2	0.2	0.2	0.2	0.2
	Total Volume gals	48	54	60	66	72	76
	Influent Vapor Temp. °F	60	60	60	60	60	60
	Air Temperature °F	79.1	80.2	83.6	84.8	86.0	86.9
	Barometric Pressure "Hg	30.23	30.23	30.22	30.20	30.19	30.18
	Absolute Pressure "Hg	24.15	24.15	24.14	24.13	24.12	24.11
VAPOR /INFLUENT	HC ppmv	56,880	-	55,780	-	56,440	-
	CO <sub>2</sub> %	7.36	-	7.12	-	7.24	-
	CO %	1.64	-	1.54	-	1.55	-
	O <sub>2</sub> %	4.3	-	4.5	-	4.4	-
	H <sub>2</sub> S ppm	0	-	0	-	0	-
NOTES	FW induced vacuum and UWF steadily at 70" H <sub>2</sub> O, 37.58 scfm						
	GWR = 0.29 gpm						
	1100 HRS - NOTE! UWF increased to 38.57 scfm - Vacuum @ 70" H <sub>2</sub> O						
MANIFOLD	LNAPL % Vol Gals	-	-	-	-	-	-
	Depth of GW Depression ft	-5.5	-5.5	-5.5	-5.5	-5.5	-5.5
	Extraction Well DTLNAPL ft						
	Extraction Well DTGW ft						





Location: Johnston Federal #4, San Juan County, NM			Project Managers: Sadler/Faucher					
Date: 8-27-13		-	-	-	-	-		
Parameters	Time	Time	Time	Time	Time	Time	Time	
	1330	1400	1430	1500	1530			
WELL # MW- 1	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	Hr Meter	
	6568.5	6569.0	6569.5	6560.0	6560.5			
ENGINE/BLOWER	R.P.M.	2300	2300	2300	2300	2300		
	Oil Pressure psi	50	50	50	50	50		
	Water Temp °F	160	160	160	160	160		
	Volts	13	13	13	13	13		
	Intake Vacuum "Hg	12	12	12	12	12		
	Gas Flow Fuel/Propane cfh	0	0	0	0	0		
ATMOSPHERE/VACUUM/AIR PUMP/VOLUME	GW Pump ON/OFF	ON	ON	ON	ON	ON		
	Extraction Well Flow scfm	38.57	38.57	38.57	38.57	38.57		
	Extraction Well Vacuum "H <sub>2</sub> O	70	70	70	70	70		
	Pump Rate gals/min	0.2	0.2	0.2	0.2	0.2		
	Total Volume gals	82	88	94	100	106		
	Influent Vapor Temp. °F	60	60	60	60	60		
	Air Temperature °F	88.7	91.2	92.3	92.8	93.0		
	Barometric Pressure "Hg	30.17	30.16	30.15	30.14	30.13		
	Absolute Pressure "Hg	24.10	24.16	24.09	24.08	24.07		
VAPOR /INFLUENT	HC ppmv	53,170	-	54,420	-	54,180		
	CO <sub>2</sub> %	6.86	-	7.16	-	7.20		
	CO %	1.45	-	1.58	-	1.62		
	O <sub>2</sub> %	4.6	-	5.2	-	5.3		
	H <sub>2</sub> S ppm	0	-	0	-	0		
NOTES	<p>EW induced vacuum and UVP steady @ 70" H<sub>2</sub>O, 38.57 scfm</p> <p>GW RP = 0.2 gpm <u>NOTE</u> An occasional slug (approximately 1.5L of LNAPL will float through with GW - <u>Total LNAPL for the 8 hour Event is estimated at 20 gallons.</u> Sight taken from collection tank</p> <p>1530 hrs - Event #3 completed</p> <p>1615 hrs - Secured all wells - <u>Departed site</u></p>							
	MANIFOLD	LNAPL % Vol Gals	<u>SEE -</u>	<u>NOTE -</u>	<u>ABOVE -</u>	-	-	
		Depth of GW Depression ft	-5.5	-5.5	-5.5	-5.5	-5.5	
		Extraction Well DTLNAPL ft					47.37	
		Extraction Well DTGW ft					47.38	




**JOHNSTON FEDERAL NO. 4 SITE  
AZTEC, NM**







**JOHNSTON FEDERAL NO. 4 SITE  
AZTEC, NM**





**JOHNSTON FEDERAL NO. 4 SITE**  
**AZTEC, NM**





## **Appendix B**

### **September 2013 Annual Groundwater Sampling Field Forms**



# WELL SAMPLING FIELD INFORMATION FORM

SITE/PROJECT NAME:  
SAMPLE ID:

Johnston Federal No. 4  
GW-074925-091713-CM-MW JOB# 074925  
WELL# MW-1

PURGE DATE (MM DD YY) 9/17/13  
SAMPLE DATE (MM DD YY) 9/17/13  
WELL PURGING INFORMATION  
SAMPLE TIME (24 HOUR) 1720  
WATER VOL. IN CASING (GALLONS) 0.77  
ACTUAL VOL. PURGED (GALLONS) 2.50 2.25

## PURGING AND SAMPLING EQUIPMENT

PURGING EQUIPMENT.....DEDICATED ☒ Y ☐ N

SAMPLING EQUIPMENT.....DEDICATED ☒ Y ☐ N

(CIRCLE ONE)

(CIRCLE ONE)

PURGING DEVICE

☒ G

A - SUBMERSIBLE PUMP

D - GAS LIFT PUMP

G - BAILER

X=

☒ G

B - PERISTALTIC PUMP

E - PURGE PUMP

H - WATERRA®

PURGING DEVICE OTHER (SPECIFY)

SAMPLING DEVICE

☒ G

C - BLADDER PUMP

F - DIPPER BOTTLE

X - OTHER

X=

SAMPLING DEVICE OTHER (SPECIFY)

PURGING MATERIAL

☒ E

A - TEFLON

D - PVC

X=

☒ E

B - STAINLESS STEEL

E - POLYETHYLENE

PURGING MATERIAL OTHER (SPECIFY)

SAMPLING MATERIAL

☒ E

C - POLYPROPYLENE

X - OTHER

X=

SAMPLING MATERIAL OTHER (SPECIFY)

PURGE TUBING

☒ C

A - TEFLON

D - POLYPROPYLENE

G - COMBINATION  
TEFLON/POLYPROPYLENE

X=

☒ C

B - TYGON

E - POLYETHYLENE

PURGE TUBING OTHER (SPECIFY)

SAMPLING TUBING

☒ C

C - ROPE

F - SILICONE

X - OTHER

X=

SAMPLING TUBING OTHER (SPECIFY)

FILTERING DEVICES 0.45

☒ A

A - IN-LINE DISPOSABLE

B - PRESSURE

0.45 for metals only

## FIELD MEASUREMENTS

DEPTH TO WATER

46.88

(feet)

WELL ELEVATION

(feet)

WELL DEPTH

51.69

(feet)

GROUNDWATER ELEVATION

(feet)

TEMPERATURE

pH

TDS

SC

DO

ORP

VOLUME

15.43 (°C)

6.77 (std)

1,484 (g/L)

2283 (µS/cm)

2.04 (mg/L)

-337.9 (mV)

1.50 (gal)

15.39 (°C)

6.77 (std)

1,482 (g/L)

2280 (µS/cm)

2.28 (mg/L)

-323.8 (mV)

2.0 (gal)

15.42 (°C)

6.79 (std)

1,474 (g/L)

2267 (µS/cm)

2.68 (mg/L)

-317.3 (mV)

2.25 (gal)

(°C)

(std)

(g/L)

(µS/cm)

(mg/L)

(mV)

(gal)

(°C)

(std)

(g/L)

(µS/cm)

(mg/L)

(mV)

(gal)

## FIELD COMMENTS

SAMPLE APPEARANCE:

cloudy

OR:

hydrocarbon

COLOR:

gray

SHEEN Y/N

slight but continuous

WEATHER CONDITIONS:

TEMPERATURE

80's

WINDY Y/N

no

PRECIPITATION Y/N (IF Y TYPE)

no

SPECIFIC COMMENTS:

Duplicate @ 1730

I CERTIFY THAT SAMPLING PROCEDURES WERE IN ACCORDANCE WITH APPLICABLE CRA PROTOCOLS

DATE

9/17/13

PRINT

Johnston Mathews

SIGNATURE

Johnston Mathews



# WELL SAMPLING FIELD INFORMATION FORM

SITE/PROJECT NAME:  
SAMPLE ID:

Johnston Federal 4  
GW-074925-091713-CM-MW-2  
JOB# 074925  
WELL# MW-2

9/17/13 9/17/13 1650 3.36 10.25  
PURGE DATE (MM DD YY) SAMPLE DATE (MM DD YY) SAMPLE TIME (24 HOUR) WATER VOL. IN CASING (GALLONS) ACTUAL VOL. PURGED (GALLONS)

## PURGING AND SAMPLING EQUIPMENT

PURGING EQUIPMENT.....DEDICATED ☒ Y ☐ N

SAMPLING EQUIPMENT.....DEDICATED ☒ Y ☐ N

(CIRCLE ONE)

(CIRCLE ONE)

PURGING DEVICE: ☒ G A - SUBMERSIBLE PUMP D - GAS LIFT PUMP G - BAILER X= \_\_\_\_\_  
B - PERISTALTIC PUMP E - PURGE PUMP H - WATERRA® PURGING DEVICE OTHER (SPECIFY)  
SAMPLING DEVICE: ☒ G C - BLADDER PUMP F - DIPPER BOTTLE X - OTHER X= \_\_\_\_\_  
SAMPLING DEVICE OTHER (SPECIFY)  
PURGING MATERIAL: ☒ E A - TEFLON D - PVC X= \_\_\_\_\_  
B - STAINLESS STEEL E - POLYETHYLENE PURGING MATERIAL OTHER (SPECIFY)  
SAMPLING MATERIAL: ☒ E C - POLYPROPYLENE X - OTHER X= \_\_\_\_\_  
SAMPLING MATERIAL OTHER (SPECIFY)  
PURGE TUBING: ☒ C A - TEFLON D - POLYPROPYLENE G - COMBINATION X= \_\_\_\_\_  
TEFLON/POLYPROPYLENE PURGE TUBING OTHER (SPECIFY)  
SAMPLING TUBING: ☒ C B - TYGON E - POLYETHYLENE X= \_\_\_\_\_  
C - ROPE F - SILICONE X - OTHER X= \_\_\_\_\_  
SAMPLING TUBING OTHER (SPECIFY)  
FILTERING DEVICES 0.45 ☒ A A - IN-LINE DISPOSABLE B - PRESSURE 0.45 metals only

## FIELD MEASUREMENTS

DEPTH TO WATER 43.51 (feet) WELL ELEVATION \_\_\_\_\_ (feet)  
WELL DEPTH 64.49 (feet) GROUNDWATER ELEVATION \_\_\_\_\_ (feet)  
TEMPERATURE pH TDS SC DO ORP VOLUME  
14.21 (°C) 7.30 (std) 1515 (g/L) 2331 (µS/cm) 6.13 (mg/L) 65.4 (mV) 9.25 (gal)  
14.07 (°C) 6.71 (std) 1511 (g/L) 2324 (µS/cm) 5.24 (mg/L) 86.3 (mV) 9.75 (gal)  
14.10 (°C) 6.53 (std) 1514 (g/L) 2329 (µS/cm) 5.45 (mg/L) 56.7 (mV) 10.25 (gal)  
\_\_\_\_ (°C) \_\_\_\_ (std) \_\_\_\_ (g/L) \_\_\_\_ (µS/cm) \_\_\_\_ (mg/L) \_\_\_\_ (mV) \_\_\_\_ (gal)  
\_\_\_\_ (°C) \_\_\_\_ (std) \_\_\_\_ (g/L) \_\_\_\_ (µS/cm) \_\_\_\_ (mg/L) \_\_\_\_ (mV) \_\_\_\_ (gal)

## FIELD COMMENTS

SAMPLE APPEARANCE: Cloudy ODOR: none COLOR: light brown SHEEN Y/N no  
WEATHER CONDITIONS: TEMPERATURE 85° WINDY Y/N no PRECIPITATION Y/N (IF Y TYPE) no  
SPECIFIC COMMENTS:

I CERTIFY THAT SAMPLING PROCEDURES WERE IN ACCORDANCE WITH APPLICABLE CWA PROTOCOLS

DATE 9/17/13 PRINT Christine Mathews SIGNATURE [Signature]



# WELL SAMPLING FIELD INFORMATION FORM

SITE/PROJECT NAME:  
SAMPLE ID:

Johnston Federal 4 JOB# 074925  
GLW-074925-091713-CM-MW3 WELL# MW-3

9/17/13 9/17/13 1705 2.40 7.25  
PURGE DATE (MM DD YY) SAMPLE DATE (MM DD YY) SAMPLE TIME (24 HOUR) WATER VOL IN CASING (GALLONS) ACTUAL VOL. PURGED (GALLONS)

## PURGING AND SAMPLING EQUIPMENT

PURGING EQUIPMENT.....DEDICATED ☒ Y ☐ N

SAMPLING EQUIPMENT.....DEDICATED ☒ Y ☐ N

(CIRCLE ONE)

(CIRCLE ONE)

PURGING DEVICE

☒ G

A - SUBMERSIBLE PUMP

D - GAS LIFT PUMP

G - BAILER

X= \_\_\_\_\_

B - PERISTALTIC PUMP

E - PURGE PUMP

H - WATERA®

PURGING DEVICE OTHER (SPECIFY)

SAMPLING DEVICE

☒ G

C - BLADDER PUMP

F - DIPPER BOTTLE

X - OTHER

X= \_\_\_\_\_

SAMPLING DEVICE OTHER (SPECIFY)

PURGING MATERIAL

☒ E

A - TEFLON

D - PVC

X= \_\_\_\_\_

B - STAINLESS STEEL

E - POLYETHYLENE

PURGING MATERIAL OTHER (SPECIFY)

SAMPLING MATERIAL

☒ E

C - POLYPROPYLENE

X - OTHER

X= \_\_\_\_\_

SAMPLING MATERIAL OTHER (SPECIFY)

PURGE TUBING

☒ C

A - TEFLON

D - POLYPROPYLENE

G - COMBINATION  
TEFLON/POLYPROPYLENE

X= \_\_\_\_\_

B - TYGON

E - POLYETHYLENE

PURGE TUBING OTHER (SPECIFY)

SAMPLING TUBING

☒ C

C - ROPE

F - SILICONE

X - OTHER

X= \_\_\_\_\_

SAMPLING TUBING OTHER (SPECIFY)

FILTERING DEVICES 0.45

☒ A

A - IN-LINE DISPOSABLE

B - PRESSURE

0.45 micron for metals only

## FIELD MEASUREMENTS

DEPTH TO WATER

42.47

(feet)

WELL ELEVATION

(feet)

WELL DEPTH

57.47

(feet)

GROUNDWATER ELEVATION

(feet)

TEMPERATURE

pH

TDS

SC

DO

ORP

VOLUME

15.58 (°C)

7.06 (std)

1.264 (g/L)

1944 (µS/cm)

2.81 (mg/L)

-156.1 (mV)

6.25 (gal)

15.44 (°C)

6.82 (std)

1.249 (g/L)

1922 (µS/cm)

1.86 (mg/L)

-154.1 (mV)

6.75 (gal)

15.44 (°C)

6.80 (std)

1.263 (g/L)

1943 (µS/cm)

1.70 (mg/L)

-164.9 (mV)

7.25 (gal)

\_\_\_\_\_ (°C)

\_\_\_\_\_ (std)

\_\_\_\_\_ (g/L)

\_\_\_\_\_ (µS/cm)

\_\_\_\_\_ (mg/L)

\_\_\_\_\_ (mV)

\_\_\_\_\_ (gal)

\_\_\_\_\_ (°C)

\_\_\_\_\_ (std)

\_\_\_\_\_ (g/L)

\_\_\_\_\_ (µS/cm)

\_\_\_\_\_ (mg/L)

\_\_\_\_\_ (mV)

\_\_\_\_\_ (gal)

## FIELD COMMENTS

SAMPLE APPEARANCE:

CLOUDY

ODOR:

B10

COLOR:

GRAY

SHEEN Y/N

N

WEATHER CONDITIONS:

TEMPERATURE

80s

WINDY Y/N

N

PRECIPITATION Y/N (IF Y TYPE)

N

SPECIFIC COMMENTS:

I CERTIFY THAT SAMPLING PROCEDURES WERE IN ACCORDANCE WITH APPLICABLE EPA PROTOCOLS

DATE

9/17/13

PRINT

Christine Mathew

SIGNATURE

Christine Mathew



## WELL SAMPLING FIELD INFORMATION FORM

SITE/PROJECT NAME:

SAMPLE ID:

Johnston Federal 4  
GW-074925-091713-CM-MW-4

JOB#

074925

WELL#

MW-4

9/17/13

PURGE DATE  
(MM DD YY)

9/17/13

SAMPLE DATE  
(MM DD YY)

WELL PURGING INFORMATION

1635

SAMPLE TIME  
(24 HOUR)

2.61

WATER VOL. IN CASING  
(GALLONS)

8.00

ACTUAL VOL. PURGED  
(GALLONS)

## PURGING AND SAMPLING EQUIPMENT

PURGING EQUIPMENT.....DEDICATED ☒ Y ☐ N

(CIRCLE ONE)

SAMPLING EQUIPMENT.....DEDICATED ☒ Y ☐ N

(CIRCLE ONE)

PURGING DEVICE

☒ G

A - SUBMERSIBLE PUMP

D - GAS LIFT PUMP

G - BAILER

X= \_\_\_\_\_

B - PERISTALTIC PUMP

E - PURGE PUMP

H - WATERRA®

PURGING DEVICE OTHER (SPECIFY)

SAMPLING DEVICE

☒ G

C - BLADDER PUMP

F - DIPPER BOTTLE

X - OTHER

X= \_\_\_\_\_

SAMPLING DEVICE OTHER (SPECIFY)

PURGING MATERIAL

☒ E

A - TEFLON

D - PVC

X= \_\_\_\_\_

B - STAINLESS STEEL

E - POLYETHYLENE

PURGING MATERIAL OTHER (SPECIFY)

SAMPLING MATERIAL

☒ E

C - POLYPROPYLENE

X - OTHER

X= \_\_\_\_\_

SAMPLING MATERIAL OTHER (SPECIFY)

PURGE TUBING

☒ C

A - TEFLON

D - POLYPROPYLENE

G - COMBINATION  
TEFLON/POLYPROPYLENE

X= \_\_\_\_\_

B - TYGON

E - POLYETHYLENE

PURGE TUBING OTHER (SPECIFY)

SAMPLING TUBING

☒ C

C - ROPE

F - SILICONE

X - OTHER

X= \_\_\_\_\_

SAMPLING TUBING OTHER (SPECIFY)

FILTERING DEVICES 0.45

☒ A

A - IN-LINE DISPOSABLE

B - PRESSURE

0.45 micron for metals only

## FIELD MEASUREMENTS

DEPTH TO WATER

43.65

(feet)

WELL ELEVATION

(feet)

WELL DEPTH

59.94

(feet)

GROUNDWATER ELEVATION

(feet)

TEMPERATURE

pH

TDS

SC

DO

ORP

VOLUME

16.07

(°C)

6.20

(std)

1.353

(g/L)

2081

(µS/cm)

5.07

(mg/L)

-113.1

(mV)

7.0

(gal)

15.62

(°C)

5.88

(std)

1.348

(g/L)

2075

(µS/cm)

3.54

(mg/L)

-104.2

(mV)

7.5

(gal)

15.59

(°C)

5.91

(std)

1.348

(g/L)

2073

(µS/cm)

3.12

(mg/L)

-105.4

(mV)

8.0

(gal)

(°C)

(std)

(g/L)

(µS/cm)

(mg/L)

(mV)

(gal)

(°C)

(std)

(g/L)

(µS/cm)

(mg/L)

(mV)

(gal)

SAMPLE APPEARANCE:

SLIGHTLY  
CLOUDY

ODOR:

NONE

COLOR:

LIGHT  
BROWN

SHEEN Y/N

N

WEATHER CONDITIONS:

TEMPERATURE

80s

WINDY Y/N

N

PRECIPITATION Y/N (IF Y TYPE)

N

SPECIFIC COMMENTS:

I CERTIFY THAT SAMPLING PROCEDURES WERE IN ACCORDANCE WITH APPLICABLE CIRA PROTOCOLS

DATE

9/17/13

PRINT

Christine Mathews

SIGNATURE

Christine Mathews



## **Appendix C**

### **September 2013 Annual Groundwater Laboratory Analytical Report**



October 07, 2013

Christine Matthews  
CRA  
6121 Indian School Rd NE  
Suite 200  
Albuquerque, NM 87110

RE: Project: 074925 Johnston Federal No. 4  
Pace Project No.: 60153641

Dear Christine Matthews:

Enclosed are the analytical results for sample(s) received by the laboratory on September 20, 2013. The results relate only to the samples included in this report. Results reported herein conform to the most current TNI standards and the laboratory's Quality Assurance Manual, where applicable, unless otherwise noted in the body of the report.

If you have any questions concerning this report, please feel free to contact me.

Sincerely,



Alice Flanagan

alice.flanagan@pacelabs.com  
Project Manager

Enclosures

cc: Angela Bown, COP Conestoga-Rovers & Associa  
Jeff Walker, COP Conestoga-Rovers & Associa



## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## CERTIFICATIONS

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

---

### Kansas Certification IDs

9608 Loiret Boulevard, Lenexa, KS 66219

WY STR Certification #: 2456.01

Arkansas Certification #: 13-012-0

Illinois Certification #: 003097

Iowa Certification #: 118

Kansas/NELAP Certification #: E-10116

Louisiana Certification #: 03055

Nevada Certification #: KS000212008A

Oklahoma Certification #: 9205/9935

Texas Certification #: T104704407-13-4

Utah Certification #: KS000212013-3

Illinois Certification #: 003097

---

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## SAMPLE SUMMARY

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

Lab ID	Sample ID	Matrix	Date Collected	Date Received
60153641001	GW-074925-091713-CM-MW-1	Water	09/17/13 17:20	09/20/13 08:30
60153641002	GW-074925-091713-CM-MW-2	Water	09/17/13 16:50	09/20/13 08:30
60153641003	GW-074925-091713-CM-MW-3	Water	09/17/13 17:05	09/20/13 08:30
60153641004	GW-074925-091713-CM-MW-4	Water	09/17/13 16:35	09/20/13 08:30
60153641005	GW-074925-091713-CM-DUP	Water	09/17/13 17:30	09/20/13 08:30
60153641006	TB-074925-091813-CM-001	Water	09/18/13 08:30	09/20/13 08:30

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## SAMPLE ANALYTE COUNT

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

Lab ID	Sample ID	Method	Analysts	Analytes Reported
60153641001	GW-074925-091713-CM-MW-1	EPA 6010	NDJ	2
		EPA 8270C by SIM	NAW	3
		EPA 5030B/8260	PRG	8
		EPA 300.0	OL	1
60153641002	GW-074925-091713-CM-MW-2	EPA 6010	NDJ	2
		EPA 8270C by SIM	NAW	3
		EPA 5030B/8260	PRG	8
		EPA 300.0	OL	1
60153641003	GW-074925-091713-CM-MW-3	EPA 6010	NDJ	2
		EPA 8270C by SIM	NAW	3
		EPA 5030B/8260	PRG	8
		EPA 300.0	OL	1
60153641004	GW-074925-091713-CM-MW-4	EPA 6010	NDJ	2
		EPA 8270C by SIM	NAW	3
		EPA 5030B/8260	PRG	8
		EPA 300.0	OL	1
60153641005	GW-074925-091713-CM-DUP	EPA 5030B/8260	PRG	8
60153641006	TB-074925-091813-CM-001	EPA 5030B/8260	PRG	8

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## PROJECT NARRATIVE

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

---

**Method:** EPA 6010

**Description:** 6010 MET ICP, Dissolved

**Client:** COP Conestoga-Rovers & Associates, Inc. NM

**Date:** October 07, 2013

**General Information:**

4 samples were analyzed for EPA 6010. All samples were received in acceptable condition with any exceptions noted below.

**Hold Time:**

The samples were analyzed within the method required hold times with any exceptions noted below.

**Sample Preparation:**

The samples were prepared in accordance with EPA 3010 with any exceptions noted below.

**Initial Calibrations (including MS Tune as applicable):**

All criteria were within method requirements with any exceptions noted below.

**Continuing Calibration:**

All criteria were within method requirements with any exceptions noted below.

**Method Blank:**

All analytes were below the report limit in the method blank, where applicable, with any exceptions noted below.

**Laboratory Control Spike:**

All laboratory control spike compounds were within QC limits with any exceptions noted below.

**Matrix Spikes:**

All percent recoveries and relative percent differences (RPDs) were within acceptance criteria with any exceptions noted below.

**Additional Comments:**

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## PROJECT NARRATIVE

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

---

**Method:** EPA 8270C by SIM

**Description:** 8270 MSSV PAH by SIM

**Client:** COP Conestoga-Rovers & Associates, Inc. NM

**Date:** October 07, 2013

**General Information:**

4 samples were analyzed for EPA 8270C by SIM. All samples were received in acceptable condition with any exceptions noted below.

**Hold Time:**

The samples were analyzed within the method required hold times with any exceptions noted below.

**Sample Preparation:**

The samples were prepared in accordance with EPA 3510C with any exceptions noted below.

**Initial Calibrations (including MS Tune as applicable):**

All criteria were within method requirements with any exceptions noted below.

**Continuing Calibration:**

All criteria were within method requirements with any exceptions noted below.

**Internal Standards:**

All internal standards were within QC limits with any exceptions noted below.

**Surrogates:**

All surrogates were within QC limits with any exceptions noted below.

**Method Blank:**

All analytes were below the report limit in the method blank, where applicable, with any exceptions noted below.

**Laboratory Control Spike:**

All laboratory control spike compounds were within QC limits with any exceptions noted below.

**Matrix Spikes:**

All percent recoveries and relative percent differences (RPDs) were within acceptance criteria with any exceptions noted below.

QC Batch: MSSV/12908

A matrix spike/matrix spike duplicate was not performed due to insufficient sample volume.

**Additional Comments:**

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## PROJECT NARRATIVE

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

---

**Method:** EPA 5030B/8260

**Description:** 8260 MSV

**Client:** COP Conestoga-Rovers & Associates, Inc. NM

**Date:** October 07, 2013

**General Information:**

6 samples were analyzed for EPA 5030B/8260. All samples were received in acceptable condition with any exceptions noted below.

**Hold Time:**

The samples were analyzed within the method required hold times with any exceptions noted below.

**Initial Calibrations (including MS Tune as applicable):**

All criteria were within method requirements with any exceptions noted below.

**Continuing Calibration:**

All criteria were within method requirements with any exceptions noted below.

**Internal Standards:**

All internal standards were within QC limits with any exceptions noted below.

**Surrogates:**

All surrogates were within QC limits with any exceptions noted below.

**Method Blank:**

All analytes were below the report limit in the method blank, where applicable, with any exceptions noted below.

**Laboratory Control Spike:**

All laboratory control spike compounds were within QC limits with any exceptions noted below.

**Matrix Spikes:**

All percent recoveries and relative percent differences (RPDs) were within acceptance criteria with any exceptions noted below.

QC Batch: MSV/56540

A matrix spike/matrix spike duplicate was not performed due to insufficient sample volume.

QC Batch: MSV/56552

A matrix spike/matrix spike duplicate was not performed due to insufficient sample volume.

**Additional Comments:**

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## PROJECT NARRATIVE

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

---

**Method:** EPA 300.0

**Description:** 300.0 IC Anions 28 Days

**Client:** COP Conestoga-Rovers & Associates, Inc. NM

**Date:** October 07, 2013

**General Information:**

4 samples were analyzed for EPA 300.0. All samples were received in acceptable condition with any exceptions noted below.

**Hold Time:**

The samples were analyzed within the method required hold times with any exceptions noted below.

**Initial Calibrations (including MS Tune as applicable):**

All criteria were within method requirements with any exceptions noted below.

**Continuing Calibration:**

All criteria were within method requirements with any exceptions noted below.

**Method Blank:**

All analytes were below the report limit in the method blank, where applicable, with any exceptions noted below.

**Laboratory Control Spike:**

All laboratory control spike compounds were within QC limits with any exceptions noted below.

**Matrix Spikes:**

All percent recoveries and relative percent differences (RPDs) were within acceptance criteria with any exceptions noted below.

**Additional Comments:**

This data package has been reviewed for quality and completeness and is approved for release.

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## ANALYTICAL RESULTS

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

**Sample:** GW-074925-091713-CM-MW-1 **Lab ID:** 60153641001 **Collected:** 09/17/13 17:20 **Received:** 09/20/13 08:30 **Matrix:** Water

Parameters	Results	Units	Report Limit	MDL	DF	Prepared	Analyzed	CAS No.	Qual
<b>6010 MET ICP, Dissolved</b>									
Analytical Method: EPA 6010 Preparation Method: EPA 3010									
Iron, Dissolved	ND	mg/L	0.050	0.012	1	09/26/13 10:25	09/27/13 10:21	7439-89-6	
Manganese, Dissolved	0.89	mg/L	0.0050	0.00049	1	09/26/13 10:25	09/27/13 10:21	7439-96-5	
<b>8270 MSSV PAH by SIM</b>									
Analytical Method: EPA 8270C by SIM Preparation Method: EPA 3510C									
Naphthalene	36.5	ug/L	2.5	0.16	5	09/24/13 00:00	10/03/13 11:53	91-20-3	
<b>Surrogates</b>									
2-Fluorobiphenyl (S)	61	%	36-120		1	09/24/13 00:00	10/02/13 21:57	321-60-8	
Terphenyl-d14 (S)	73	%	29-134		1	09/24/13 00:00	10/02/13 21:57	1718-51-0	
<b>8260 MSV</b>									
Analytical Method: EPA 5030B/8260									
Benzene	4690	ug/L	50.0	3.0	50		09/25/13 18:58	71-43-2	
Ethylbenzene	1170	ug/L	50.0	9.0	50		09/25/13 18:58	100-41-4	
Toluene	7550	ug/L	50.0	8.5	50		09/25/13 18:58	108-88-3	
Xylene (Total)	11000	ug/L	150	21.0	50		09/25/13 18:58	1330-20-7	
<b>Surrogates</b>									
4-Bromofluorobenzene (S)	103	%	80-120		50		09/25/13 18:58	460-00-4	
1,2-Dichloroethane-d4 (S)	105	%	80-120		50		09/25/13 18:58	17060-07-0	
Toluene-d8 (S)	95	%	80-120		50		09/25/13 18:58	2037-26-5	
Preservation pH	1.0		0.10	0.10	50		09/25/13 18:58		
<b>300.0 IC Anions 28 Days</b>									
Analytical Method: EPA 300.0									
Sulfate	371	mg/L	20.0	3.2	20		10/04/13 19:17	14808-79-8	

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## ANALYTICAL RESULTS

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

**Sample:** GW-074925-091713-CM-MW-2 **Lab ID:** 60153641002 **Collected:** 09/17/13 16:50 **Received:** 09/20/13 08:30 **Matrix:** Water

Parameters	Results	Units	Report Limit	MDL	DF	Prepared	Analyzed	CAS No.	Qual
<b>6010 MET ICP, Dissolved</b>									
Analytical Method: EPA 6010 Preparation Method: EPA 3010									
Iron, Dissolved	ND	mg/L	0.050	0.012	1	09/26/13 10:25	09/27/13 10:34	7439-89-6	
Manganese, Dissolved	ND	mg/L	0.0050	0.00049	1	09/26/13 10:25	09/27/13 10:34	7439-96-5	
<b>8270 MSSV PAH by SIM</b>									
Analytical Method: EPA 8270C by SIM Preparation Method: EPA 3510C									
Naphthalene	ND	ug/L	0.50	0.031	1	09/24/13 00:00	10/02/13 22:15	91-20-3	
<b>Surrogates</b>									
2-Fluorobiphenyl (S)	68 %		36-120		1	09/24/13 00:00	10/02/13 22:15	321-60-8	
Terphenyl-d14 (S)	102 %		29-134		1	09/24/13 00:00	10/02/13 22:15	1718-51-0	
<b>8260 MSV</b>									
Analytical Method: EPA 5030B/8260									
Benzene	ND	ug/L	1.0	0.060	1		09/25/13 19:12	71-43-2	
Ethylbenzene	ND	ug/L	1.0	0.18	1		09/25/13 19:12	100-41-4	
Toluene	ND	ug/L	1.0	0.17	1		09/25/13 19:12	108-88-3	
Xylene (Total)	ND	ug/L	3.0	0.42	1		09/25/13 19:12	1330-20-7	
<b>Surrogates</b>									
4-Bromofluorobenzene (S)	100 %		80-120		1		09/25/13 19:12	460-00-4	
1,2-Dichloroethane-d4 (S)	108 %		80-120		1		09/25/13 19:12	17060-07-0	
Toluene-d8 (S)	95 %		80-120		1		09/25/13 19:12	2037-26-5	
Preservation pH	1.0		0.10	0.10	1		09/25/13 19:12		
<b>300.0 IC Anions 28 Days</b>									
Analytical Method: EPA 300.0									
Sulfate	1230	mg/L	100	16.0	100		10/04/13 19:32	14808-79-8	

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## ANALYTICAL RESULTS

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

**Sample:** GW-074925-091713-CM-MW-3 **Lab ID:** 60153641003 **Collected:** 09/17/13 17:05 **Received:** 09/20/13 08:30 **Matrix:** Water

Parameters	Results	Units	Report Limit	MDL	DF	Prepared	Analyzed	CAS No.	Qual
<b>6010 MET ICP, Dissolved</b>									
Analytical Method: EPA 6010 Preparation Method: EPA 3010									
Iron, Dissolved	0.80	mg/L	0.050	0.012	1	09/26/13 10:25	09/27/13 10:37	7439-89-6	
Manganese, Dissolved	0.67	mg/L	0.0050	0.00049	1	09/26/13 10:25	09/27/13 10:37	7439-96-5	
<b>8270 MSSV PAH by SIM</b>									
Analytical Method: EPA 8270C by SIM Preparation Method: EPA 3510C									
Naphthalene	ND	ug/L	0.50	0.031	1	09/24/13 00:00	10/02/13 22:34	91-20-3	
<b>Surrogates</b>									
2-Fluorobiphenyl (S)	65 %		36-120		1	09/24/13 00:00	10/02/13 22:34	321-60-8	
Terphenyl-d14 (S)	85 %		29-134		1	09/24/13 00:00	10/02/13 22:34	1718-51-0	
<b>8260 MSV</b>									
Analytical Method: EPA 5030B/8260									
Benzene	1.2	ug/L	1.0	0.060	1		09/25/13 19:26	71-43-2	
Ethylbenzene	ND	ug/L	1.0	0.18	1		09/25/13 19:26	100-41-4	
Toluene	ND	ug/L	1.0	0.17	1		09/25/13 19:26	108-88-3	
Xylene (Total)	ND	ug/L	3.0	0.42	1		09/25/13 19:26	1330-20-7	
<b>Surrogates</b>									
4-Bromofluorobenzene (S)	103 %		80-120		1		09/25/13 19:26	460-00-4	
1,2-Dichloroethane-d4 (S)	105 %		80-120		1		09/25/13 19:26	17060-07-0	
Toluene-d8 (S)	93 %		80-120		1		09/25/13 19:26	2037-26-5	
Preservation pH	1.0		0.10	0.10	1		09/25/13 19:26		
<b>300.0 IC Anions 28 Days</b>									
Analytical Method: EPA 300.0									
Sulfate	808	mg/L	50.0	8.0	50		10/04/13 19:46	14808-79-8	

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## ANALYTICAL RESULTS

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

**Sample:** GW-074925-091713-CM-MW-4 **Lab ID:** 60153641004 **Collected:** 09/17/13 16:35 **Received:** 09/20/13 08:30 **Matrix:** Water

Parameters	Results	Units	Report Limit	MDL	DF	Prepared	Analyzed	CAS No.	Qual
<b>6010 MET ICP, Dissolved</b>									
Analytical Method: EPA 6010 Preparation Method: EPA 3010									
Iron, Dissolved	0.51	mg/L	0.050	0.012	1	09/26/13 10:25	09/27/13 10:40	7439-89-6	
Manganese, Dissolved	1.6	mg/L	0.0050	0.00049	1	09/26/13 10:25	09/27/13 10:40	7439-96-5	
<b>8270 MSSV PAH by SIM</b>									
Analytical Method: EPA 8270C by SIM Preparation Method: EPA 3510C									
Naphthalene	ND	ug/L	0.50	0.031	1	09/24/13 00:00	10/02/13 22:53	91-20-3	
<b>Surrogates</b>									
2-Fluorobiphenyl (S)	65	%	36-120		1	09/24/13 00:00	10/02/13 22:53	321-60-8	
Terphenyl-d14 (S)	96	%	29-134		1	09/24/13 00:00	10/02/13 22:53	1718-51-0	
<b>8260 MSV</b>									
Analytical Method: EPA 5030B/8260									
Benzene	6.5	ug/L	1.0	0.060	1		09/25/13 19:39	71-43-2	
Ethylbenzene	ND	ug/L	1.0	0.18	1		09/25/13 19:39	100-41-4	
Toluene	ND	ug/L	1.0	0.17	1		09/25/13 19:39	108-88-3	
Xylene (Total)	ND	ug/L	3.0	0.42	1		09/25/13 19:39	1330-20-7	
<b>Surrogates</b>									
4-Bromofluorobenzene (S)	98	%	80-120		1		09/25/13 19:39	460-00-4	
1,2-Dichloroethane-d4 (S)	108	%	80-120		1		09/25/13 19:39	17060-07-0	
Toluene-d8 (S)	93	%	80-120		1		09/25/13 19:39	2037-26-5	
Preservation pH	1.0		0.10	0.10	1		09/25/13 19:39		
<b>300.0 IC Anions 28 Days</b>									
Analytical Method: EPA 300.0									
Sulfate	925	mg/L	100	16.0	100		10/04/13 20:01	14808-79-8	

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## ANALYTICAL RESULTS

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

**Sample:** GW-074925-091713-CM-DUP **Lab ID:** 60153641005 **Collected:** 09/17/13 17:30 **Received:** 09/20/13 08:30 **Matrix:** Water

Parameters	Results	Units	Report Limit	MDL	DF	Prepared	Analyzed	CAS No.	Qual
<b>8260 MSV</b>									
Analytical Method: EPA 5030B/8260									
Benzene	<b>4700</b>	ug/L	50.0	3.0	50		09/25/13 19:53	71-43-2	
Ethylbenzene	<b>1040</b>	ug/L	50.0	9.0	50		09/25/13 19:53	100-41-4	
Toluene	<b>7210</b>	ug/L	50.0	8.5	50		09/25/13 19:53	108-88-3	
Xylene (Total)	<b>9970</b>	ug/L	150	21.0	50		09/25/13 19:53	1330-20-7	
<b>Surrogates</b>									
4-Bromofluorobenzene (S)	102	%	80-120		50		09/25/13 19:53	460-00-4	
1,2-Dichloroethane-d4 (S)	109	%	80-120		50		09/25/13 19:53	17060-07-0	
Toluene-d8 (S)	93	%	80-120		50		09/25/13 19:53	2037-26-5	
Preservation pH	<b>1.0</b>		0.10	0.10	50		09/25/13 19:53		

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## ANALYTICAL RESULTS

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

**Sample:** TB-074925-091813-CM-001 **Lab ID:** 60153641006 Collected: 09/18/13 08:30 Received: 09/20/13 08:30 Matrix: Water

Parameters	Results	Units	Report Limit	MDL	DF	Prepared	Analyzed	CAS No.	Qual
<b>8260 MSV</b> Analytical Method: EPA 5030B/8260									
Benzene	ND	ug/L	1.0	0.060	1		09/25/13 23:20	71-43-2	
Ethylbenzene	ND	ug/L	1.0	0.18	1		09/25/13 23:20	100-41-4	
Toluene	ND	ug/L	1.0	0.17	1		09/25/13 23:20	108-88-3	
Xylene (Total)	ND	ug/L	3.0	0.42	1		09/25/13 23:20	1330-20-7	
<b>Surrogates</b>									
4-Bromofluorobenzene (S)	97	%	80-120		1		09/25/13 23:20	460-00-4	
1,2-Dichloroethane-d4 (S)	101	%	80-120		1		09/25/13 23:20	17060-07-0	
Toluene-d8 (S)	101	%	80-120		1		09/25/13 23:20	2037-26-5	
Preservation pH	<b>1.0</b>		0.10	0.10	1		09/25/13 23:20		

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## QUALITY CONTROL DATA

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

QC Batch: MPRP/24442 Analysis Method: EPA 6010  
QC Batch Method: EPA 3010 Analysis Description: 6010 MET Dissolved  
Associated Lab Samples: 60153641001, 60153641002, 60153641003, 60153641004

METHOD BLANK: 1260460 Matrix: Water

Associated Lab Samples: 60153641001, 60153641002, 60153641003, 60153641004

Parameter	Units	Blank Result	Reporting Limit	Analyzed	Qualifiers
Iron, Dissolved	mg/L	ND	0.050	09/27/13 10:15	
Manganese, Dissolved	mg/L	ND	0.0050	09/27/13 10:15	

LABORATORY CONTROL SAMPLE: 1260461

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Iron, Dissolved	mg/L	10	10.1	101	80-120	
Manganese, Dissolved	mg/L	1	1.0	101	80-120	

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 1260462 1260463

Parameter	Units	60153641001 Result	MS Spike Conc.	MSD Spike Conc.	MS Result	MSD Result	MS % Rec	MSD % Rec	% Rec Limits	RPD	Max RPD	Qual
Iron, Dissolved	mg/L	ND	10	10	10	9.9	100	99	75-125	0	20	
Manganese, Dissolved	mg/L	0.89	1	1	1.8	1.8	94	95	75-125	1	20	

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## QUALITY CONTROL DATA

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

QC Batch: MSV/56540 Analysis Method: EPA 5030B/8260  
QC Batch Method: EPA 5030B/8260 Analysis Description: 8260 MSV Water 10 mL Purge  
Associated Lab Samples: 60153641001, 60153641002, 60153641003, 60153641004, 60153641005

METHOD BLANK: 1259864 Matrix: Water

Associated Lab Samples: 60153641001, 60153641002, 60153641003, 60153641004, 60153641005

Parameter	Units	Blank Result	Reporting Limit	Analyzed	Qualifiers
Benzene	ug/L	ND	1.0	09/25/13 16:55	
Ethylbenzene	ug/L	ND	1.0	09/25/13 16:55	
Toluene	ug/L	ND	1.0	09/25/13 16:55	
Xylene (Total)	ug/L	ND	3.0	09/25/13 16:55	
1,2-Dichloroethane-d4 (S)	%	107	80-120	09/25/13 16:55	
4-Bromofluorobenzene (S)	%	99	80-120	09/25/13 16:55	
Toluene-d8 (S)	%	97	80-120	09/25/13 16:55	

LABORATORY CONTROL SAMPLE: 1259865

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Benzene	ug/L	20	21.9	109	73-122	
Ethylbenzene	ug/L	20	21.1	105	76-123	
Toluene	ug/L	20	20.1	100	76-122	
Xylene (Total)	ug/L	60	62.0	103	76-122	
1,2-Dichloroethane-d4 (S)	%			107	80-120	
4-Bromofluorobenzene (S)	%			102	80-120	
Toluene-d8 (S)	%			95	80-120	

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## QUALITY CONTROL DATA

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

QC Batch:	MSV/56552	Analysis Method:	EPA 5030B/8260
QC Batch Method:	EPA 5030B/8260	Analysis Description:	8260 MSV Water 10 mL Purge
Associated Lab Samples:	60153641006		

METHOD BLANK: 1260052 Matrix: Water

Associated Lab Samples: 60153641006

Parameter	Units	Blank Result	Reporting Limit	Analyzed	Qualifiers
Benzene	ug/L	ND	1.0	09/25/13 22:39	
Ethylbenzene	ug/L	ND	1.0	09/25/13 22:39	
Toluene	ug/L	ND	1.0	09/25/13 22:39	
Xylene (Total)	ug/L	ND	3.0	09/25/13 22:39	
1,2-Dichloroethane-d4 (S)	%	100	80-120	09/25/13 22:39	
4-Bromofluorobenzene (S)	%	100	80-120	09/25/13 22:39	
Toluene-d8 (S)	%	98	80-120	09/25/13 22:39	

LABORATORY CONTROL SAMPLE: 1260053

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Benzene	ug/L	20	21.3	106	73-122	
Ethylbenzene	ug/L	20	21.0	105	76-123	
Toluene	ug/L	20	19.7	98	76-122	
Xylene (Total)	ug/L	60	60.6	101	76-122	
1,2-Dichloroethane-d4 (S)	%			104	80-120	
4-Bromofluorobenzene (S)	%			99	80-120	
Toluene-d8 (S)	%			96	80-120	

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## QUALITY CONTROL DATA

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

QC Batch:	OEXT/40632	Analysis Method:	EPA 8270C by SIM
QC Batch Method:	EPA 3510C	Analysis Description:	8270 Water PAH by SIM MSSV
Associated Lab Samples:	60153641001, 60153641002, 60153641003, 60153641004		

METHOD BLANK: 1258787 Matrix: Water

Associated Lab Samples: 60153641001, 60153641002, 60153641003, 60153641004

Parameter	Units	Blank Result	Reporting Limit	Analyzed	Qualifiers
Naphthalene	ug/L	ND	0.50	09/30/13 19:37	
2-Fluorobiphenyl (S)	%	44	36-120	09/30/13 19:37	
Terphenyl-d14 (S)	%	58	29-134	09/30/13 19:37	

LABORATORY CONTROL SAMPLE: 1258788

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Naphthalene	ug/L	10	5.0	50	44-120	
2-Fluorobiphenyl (S)	%			46	36-120	
Terphenyl-d14 (S)	%			57	29-134	

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## QUALITY CONTROL DATA

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

QC Batch: WETA/26476 Analysis Method: EPA 300.0  
QC Batch Method: EPA 300.0 Analysis Description: 300.0 IC Anions  
Associated Lab Samples: 60153641001, 60153641002, 60153641003, 60153641004

METHOD BLANK: 1265087 Matrix: Water  
Associated Lab Samples: 60153641001, 60153641002, 60153641003, 60153641004

Parameter	Units	Blank Result	Reporting Limit	Analyzed	Qualifiers
Sulfate	mg/L	ND	1.0	10/04/13 17:37	

LABORATORY CONTROL SAMPLE: 1265088

Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Sulfate	mg/L	5	4.8	97	90-110	

MATRIX SPIKE & MATRIX SPIKE DUPLICATE: 1265089 1265090

Parameter	Units	60153603001 Result	MS Spike Conc.	MSD Spike Conc.	MS Result	MSD Result	MS % Rec	MSD % Rec	% Rec Limits	RPD	Max RPD	Qual
Sulfate	mg/L	1760	1000	1000	2620	2650	86	89	80-120	1	15	

MATRIX SPIKE SAMPLE: 1265091

Parameter	Units	60153603002 Result	Spike Conc.	MS Result	MS % Rec	% Rec Limits	Qualifiers
Sulfate	mg/L	1110	1000	2000	89	80-120	

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## QUALIFIERS

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

---

### DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to changes in sample preparation, dilution of the sample aliquot, or moisture content.

ND - Not Detected at or above adjusted reporting limit.

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PRL - Pace Reporting Limit.

RL - Reporting Limit.

S - Surrogate

1,2-Diphenylhydrazine (8270 listed analyte) decomposes to Azobenzene.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up

U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.

### BATCH QUALIFIERS

Batch: OEXT/40632

[M5] A matrix spike/matrix spike duplicate was not performed for this batch due to insufficient sample volume.

Batch: MSV/56540

[M5] A matrix spike/matrix spike duplicate was not performed for this batch due to insufficient sample volume.

Batch: MSV/56552

[M5] A matrix spike/matrix spike duplicate was not performed for this batch due to insufficient sample volume.

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..



## QUALITY CONTROL DATA CROSS REFERENCE TABLE

Project: 074925 Johnston Federal No. 4

Pace Project No.: 60153641

Lab ID	Sample ID	QC Batch Method	QC Batch	Analytical Method	Analytical Batch
60153641001	GW-074925-091713-CM-MW-1	EPA 3010	MPRP/24442	EPA 6010	ICP/19045
60153641002	GW-074925-091713-CM-MW-2	EPA 3010	MPRP/24442	EPA 6010	ICP/19045
60153641003	GW-074925-091713-CM-MW-3	EPA 3010	MPRP/24442	EPA 6010	ICP/19045
60153641004	GW-074925-091713-CM-MW-4	EPA 3010	MPRP/24442	EPA 6010	ICP/19045
60153641001	GW-074925-091713-CM-MW-1	EPA 3510C	OEXT/40632	EPA 8270C by SIM	MSSV/12908
60153641002	GW-074925-091713-CM-MW-2	EPA 3510C	OEXT/40632	EPA 8270C by SIM	MSSV/12908
60153641003	GW-074925-091713-CM-MW-3	EPA 3510C	OEXT/40632	EPA 8270C by SIM	MSSV/12908
60153641004	GW-074925-091713-CM-MW-4	EPA 3510C	OEXT/40632	EPA 8270C by SIM	MSSV/12908
60153641001	GW-074925-091713-CM-MW-1	EPA 5030B/8260	MSV/56540		
60153641002	GW-074925-091713-CM-MW-2	EPA 5030B/8260	MSV/56540		
60153641003	GW-074925-091713-CM-MW-3	EPA 5030B/8260	MSV/56540		
60153641004	GW-074925-091713-CM-MW-4	EPA 5030B/8260	MSV/56540		
60153641005	GW-074925-091713-CM-DUP	EPA 5030B/8260	MSV/56540		
60153641006	TB-074925-091813-CM-001	EPA 5030B/8260	MSV/56552		
60153641001	GW-074925-091713-CM-MW-1	EPA 300.0	WETA/26476		
60153641002	GW-074925-091713-CM-MW-2	EPA 300.0	WETA/26476		
60153641003	GW-074925-091713-CM-MW-3	EPA 300.0	WETA/26476		
60153641004	GW-074925-091713-CM-MW-4	EPA 300.0	WETA/26476		

## REPORT OF LABORATORY ANALYSIS

This report shall not be reproduced, except in full,  
without the written consent of Pace Analytical Services, Inc..





Sample Condition Upon Receipt  
ESI Tech Spec Client

WO#: 60153641



60153641

Client Name: COR CRA NM

Courier: Fed Ex ☒ UPS ☐ USPS ☐ Client ☐ Commercial ☐ Pace ☐ Other ☐

Tracking #: 8023 0627 9454 Pace Shipping Label Used? Yes ☒ No ☐

Custody Seal on Cooler/Box Present: Yes ☒ No ☐ Seals intact: Yes ☒ No ☐

Packing Material: Bubble Wrap ☒ Bubble Bags ☐ Foam ☐ None ☐ Other ☐

Thermometer Used: T-112 / T-194

Type of Ice: Water Blue ☐ None ☐ Samples received on ice, cooling process has begun.  
(circle one)

Cooler Temperature: 4.9

Date and initials of person examining contents: JS 9/20/13 1150

Temperature should be above freezing to 6°C

Chain of Custody present:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	1.
Chain of Custody filled out:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	2.
Chain of Custody relinquished:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	3.
Sampler name & signature on COC:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	4.
Samples arrived within holding time:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	5.
Short Hold Time analyses (<72hr):	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> N/A	6.
Rush Turn Around Time requested:	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> N/A	7.
Sufficient volume:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	8.
Correct containers used:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	
Pace containers used:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	9.
Containers intact:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	10.
Unpreserved 5035A soils frozen w/in 48hrs?	<input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A	11.
Filtered volume received for dissolved tests?	<input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A	12.
Sample labels match COC:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	
Includes date/time/ID/analyses	Matrix: <u>water</u>	13.
All containers needing preservation have been checked.	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	
All containers needing preservation are found to be in compliance with EPA recommendation.	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	14.
Exceptions: VOA, coliform, TOC, O&G, WI-DRO (water), Phenolics	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Initial when completed <u>JS</u> Lot # of added preservative
Trip Blank present:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	
Pace Trip Blank lot # (if purchased): <u>081213.3</u>		15.
Headspace in VOA vials (>6mm):	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> N/A	
		16.
Project sampled in USDA Regulated Area:	<input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A	17. List State:

Client Notification/ Resolution:

Copy COC to Client? Y ☐ N ☒

Field Data Required? Y / N

Person Contacted: \_\_\_\_\_ Date/Time: \_\_\_\_\_

Comments/ Resolution: \_\_\_\_\_

Project Manager Review: MXF

Date: 9/20/13

Temp Log: Record start and finish times when unpacking cooler, if >20 min, recheck sample temps.	
Start: <u>1140</u>	Start:
End: <u>1150</u>	End:
Temp: <u>1150</u>	Temp:



