

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYForm Approved,
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other Wildcat
well well

2. NAME OF OPERATOR
TransOcean Oil, Inc

3. ADDRESS OF OPERATOR 77002
1700 First City East, 1111 Fannin, Houston, Tx

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐	☐
FRACTURE TREAT	☐	☐
SHOOT OR ACIDIZE	☐	☐
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☐
ABANDON* TEMPORARY ☒	☐	☐
(other)		

5. LEASE
MOOC 142001021

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
ISLETA PUEBLO

7. UNIT AGREEMENT NAME
N/A

8. FARM OR LEASE NAME
ISLETA #4

9. WELL NO.
#1

10. FIELD OR WILDCAT NAME
Wildcat

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec 8, T8N R3E

12. COUNTY OR PARISH
Bernalillo

13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5264 G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Temporarily abandoned Well in order to determine if the hole has any further mechanical use to the exploration effort in this area (i.e. reenter and sidetrack).

1. Set cmt plug at 9700-9500' (100 sk CI "B" + 3% D-28 RET).
2. Set cmt plug at 8950-8750' (100 sk CI "B" + 3% D-28 RET).
3. Set cmt plug at 8400-8200' (100 sk CI "B" + 3% D-28 RET).
4. Set cmt plug at 5500-5200' (225 sk CI "B" NEAT).
5. Set cmt plug at 700-500' (125 sk CI "B" NEAT).
6. Set Dry Hole marker w/50 sks CI "B" NEAT at surface.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED J.M. CrewsTITLE Sr Drilling Engineer DATE 11/17/78

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: