



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No. **N. M. 039087**

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

MAY 16 1960

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 12

19 60

Well No. **1-14** is located **1650** ft. from **N** line and **990** ft. from **E** line of sec. **14**

NE 1/4 sec. 14 **6 N** **11 W** **N.M.P.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat **Valencia** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD of well is 4638'. 13-3/8" csg. set at 390' with cement circulated. 10-3/4" csg set at 1374' - mudded off. 8-5/8" csg set at 2558' and cemented with 75 sacks. Verbal instructions from Mr. McGrath (USGS Engineer at Farmington) were to spot cement plug from 4200' to 4300', one in surface pipe and to leave 4' pipe marked extending up from abandoned well head.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **SOUTHLAND ROYALTY CO.**

Address **P. O. Box 1515**

Midland, Texas

By **/s/ Alton C. Goodrich**

Title **District Production Supt.**