

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER- CARBON DIOXIDE & HYDROCARBONS		7. Unit Agreement Name
2. Name of Operator HNG FOSSIL FUELS COMPANY		8. Farm or Lease Name SAUBLE
3. Address of Operator P. O. BOX 1188, HOUSTON, TEXAS 77001		9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>1980</u> FEET FROM THE <u>NORTH</u> LINE AND <u>660</u> FEET FROM THE <u>EAST</u> LINE, SECTION <u>35</u> TOWNSHIP <u>27N</u> RANGE <u>24E</u> NMPM.		10. Field and Pool, or Wildcat WILDCAT
15. Elevation (Show whether DF, RT, GR, etc.) 6390 GR		12. County COLFAX

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	OTHER <u>Temporarily Abandoned</u> ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/25/79 T.D. 1629'. Set 1585' of 7" 20.00# K-55 ST& C R-3 casing at 1594KB.
Cemented w/75 sks. Halliburton Class H cement with 18% salt.
W.O.C.

10/1/79 T.D. 2568. Spotted 100 sks. Halliburton Class H cement plug
from bottom to 2050. P. O.H. w/drill pipe. R.I.H. in 6½" bit
and drill pipe. Washed and reamed tight spot at 1730 and on to
bottom. PBTD 2080.

10/2/79 R.I.H. with 4½" guideshoe and float collar, and set 473' of 5"
13.00# K-55 ST&C R-3 Liner. Bottom of shoe at 2073' KB. Top
of Liner at 1584. Cemented Liner w/20 sks. Halliburton Class H Neat
and 50 sks Class H with 18% salt. Bumped plug at 8:45 pm w/1000#

10/3/79 Rig Released and moving to new location. Cement Bond Log showed
top of cement at 1724' and bottom at 1980'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Richard Boehm TITLE Administrative Manager DATE 10/5/79

APPROVED BY Carl Mueg TITLE SENIOR PETROLEUM GEOLOGIST DATE 10/9/79

CONDITIONS OF APPROVAL, IF ANY: