

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-007-20096

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER Coal Methane

2. Name of Operator
Pennzoil Exploration and Production Company

3. Address of Operator
P.O. Box 2967, Houston, TX 77252

4. Well Location
Unit Letter M : 660 Feet From The South Line and 715 Feet From The West Line

Section 2 Township 30N Range 17E NMPM Colfax County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
8256 GR

7. Lease Name or Unit Agreement Name
Castle Rock South
3017

8. Well No.
021-M

9. Pool name or Wildcat
Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: Drilling completed ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-14-89 Spud
6-15-89 Drilled 14 3/4" hole to 44.5'. Set and cement 2 jts (44.5') 11 3/4", 42 lb. H-40, ST&C conductor w/140 sks class G w/3% CaCl @ 15.8 ppg.
6-16-89 Drilled 11" hole to 336'. Set and cement 12 jts (330.95') 8 5/8", 24 lb. J-55 ST&C casing w/175 sks class G w/2% CaCl @ 15.8 ppg. Cement to surface.
8-07-89 Test casing and BOP w/600 psi for 30 minutes. No pressure drop.
8-12-89 Drilled 7 7/8" hole to 1873'.
8-13-89 Set and cement 50 jts (1862.15') 5 1/2", 17 lb. J-55, LT&C casing w/350 sks silicalite @ 11.0 ppg. Bump plug w/1000 psi, Cement to surface. Waiting on completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE Operations Superintendent DATE 8-14-89

TYPE OR PRINT NAME L. D. Williamson

TELEPHONE NO. 505-376-2817

(This space for State Use)

APPROVED BY R. E. Johnson TITLE DISTRICT SUPERVISOR DATE 8-17-89

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

AUG 15 1989

OIL CONSERVATION DIV,
SANTA FE