

90-1
Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240
DISTRICT II
P.O. Drawer DD, Artesia, NM 88210
DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-007-20104
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Castle Rock 3017
8. Well No. 031 F
9. Pool name or Wildcat Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☐ OTHER Coal Methane
2. Name of Operator Pennzoil Exploration & Production Company
3. Address of Operator P.O. Box 2967, Houston, TX 77252
4. Well Location Unit Letter F : 2098 Feet From The North Line and 2070 Feet From The West Line Section 3 Township 30 N Range 17 E NMPM Colfax County
10. Elevation (Show whether DF, RKD, RT, GR, etc.) 8512 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐		CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: Drilling completed ☒	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/7/90 Spud. Drill 14 3/4" hole to 22'. Set 13 3/8" conductor.
5/8/90 Drill 12 1/4" hole to 335'. Set and cement 12 jts (327') 8 5/8", 24 lb. J-55, st&c casing w/225 sks class G w/ 2% CaCl @ 15.8 ppg. Bump plug w/500 psi. No cement at surface. Pump 25 sks Top Job @ 2130 W.O.C.
5/9/90 Test casing & BOP w/500 psi for 30 minutes. No pressure drop.
5/10/90 Drill 7 7/8" hole to 2168. Load hole with mud & log.
5/11/90 Set and cement 56 jts (2144') 5 1/2", 17 lb, J-55, lt&c casing w/315 sks silicalite @ 11.5 ppg. Returns to surface. Bump plug w/1200 psi @ 0300. Well shut in waiting on completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE Operations Superintendent DATE 5/14/90

TYPE OR PRINT NAME L. D. Williamson TELEPHONE NO 505-376-2817

(This space for State Use)

APPROVED BY R. E. Johnson TITLE DISTRICT SUPERVISOR DATE 5-15-90

CONDITIONS OF APPROVAL, IF ANY: