

90-3
Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Artesia, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-007-20106
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☐ GAS WELL ☐ OTHER Coal Methane	7. Lease Name or Unit Agreement Name Castle Rock 3118
2. Name of Operator Pennzoil Exploration & Production Company	8. Well No. 321 I
3. Address of Operator P.O. Box 2967, Houston, TX 77252	9. Pool name or Wildcat Wildcat
4. Well Location Unit Letter <u>I</u> : <u>1195</u> Feet From The <u>East</u> Line and <u>1950</u> Feet From The <u>South</u> Line Section <u>32</u> Township <u>31 N</u> Range <u>18 E</u> NMPM Colfax County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 8593 GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐		CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: <u>Drilling completed</u> ☒	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/1/90 Spud. Drill 14 1/4" hole to 22 ft. Set 13 3/8" conductor.
5/2/90 Drill 12 1/4" hole to 330'. Set and cement 12 jts (329') 8 5/8", 24 lb, J-55, st&c casing w/215 sks class G w/3% CaCl @ 15.8 ppg. Bump plug w/500 psi @ 0330.
5/3/90 Test casing and BOP w/500 psi for 30 min. No pressure drop.
5/4/90 Drill 7 7/8" hole to TD @ 2121'. Load hole with mud & log.
5/5/90 Set and cement 52 jts (1988') 5 1/2, 17 lb, J-55, lt&c casing w/265 sks silicalite @ 11.5 ppg. Returns to surface. Bump plug w/1100 psi @ 2100 hrs. Well shut in waiting on completion.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. D. Williamson TITLE Operations Superintendent DATE 5/14/90

TYPE OR PRINT NAME L. D. Williamson

TELEPHONE NO 505-376-2817

(This space for State Use)

APPROVED BY R. E. Johnson DISTRICT SUPERVISOR DATE 5-15-90

CONDITIONS OF APPROVAL, IF ANY: