

Submit 3 Copies To Appropriate District Office

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

District I

1625 N. French Dr. Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20107

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR D

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

8. Well No. 24

3. Address of Operator

P.O. BOX 190; RATON, NM 87740

9. Pool name or Wildcat

4. Well Location

Unit Letter F : 1713' feet from the NORTH line and 1753' feet from the WEST line

Section 32 Township 31N Range 18E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8684' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: RE-ENTER & COMPLETE ☒

12.

1/20-22/00 Drill cement plug 0'-60'. Drill cement & CIBP 1520'-1651'. Clean out to 1651'.

2/19/00 Perforate: 1952'-1957', 1915'-1919', 1883'-1887', 1850'-1854', 1836'-1840', 1802'-1806', 1789'-1793', 1777'-1781', 1672'-1681'. All 4spf.

2/23/00 Stimulate: Interval 1836'-1957' with 25000# 20/40 & 100000# 12/20 Sand with 550000 scf N2 70 Quality foam.

2/25/00 Stimulate: Interval 1777'-1806' with 25000# 20/40 & 15000# 12/20 Sand with 275000 scf N2 70 Quality foam.

2/27/00 Stimulate: Interval 1672'-1681' with 25000# 20/40 & 85000# 12/20 Sand with 520000 scf N2 70 Quality foam.

3/01-05/00 Cleaned out to 2058'. Ran After frac Log (Patterson). Clean out to 2058'. Ran tubing & rods. Well ready for production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Joel L. Pettit TITLE WELL SITE SUPERVISOR DATE 08/17/00

Type or print name: JOEL L. PETTIT Telephone No.: (505) 445-4620

(This space for State use)

APPROVED BY Ry E. Johnson TITLE DISTRICT SUPERVISOR DATE 8/25/00

Conditions of approval, if any