

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30-007-20113

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR 'A'

8. Well No. 05

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other COALBED METHANE

2. Name of Operator

SONAT RATON, LLC

3. Address of Operator

P.O. BOX 190; RATON, NM 87740

4. Well Location

Unit Letter G : 1548' feet from the NORTH line and 1363' feet from the EAST line

Section 36 Township 32N Range 19E NMPM COFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8092' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: RESTORATION ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

ROY JOHNSON GRANTED VERBAL PERMISSION AND INSTRUCTIONS TO P&A THIS WELL.

06/28/99 MIRU Leed rig. TIH w/tubing. Halliburton set 40 sk cement plug from 2150'-2000' and a 75 sk plug from 1061'-700'. TOH & WOC.

06/29/99 Tagged second plug at 1148'. Halliburton set another 75 sk plug from 1063'-700'. TOH & WOC.

06/30/99 Tagged plug at 750'. Halliburton set the shoe plug from 400'-300'. (8 5/8" shoe at 354'.) WOC.
Tried to fill the hole and was not successful.
Obtained permission from Roy Johnson to set CIBP at the bottom of the surface pipe.

07/01/99 Set CIBP at 325'. Dumped 10' of cement on top of plug. Halliburton set a 10 sk surface plug from 30'-0'.

RESTORATION: The location has been restored back to or very close to the original state as far as dirt work.
The location has been seeded and grass has started to grow.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE SR. PETROLEUM ENGINEER DATE 10/04/99

Type or print name: DON LANKFORD

Telephone No.: (505) 445-4621

(This space for State use)

APPROVED BY Roy Johnson
Conditions of approval, if any:

TITLE DISTRICT SUPERVISOR DATE 10/14/99