

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-007-20116

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR 'A'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other Coalbed Methane

2. Name of Operator

SONAT RATON, L.L.C.

3. Address of Operator

P.O. Box 190; Raton, NM 87740

8. Well No. - 07

9. Pool name or Wildcat

4. Well Location

Unit Letter B : 1074 feet from the North line and 2276 feet from the East line

Section 01

Township 31N

Range 19 E

NMPM Colfax

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

8275'(GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOE ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

07/25/99: Ran and set 7", 23#, J-55 casing at 5745'. Cement with 330 sx. RDMO United Rig #9.

08/02/99: MIRU Leed Rig #91

08/15/99: Wash to T.D. of 6620'. Condition hole.

08/16/99: Run open hole logs. Ran and set 5", 18#, P-110 liner @ 6619' (Top of liner 5562').

08/17/99: Cement with 200 sx.

08/18/99: CO liner to 6575'.

08/20/99: Squeeze liner top with 200 sx cement.

08/21/99: Perforate 4370-72 with 45PF. Cement with 500 sx.

08/22/99: Perforate 3150-52' with 4 SPF. Set cement retainer at 3039'. Cement with 500 sx. with 60-100% returns.

08/26/99: C.O. to linertop @ 5562'. Run CBL

08/27/99: C.O. to 6575'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Wael W. Patscher

TITLE

Petroleum Engrs. Advisor

DATE

9/2/99

Type or print name

Wael W. Patscher

Telephone No. 505-445-462

(This space for State use)

APPROVED BY

Ry E Johnson

TITLE

DISTRICT SUPERVISOR

DATE

9/27/99

Conditions of approval, if any: