

189514 Submit 3 Copies To Appropriate
District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20140
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: VPR A
8. Well No. 31
9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☐ Gas Well ☒ Other Coalbed Methane	
2. Name of Operator Sonat Raton, L.L.C.	
3. Address of Operator P.O. Box 190, Raton, NM 87740	
4. Well Location Unit I : 1464' feet from the SOUTH line and 551 feet from the EAST line Section 34 Township 32N Range 19E NMPM COLFAX County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐	REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐	CASING TEST AND CEMENT JOB ☐
OTHER: ☐	OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

02/01/00: Spud @9:00 a.m. Drill 11" surface hole to 350'. Run 16 jts of 8 5/8" and set at 336'. Cement with 100 sks of Midcon plus additives. Circulated 5 bbls of slurry to surface. WOC

02/02/00: Drill 7 7/8" hole to 2535'.

02/02/00: Drill 7 7/8 hole to TD @ 2535'. Reeves ran open hole logs. RDMO Pense Drilling, MIRU Leed Well Service.

02/03/00 Run 5 1/2" casing. Set and cement at 2507'. Cemented with 325 sacks of Midcon 2 plus additives. Circulated 15 bbls of cement to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE Sr. Petroleum Engineer DATE 2/10/00

Type or print name Donald R. Lankford Telephone No. (505)445-4621

(This space for State use)

APPROVED BY R. E. Johnson TITLE DISTRICT SUPERVISOR DATE 2/14/00
Conditions of approval, if any: