

180514 Submit 3 Copies To Appropriate
District Office
District I
1625 N. French Dr., Hobbs, NM 87249
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-007-20162
1. Type of Well: Oil Well ☐ Gas Well ☒ Other Coalbed Methane		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator EL PASO ENERGY RATON, L.L.C.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 190, Raton, NM 87740		7. Lease Name or Unit Agreement Name: VPR A
4. Well Location Unit <u>K</u> <u>1558'</u> feet from the <u>SOUTH</u> line and <u>1459'</u> feet from the <u>WEST</u> line Section <u>02</u> Township <u>31N</u> Range <u>19E</u> NMPM COLFAX County		8. Well No. <u>27</u>
10. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>8290' (GR)</u>		9. Pool name or Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: COMPLETION ☒

12.
2/11/00: Ran CBL (Patterson Wireline). TOC 2150'.
2/23/00: Perforate 2080'-2081'. Cement sqzd with 130 sxs.
3/13 -15/00: Ran CBL. TOC 1598'. Cleaned out to 2267'.
5/16-31/00: Set retainer @ 2000'. Cement sqzd w/ 50 sxs. Perforate 1560'-1561'. Cement sqzd with 200 sxs. Ran CBL. TOC 1450'.
Perforate 1408'-1409'. Cement sqzd with 160 sxs. Cleaned out to 2095'. Ran CBL. TOC 630'. Drld out to 2375'.
6/3/00: Ran Century Log 2500'-2000'. Pumped 50 sxs. cement from surface via 5 1/2" X 8 5/8" annulus.
6/8-9/00: Ran packer. Tested sqz perf 2080'-2081' to 1500#. Bled to 400# in 5 minutes. Tested sqz perfs 1560'-1561'. Pumped in @ 0.125 bpm with 500 #. Tested sqz perfs 1408'-1409'—OK. Clean out to 2412'. Set packer @ 2412'.
6/10/00: Stimulate open hole interval 2267'-2412': 30000# 20/40 & 75000 12/20 Sand. 480000 scf N2 70 Quality Foam.
6/11/00: Perforate: 2203'-2205', 2198'-2200', 2186'-2188'. All 4 spf.
6/13/00: Stimulate: 20000# 20/40 & 25000# 12/20 Sand. 270000 scf N2 70 Quality foam.
6/14/00: Perforate: 1403'-1407', 1356'-1360', 1342'-1348', 1300'-1306', 1285'-1289'. All 4 spf.
6/15/00: Stimulate: 25000# 20/40 & 50000# 12/20 Sand. 235000 scf N2 70 Quality foam.
Perforate: 1206'-1208', 1191'-1193', 1122'-1126'. All 4spf.
Stimulate: 25000# 20/40 & 50000# 12/20 Sand. 275000 scf N2 70 Quality foam.
6/16/00: Perforate: 994'-996', 985'-988', 977'-979', 966'-968', 921'-923', 880'-883'. All 4spf.
Stimulate: 25000# 20/40 & 75000# 12/20 Sand. 305000 scf N2 70 Quality foam.
6/19-25/00: Cleaned out to 2412'. Ran tubing & rods. Well ready to produce.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Joel L. Pettit TITLE Well Site Supervisor DATE 8/15/00

Type or print name JOEL L. PETTIT Telephone No. (505)445-4620

(This space for State use)

APPROVED BY Ry Johnson TITLE DISTRICT SUPERVISOR DATE 8/25/00
Conditions of approval, if any: