

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 87240
 District II
 811 South First, Artesia, NM 87210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised March 25, 1999

OIL CONSERVATION DIVISION
 2040 South Pacheco
 Santa Fe, NM 87505

WELL API NO. **30-007-20177**

5. Indicate Type of Lease
 STATE FEE

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:
VPR D

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
 1. Type of Well:
 Oil Well Gas Well Other

2. Name of Operator
SONAT RATON, LLC

3. Address of Operator
 P.O. BOX 190; RATON, NM 87740

4. Well Location
 Unit Letter K : 1542' feet from the South line and 1695' feet from the West line
 Section 6 Township 30N Range 18E NMPM COFAX County

8. Well No. **9**

9. Pool name or Wildcat

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8427' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12.

3/10/00 Spud well at 9:00 PM. Drill 11" Surface hole.

3/11/00 Run 8-5/8" Casing to 337'. Cement with Halliburton. Pump 100 sx Midcon 2 + adds. 8 bbls cement to surface. WOC 8 hrs. Drill 7-7/8" hole.

3/12/00 Drill 7-7/8" hole to Td @ 1990'. Log Wellbore. Run 5-1/2" casing to 1920'. Cement with BJ. Mix and Pump 300 sx of cement. Circulated approx. 45 bbls of cement to surface. Release rig.

3/25/00 Rig up Patterson Wireline. Run CBL. TOC = 25'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE DR Lankford TITLE SR. PETROLEUM ENGINEER DATE 3/25/00

Type or print name: DON LANKFORD Telephone No.: (505) 445-4621

(This space for State use)

APPROVED BY Ry E Johnson TITLE **DISTRICT SUPERVISOR** DATE 4/4/00
 Conditions of approval, if any: