

Submit 3 Copies To Appropriate District Office

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO. 30-007-20179
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: VPR D
8. Well No. 13
9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well Gas Well Other COALBED METHANE

2. Name of Operator
EL PASO ENERGY RATON, LLC

3. Address of Operator
P.O. BOX 190; RATON, NM 87740

4. Well Location
Unit Letter A : 1037' feet from the North line and 1169' feet from the East line
Section 1 Township 30N Range 17E NMPM COFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
8373' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK PLUG AND ABANDON

TEMPORARILY ABANDON CHANGE PLANS

PULL OR ALTER CASING MULTIPLE COMPLETION

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING

COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT

CASING TEST AND CEMENT JOB

OTHER: COMPLETION

12.

04/15/00 Ran CBL. Confirmed cement was not circulated to surface.

06/21-30/00 Perforate squeeze holes 1721-1722'. Cement sqzd w/190 sxs. No cement to surface. Attempted CBL. Tagged @ 1300'. TOC @ 250'. Cleaned out to 1820' Tested csg to 1500# - OK. Ran CBL & tagged @ 1815. TOC @ 250'. Ran Century Log 1815'-1200'.

07/29/00 Perforate: 1726-1732' (4spf).

07/31/00 Stimulate: 15000# 20/40 & 50000 # 12/20 Sand. 570000 scf N2 70 Quality Foam.
Perforate: 1626'-1630', 1645'-1649', 1679'-1683'. All 4spf.
Stimulate: 20000# 20/40 & 50000 # 12/20 Sand. 420000 scf N2 70 Quality Foam.
Perforate: 1459'-1464. (4spf).
Stimulate: 15000# 20/40 & 30000 # 12/20 Sand. 405000 scf N2 70 Quality Foam.

08/02-11/00 Clean out to 1815'. TIH with Production Tubing and Rods. Well ready to be electrified.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Joel L. Pettit TITLE WELL SITE SUPERVISOR DATE 8/15/00

Type or print name: JOEL L. PETTIT Telephone No.: (505) 445-4620
(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 8/18/00
Conditions of approval, if any: