

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

WELL API NO. 30-007-20185
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: <b>VPR B</b>
8. Well No. <b>5</b>
9. Pool name or Wildcat
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8290' (GR)

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well  Gas Well  Other

2. Name of Operator  
**SONAT RATON, LLC**

3. Address of Operator  
P.O. BOX 190; RATON, NM 87740

4. Well Location  
Unit Letter  K :  1615  feet from the  South  line and  1403  feet from the  West  line  
Section  35  Township  30N  Range  18E  NMPM COLFAX County

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

<b>NOTICE OF INTENTION TO:</b> PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPLETION <input type="checkbox"/> OTHER: <input type="checkbox"/>	<b>SUBSEQUENT REPORT OF:</b> REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>
---	--

12.

5/03/00 Spud well at 12:00 PM. Drill 11" hole to 350'. Run 8-5/8" casing to 336'. BJ pumped 110 sx Type III +Add. 8 Bbls cement returned to surface. WOC.

5/04/00 WOC. Drill to TD of 2750'. RU Patterson and log 2728' to 337'

5/05/00 Run 5-1/2" casing to 2708'. Cement with BJ. Mix and Pump 275 sx of cement. 1 bbl cement to surface. Release rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  DR Lankford  TITLE  SR. PETROLEUM ENGINEER  DATE  5/18/00

Type or print name: DON LANKFORD Telephone No.: (505) 445-4621  
(This space for State use)

APPROVED BY  R. E. Johnson  TITLE  DISTRICT SUPERVISOR  DATE  5/19/00   
Conditions of approval, if any: