

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Oil Conservation Division
2040 South Pacheco
Santa Fe, NM 87505

Form C-101
Revised March 17, 1999

Submit to appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

¹ Operator Name and Address El Paso Energy Raton, L.L.C. P.O. Box 190 Raton, NM 87740		² OGRID Number 180514
³ Property Code 25179	⁵ Property Name Vermejo Park Ranch (VPR)	³ API Number 30-007-20218
		⁶ Well No. VPR D-39

⁷ Surface Location									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
K	8	30N	18E	K	1735'	SOUTH	1356'	WEST	COLFAX

⁸ Proposed Bottom Hole Location If Different From Surface									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
⁹ Proposed Pool 1 CASTLE ROCK PARK-VERMEJO GAS (97046)					¹⁰ Proposed Pool 2				

¹¹ Work Type Code N	¹² Well Type Code G	¹³ Cable/Rotary ROTARY/AIR	¹⁴ Lease Type Code P	¹⁵ Ground Level Elevation 8522' (GL)
¹⁶ Multiple No	¹⁷ Proposed Depth 2500'	¹⁸ Formation Trinidad	¹⁹ Contractor Not Available	²⁰ Spud Date January 25, 2001

²¹ Proposed Casing and Cement Program					
Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
11"	8 5/8"	23#	300'	100 sx.	SURFACE
7 7/8"	5 1/2"	15.50#	2500'	300 sx.	SURFACE

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

1. Drill 11" hole to +/- 310' with air.
2. Set 8 5/8" surface casing at +/- 300' and cement to surface.
3. Drill 7 7/8" hole to 2500' with air. Run open hole logs.
4. Set 5 1/2" production casing to TD and cement to surface. Cement volumes calculated off open hole logs.
5. Perforate and stimulate the Vermejo Coals. Clean out well bore and run production equipment.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature: DR Lankford

Printed name: Donald R. Lankford

Title: Senior Petroleum Engineer

Date: 11/07/2000

Phone: (505) 445-4620

OIL CONSERVATION DIVISION

Approved by: [Signature]

Title:

DISTRICT SUPERVISOR

Approval Date: 11/7/00

Expiration Date: 11/7/01

Conditions of Approval:

Attached ☐

Certificate Number 5108