

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20222

5. Indicate Type of Lease
STATE FEE X

State Oil & Gas Use No. []

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL [] GAS WELL [] DRY [] OTHER X COALBED METHANE

b. Type of Completion:
NEW WORK PLUG DIFF. RESVR. OTHER
WELL [] OVER [] DEEPEN [] BACK []

7. Lease Name or Unit Agreement Name
VPR D

2. Name of Operator
EL PASO ENERGY RATON, L.L.C.

8. Well No.
43

3. Address of Operator
PO BOX 190
RATON, NEW MEXICO 87740

9. Pool name or Wildcat
Castle Rock Park - Vermejo Gas

4. Well Location

Unit Letter C : 1015 Feet From The North Line and 2143 Feet From The West Line

Section 09 Township 30N Range 18E NMPM COLFAX County
10. Date Spudded 02/23/01 11. Date T.D. Reached 2130' 12. Date Compl. (Ready to Prod.) 06/18/01 13. Elevations (DF& R(B. RT, GR, etc.) 8340' 14. Elev. Casinghead 8340'

15. Total Depth 2130' 16. Plug Back T.D. 2053' 17. If Multiple Compl. How Many Zones? 18. Intervals Drilled By 0 - TD 19. Producing Interval(s), of this completion - Top, Bottom, Name 1644' - 1921' VERMEJO COALS 20. Was Directional Survey Made No

21. Type Electric and Other Logs Run

Array Induction, Compensated Density, and Sector Bond Log.

21. Was Well Cored
No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24 lb.	315'	11"	100 sx.	None
5 1/2"	15.5 lb.	2081'	7 7/8"	265 sx.	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	25. TUBING RECORD
					SIZE DEPTH SET PACKER SET
					2 7/8" 1957' N/A

26. Perforations:

1917' - 1921' Shot 4 SPF, 16 holes
1868' - 1870', Shot 4 SPF, 8 holes
1824' - 1827', 1810' - 1812' Shot 4 SPF, 8 holes Vermejo Coals
1739' - 1742' Shot 4 SPF, 12 holes
1688' - 1691', 1680' - 1682' Shot 4 SPF, 8 holes
1644' - 1646', 1654' - 1660' Shot 4 SPF, 24 holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED
1644' - 1921' 202,825 lbs 16/30 mesh sand

28. PRODUCTION

Date First Production 06/22/01	Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/045 pc pump. Flowing gas up 5 1/2" casing				Well Status (Prod. or Shut-in) Prod.		
Date of Test 06/22/01	Hours Tested 24 Hours	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 40	Water - Bbl. 20	Gas - Oil Ratio N/A
Flow Tubing Press.	Casing Pressure 100 psi	Calculated 24- Hour Rate	Oil - Bbl N/A	Gas - MCF 40	Water - Bbl. 20	Oil Gravity - API - (Corr.) N/A	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold, used for fuel

Test Witnessed By:

Mike Potter

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature: William M. Ordemann

Printed
Name: William M. Ordemann

Title: Engineer

Date: 07/27/01

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anyh	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Ozite
T. Gfiorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T. Raton - Surface 0'
T. Blinebry	T. Gr. Wash	T. Morrison	T. Vermijo 1,638'
T. Tubb	T. Delaware Sand	T. Todillo	T. Trinidad 1,940'
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet

LITHOLOGY RECORD

(Attach additional sheet if necessary)

[illegible]