

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO. **30-007-20235**

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR B

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190; RATON, NM 87740

8. Well No. **31**

9. Pool name or Wildcat

4. Well Location

Unit Letter G : 1511 feet from the North line and 1672 feet from the East line

Section 02 Township 29N Range 18E NMPM County COLFAX

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

8194' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐ **COMPLETION** ☒

12.

05/17/01 Patterson ran a Cement Bond Log. PBTD at 2707'. TOC at the surface.

05/25/01 Patterson perf'd 1st stage: 2630' - 2632'

Halliburton Cobra frac'd 1st stage: Pumped 169 gals 7.5% HCL acid, 70% quality nitrogen foam with 17,000 lbs 16/30 sand W/ATP 5453 psi, ISIP 1450 psi.

Patterson perf'd 2nd stage: 2587' - 2593'

Halliburton Cobra frac'd 2nd stage: Pumped 250 gals 7.5% HCL acid, 70% quality nitrogen foam with 21,000 lbs 16/30 sand W/ATP 7239 psi, ISIP 5900 psi.

Patterson perf'd 3rd stage: 2563' - 2565'

Halliburton Cobra frac'd 3rd stage: Pumped 225 gals 7.5% HCL acid, 70% quality nitrogen foam with 17,000 lbs 16/30 sand W/ATP 7113 psi, ISIP 5600 psi.

Patterson perf'd 4th stage: 2413' - 2417'

Halliburton Cobra frac'd 4th stage: Pumped 277 gals 7.5% HCL acid, 70% quality nitrogen foam with 23,419 lbs 16/30 sand W/ATP 6786 psi, ISIP 5500 psi.

Patterson perf'd 5th stage: 2381' - 2383'

Halliburton Cobra frac'd 5th stage: Pumped 158 gals 7.5% HCL acid, 70% quality nitrogen foam with 7,200 lbs 16/30 sand W/ATP 6654 psi, ISIP 4900 psi.

06/14/01 Well is ready to be put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William M. Ordemann TITLE Engineer DATE 08/01/01

Type of print name: William M. Ordemann

Telephone No.: (505) 445-6724

(This space for State use)

APPROVED BY [Signature] TITLE **DISTRICT SUPERVISOR** DATE 8/14/01

Conditions of approval, if any: