

Submit To Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1009 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-105
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-007-20253

5. Indicate Type of Lease

STATE FEE X

State Oil & Gas ☐ se No. ☒

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well
OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER X COALBED METHANE

b. Type of Completion:

NEW WORK PLUG DIFF.
WELL ☒ OVER ☐ DEEPEN ☐ BACK ☐ RESVR. ☐ OTHER

7. Lease Name or Unit Agreement Name

VPR E

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

8. Well No.

11

3. Address of Operator

PO BOX 190
RATON, NEW MEXICO 87740

9. Pool name or Wildcat

Stubblefield Canyon Raton - Vermejo Gas

4. Well Location

Unit Letter H 1343 feet from the North Line and 996 feet from the East Line

Section 05 Township 31N Range 19E NMPM COLFAX County

10. Date Spudded

03/21/01

11. Date T.D. Reached

03/24/01

12. Date Compl. (Ready to Prod.)

07/22/01

13. Elevations (DF& R(B, RT, GR, etc.)

8592'

14. Elev. Casinghead

592'

15. Total Depth

2735'

16. Plug Back T.D.

2622'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools
0 - TD

Cable Tools
None

19. Producing Interval(s), of this completion - Top, Bottom, Name

1172' - 2496' VERMEJO COALS

20. Was Directional Survey Made
No

21. Type Electric and Other Logs Run

Array Induction, Compensated Density, and Cement Bond Log

21. Was Well Cored
No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24 lb.	323'	11"	100 sx.	None
5 1/2"	15.5 lb.	2647'	7 7/8"	410 sx.	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	2541'	N/A

26. Perforations

2489' - 2496' Shot 4 SPF, 28 Holes

2417' - 2419', 2428' - 2431' Shot 4 SPF, 20 Holes

2332' - 2334' Shot 4 SPF, 8 Holes

2271' - 2273' Shot 4 SPF, 8 Holes

1964' - 1966' Shot 4 SPF, 8 Holes

1926' - 1928' Shot 4 SPF, 8 Holes

1276' - 1278', 1284' - 1292' Shot 4 SPF, 40 Holes

1232' - 1240' Shot 4 SPF, 32 Holes

1172' - 1174', 1182' - 1184' Shot 4 SPF, 16 Holes

Vermejo Coals

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED

1172' - 2496' 334,331 lbs 16/30 mesh sand

28. PRODUCTION

Date First Production	Production Method (Flowing, gas lift, pumping - Size and type pump)	Well Status (Prod. or Shut-in)
08/01/01	Pumping water up 2 7/8" tubing w/095 pc pump. Flowing gas up 5 1/2" casing.	Prod.

Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
08/01/01	24 Hours	Full 2"		N/A	32	50	N/A
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
	40 psi		N/A	32	50	N/A	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold, used for fuel

Test Witnessed By:

Mike Potter

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature:  Printed Name: William M. Ordemann Title: Engineer Date: 08/13/01

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or reopened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in triplicate except on state land, where six copies are required. See Rule 1105.

Southeastern New Mexico		Northwestern New Mexico	
T. Anyh	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
3. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Ozite
T. Gortola	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T. Raton - Surface
T. Blinebry	T. Gr. Wash	T. Morrison	T. Vermajo
T. Tubb	T. Delaware Sand	T. Todillo	T. Trinidad
T. Drinkard	T. Bone Springs	T. Entrada	
T. Abo		T. Wingate	
T. Wolfcamp		T. Chinle	
T. Penn		T. Permian	
T. Cisco (Bough C)		T. Penn "A"	

No. 1, from	to	No. 3, from	to
No. 2, from	to	No. 4, from	to

include data on rate of water inflow and elevation to which water rose in hole.

LITHOLOGY RECORD (Attach additional sheet if necessary)

[illegible]