

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 South St. Frances, Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
1220 South St. Frances  
Santa Fe, NM 87505

WELL API NO.

30-007-20266

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR D

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other ☒ Coalbed Methane

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. Box 190, Raton, NM 87740

8. Well No.

45

9. Pool name or Wildcat

4. Well Location

Unit Letter C : 841.0 feet from the North line and 1758.1 feet from the West line

Section 36 Township 31N Range 17E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

8166' (GL)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: AMENDED ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).  
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01/08/02 Spud @ 5:00 p.m. Drill 11" surface hole to 335'. Run 10 jts. of 8 5/8", J-55, 23 ppf ST&C casing to 328'.

01/08/02 Halliburton mixed and pumped 85 sx Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 50 psi with 6% salt, 5#/sx gilsonite, and .3% versaset. Circulate 2 bbls of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.

01/09/02 Drill 7 7/8" hole from 335' - 1630'. Reached TD 1630' at 4:15 p.m.

01/09/02 RU Schlumberger & log well. MIRU Leed. Ran 50 jts. of 5 1/2", M-50, 15.5 ppf LT&C casing to 1579'.

01/09/02 MIRU Halliburton. Mix and pump 20 bbls gel pre flush at 3 bpm with 0 psi, 5 gal LGC-8, 120# magmafiber, 100# baracarb with 5 bbls water spacer. Pumped 191 sx Midcon II PP, 13 ppg, yield 2.03 at 3 bpm with 15 psi, 6% salt, 2 lb/sx Granulite, 5 lb/sx Gilsontite, .2% Versaset and .1% Super CBL. Plug down @ 5:15 a.m. on 01-10-02 with 2000 psi. Partial returns with no cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William M. Ordemann TITLE Engineer DATE 02-05-02

Type or print name William M. Ordemann

Telephone No. (505) 445-6724

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 4/5/02

Conditions of approval, if any: